




**4" FIRE PRO - FIRE RATED DOWNLIGHT**  
OS SERIES / 2000 LUMENS MAX



A	B	C	D	S1	S2
9.5 241.3 mm	.625 15.9 mm	17.2 436.9 mm	25.1 637.5 mm	3.8 96.5 mm	5.4 137.2 mm

**FPE4SQLEDOS - TRIM FLANGE / NON-IC RATED**

**APPLICATION**

Fire Pro 4" LED recessed square open aperture downlight for fire rated ceilings.

**FEATURES**

60 minutes rated firebox enclosure. Two-stage optical system for smooth light distribution. Zhaga International Standard LED module for ease of maintenance and replacement. Tool-less LED module, driver and J-Box access. Multi-Bar mounting brackets. Posi-lock trim retention torsion springs. Integral 0.625" collar.

**TRIM FINISH**

A variety of architectural powdercoat and anodized finishes are available.

Matte white flange is standard.

**ELECTRONICS**

LED module features high brightness white Osram LEDs. 3-step MacAdam Ellipse binning and CRI 84 minimum. Full range of electronic 120V/277V and dimming drivers.

**CONSTRUCTION**

Housing / frame constructed of #20 ga. galvanized steel. Self-Flanged one piece trim die-cast high purity aluminum and finished to specification. Extruded and machined 6063-H32 aluminum heatsink. T.I.M. gasket for optimal thermal management.

**CODE COMPLIANCE**

ASTM E119-05a, UL 263, UBC 7-1, NFPA 251, ANSI A2.1. Certified by Omega Point Laboratories. Certified by Intertek and Warnock Hersey. BAA Compliant. Non-IC rated. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. LM79/LM80/TM21 data available. Optional Wet location. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE / LUMENS DATA		
PART NUMBER	SOURCE LUMENS <sup>1</sup>	SYSTEM WATTS
FPE4SQLEDOS10L	1100	11
FPE4SQLEDOS15L	1500	13
FPE4SQLEDOS20L	2000	20

SERIES	LUMENS <sup>1</sup>	CCT	DRIVER / VOLTAGE <sup>2</sup>	OPTIONS <sup>3</sup>	FIREBOX	TRIM	FINISH <sup>5</sup>	TRIM OPTIONS
FPE4SQLEDOS	10L	1100 Lm	27K 2700K	E Electronic Driver DS2W1 1%, ELV/MLV, 120V DO10 10%, 0-10V DS10 1%, 0-10V	1 120V 2 277V	H12 12" - 24" Expandable Bars FB2012 60 Minutes Rated Enclosure	CA0244OS	SO <sup>6</sup> Micro Prism Solite™ Lens GL Clear Glass Lens FG Frosted Glass Lens Gasket WL Wet Location PF <sup>7</sup> Polished Flange AMB Anti-Microbial Finish
	15L	1500 Lm	30K 3000K					
	20L	2000 Lm	35K 3500K					
			40K 4000K					
				FS Fusing CR Corrosion Resistant PR <sup>8</sup> Deep Ceiling Extension GR Goof Ring AMB Anti-Microbial Finish	MB Matte Black SG Semi-Diffuse HZ Haze Full Diffuse PT Platinum Silver BZ Bronze OB Oil Rubbed Bronze CH Charcoal AS Anodic Sapphire AN Anodic Natural AC Anodic Champagne AZ Anodic Bronze AK Anodic Black AM Anodic Malachite SN Sun Gold CO Copper Metallic GH Graphite CC <sup>9</sup> Custom Color			

**EXAMPLE:** FPE4SQLEDOS10L35KE1/FB2012/CA0244OSMWSO

**NOTES:**  
1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 See Product Options Page for Details 4 Contact Factory 5 Inside Trim and Flange Will Match Color Specified 6 Standard Finish 7 Contact Factory for Special Finishes 8 Standard Lens 9 Flange and Reflector Same Finish



PROJECT: \_\_\_\_\_  
TYPE: \_\_\_\_\_



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.