




4" ROUND WALL WASH

PC SERIES / 3000 LUMENS



A	B	C	D	E	F
5.1	.625	4.0	5.75	9.5	11.14
129.5 mm	15.88 mm	101.6 mm	146.1 mm	241.3 mm	283.0 mm

RWFO4PC - TRIM FLANGE / NON-IC RATED

APPLICATION

Versatile 4" Round aperture recessed LED wall wash with a wide range of lumens and control options.

FEATURES

Two-stage optical system for smooth light distribution and focus control. Quick change LED module with interchangeable optics for job site adjustment and fixture maintenance. Shallow plenum design. Tool-less driver and j-box access. Posi-lock trim retention torsion springs. See RWZO4 series for trimless plaster or wood ceiling.

TRIM FINISH

A variety of architectural powdercoat and anodized finishes are available.

Matte white flange is standard.

ELECTRONICS

LED module features high brightness Phillips LEDs. 3-step MacAdam Ellipse binning and 80 and 90 CRI available. Variety of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Housing/frame constructed of #20 ga. galvanized steel to resist corrosion. Self-Flanged one piece trim spun from 0.063" thick high purity aluminum and finished to specification.

CODE COMPLIANCE

BAA Compliant. Non-IC rated. UL certified to meet US and Canadian standards. Suitable for dry or damp locations. Optional Wet location. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE TO LUMENS UPDATE

CURRENT PART NUMBER EXAMPLE	SOURCE LUMENS ¹	SYSTEM WATTS
RWFO4PC10L	1100	15.2
RWFO4PC20L	2100	23.2
RWFO4PC30L	3000	31.0

SERIES	LUMENS ¹	CCT	OPTICS	DRIVER / VOLTAGE ²	OPTIONS ³	TRIM	FINISH	TRIM OPTIONS ⁵	
RWFO4PC	80 CRI		XW Extra Wide	E_ Electronic Driver DS10_ 10%, 0-10V DO10_ 1%, 0-10V	1 120V 2 277V	BH27 ⁴ 27" Solid Bars H12 12" - 24" Expandable Bars H06 6" - 12" Expandable Bars CB24 24" C-Channel Bars EM 7W Emergency Battery Test Switch Remote	RW4FPC ⁵	SG ⁶ Semi-Diffuse HZ Haze Full Diffuse MW Matte White MB Matte Black PT Platinum Silver OB Oil Rubbed Bronze CH Charcoal AC Anodic Champagne AS Anodic Sapphire AM Anodic Malachite SN Sun Gold CO Copper Metallic GH Graphite AMB Anti Microbial Finish CC ⁷ Custom Color	
	10L 1100 Lm	27K 2700K							SKX ⁸ Linear Wall Wash Lens
	20L 2100 Lm	30K 3000K							SKW Linear Wall Wash Lens
	30L 3100 Lm	35K 3500K							Wet Location
		40K 4000K							PF ¹⁰ Polished Flange
	90 CRI								
10L 1000 Lm	27HK 2700K								
20L 2000 Lm	30HK 3000K								

EXAMPLE: RWFO4PC10L35KWDE1/BH27/RW4FPCMWSKX

NOTES:
 1 Nominal Source Lumens at Any CCT 2 Contact Factory for Additional Options 3 See Product Options Page for Details 4 Standard Bar Hangers 5 "F" Indicates Self-Flange Trim, Matte White Standard 6 Standard Finish
 7 Contact Factory for Special Finishes 8 Contact Factory for Special Lenses/Louvers 9 Standard Lens 10 Flange and Reflector Same Finish



PROJECT: _____
 TYPE: _____



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.