



**BRISTOL**  
**DAMP LOCATION**  
 CAFÉS

PROJECT: \_\_\_\_\_

QUANTITY: \_\_\_\_\_ TYPE: \_\_\_\_\_



FP1906GV  
 BZ - Bronze  
 MBI - Matte Black Interior



FP1906GV  
 AK - Anodic Black  
 MWI - Matte White Interior



FP1906GV  
 PT - Platinum Silver  
 MWI - Matte White Interior



FP1906GV  
 GH - Graphite  
 GBI - Gloss Black Interior

SERIES	LUMENS <sup>1</sup>	CCT	DRIVER / DIMMING <sup>2</sup>	ACCESSORIES	MOUNTING <sup>4</sup>	INTERIOR <sup>5</sup>	FINISH <sup>9</sup>
FP1906GV	15L 1500 Lm	27K 2700K	EX Electronic Driver, 120V/277V DS2W1 ELV/MLV, 120V DO10X 1%, 0-10V, 120V/277V	FJO <sup>3</sup> 2" Frosted Tall MFO 2" Frosted Mini	WALL MOUNT	MWI <sup>6</sup> Matte White CCI <sup>6</sup> Custom Color FCI <sup>6</sup> Fixture Color Interior	MW <sup>9</sup> Matte White MB <sup>9</sup> Matte Black PT <sup>9</sup> Platinum Silver CC <sup>9</sup> Custom Color
		30K 3000K			CP104 <sup>5</sup> Small Driver Canopy		
35K 3500K	CP6/RMD Remote Mount Driver						
40K 4000K	PA <sup>6</sup> Mounting Arm Style						
					CEILING MOUNT		
					RDC5 Small Driver Canopy		
					HM <sup>7</sup> Hang Straight		
					AT <sup>7</sup> Hang Straight All Thread		
					PM <sup>7</sup> Rigid Pendant Mount		
					CD <sup>7</sup> Cord / Cable Mount		
					CM <sup>7</sup> Cord Mount		

EXAMPLE: FP1906GV15L35KEXFJO/RDC5PM24MWIMW

**NOTES:**  
 1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 Standard Enclosure 4 See Mounting Page for Details on Components and Finishes  
 5 Contact Factory for Knock Out Holes 6 See Mounting Page for Available Arm Options 7 Specify Length in Inches: See Mounting Page for Available Lengths  
 8 Reference Color Sheet Located on Product Webpage for Full List of Available Colors 9 Standard Finishes






**BRISTOL**  
**DAMP LOCATION**  
**CAFÉS**

**DECORATIVE**

LUMENS / WATTAGE DATA				
PART NUMBER	SOURCE LUMENS <sup>1</sup>	DELIVERED LUMENS <sup>2</sup>	SYSTEM WATTS	LPW
FP1906GV15L	1500	1088	11	99

<sup>1</sup>Nominal Source Lumens at 35K    <sup>2</sup> Nominal Delivered Lumens at 35K

**HOUSING DIMENSIONS**



A	B
19.1 485.1 mm	6.9 175.3 mm

**APPLICATION**

The Cafés offer a playful variety of fixture shapes. GV products are designed for damp or dry locations.

**FEATURES**

Speculume series fixtures offer contemporary style with functional luminaire performance. Passive integral heat sink. LED module and drivers are replaceable and upgradable. Standard diffuser for visual comfort and to eliminate LED source visibility. A variety of mounting options are available.

**FINISH**

Multi-stage polyester powder-coat process applied on our dedicated paint lines. See mounting and color pages for standard finishes. Interior is Matte White unless specified. Custom Color interior finish available.

**ELECTRONICS**

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 80+. Higher CRI, R9 and custom LED configurations are available; consult factory. Variety of electronic 120V/277V and dimming drivers.

**CONSTRUCTION**

Fixtures are spun in our factory from 0.063 high purity aluminum. Die-cast aluminum heat sink for optimal thermal management. Low profile frosted diffuser over LEDs to eliminate direct source visibility.

**CODE COMPLIANCE**

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.

**SERIES SIZES**

FP1906GV



**WALL MOUNT**

(SEE MOUNTING PAGES FOR MORE OPTIONS & DIMENSIONS.)

**PA**  
MOUNTING ARM STYLE



FP1906GV SHOWN WITH CP104PA23

**CEILING MOUNT**

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

**HM / AT / PM**  
HANG STRAIGHT / ALL THREAD / PENDANT



FP1906GV SHOWN WITH RDC5PM

**CD**  
CORD / CABLE MOUNT



FP1906GV SHOWN WITH RDC5CD

**CM**  
CORD MOUNT



FP1906GV SHOWN WITH RDC5CM





**BRISTOL**  
**DAMP LOCATION**  
 CAFÉS / PHOTOMETRIC DATA

FP1906GV 15L 35K XX MF0 XX MWI

CANDLEPOWER CURVE TEST SP-00978	INTENSITY CANDELA 0° AZIMUTH	ZONAL LUMENS		SINGLE UNIT: PERFORMANCE INITIAL FOOTCANDLES BASED ON IES BEAM ANGLE				MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT								
		0° - 10°	33	3%	Mounting Height AFF	FC at Center on Floor	Beam Diameter	FC at Beam Edge	Ceiling Height	Fixture Spacing	RCR 2		RCR 4			
	0.00°	0.00°	0° - 10°	33	3%	6.5'	8 fc	29.3'	0 fc	9'	6'	21	0.23	16	0.23	
	0.00°	336	0° - 20°	125	11%	7.5'	6 fc	33.8'	0 fc	12'	8'	13	0.15	7	0.10	
	5.00°	335	0° - 30°	266	24%	8.5'	5 fc	38.3'	0 fc	16'	10'	9	0.10	7	0.10	
	10.00°	331	0° - 40°	442	41%	10.0'	3 fc	45.1'	0 fc	Delivered Illuminance Rating: (DIR)		88 FC per W/Sq. Ft.		68 FC per W/Sq. Ft.		
	15.00°	326	0° - 60°	859	79%	12.0'	2 fc	54.1'	0 fc	1' Suspension Length Square rooms used for multiple units: - RCR 2: Length & Width = Ceiling Ht. - 3.5' x 5.00 - RCR 4: Length & Width = Ceiling Ht. - 3.5' x 2.50 * Average Footcandles at 2.5' Above Floor						
	20.00°	317	0° - 80°	1,085	100%	14.0'	2 fc	63.1'	0 fc							
	30.00°	294	0° - 90°	1,088	100%	16.0'	1 fc	72.1'	0 fc							
	40.00°	269	Total	1,088	100%	20.0'	1 fc	90.1'	0 fc							
	50.00°	251														
	60.00°	222														
	70.00°	114														
	80.00°	9														
90.00°	1															

Delivered Lumens: 1,088  
 Luminaire Watts: 11  
 LER: 98.91

CP at 0deg (Nadir): 336  
 CRI: 80

Beam Angle: 132.13  
 Spacing Ratio: 1.3

Lumen Multiplier: N/A  
 CCT Multiplier: 27K x 0.97, 30K x 0.99, 40K x 1.03



# MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.  
NOTE: THIS IS TYPICAL OF SPECTRUM SPECIFICATION FOR PENDANT MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.



## WALL MOUNTING

**CP104 - SMALL DRIVER CANOPY (STANDARD)**  
MAY BE USED AS SPLICE BOX FOR DIRECT FEED

Ø 5.5  
4.0

CUSTOM AND OTHER WALL ARMS AVAILABLE - CONTACT FACTORY. ARMS MAY BE FIELD CUT ON WALL SIDE - FIXTURE SIDE THREADED 3/4" NPT REQUIRES SEALANT FOR WET LOCATION.

**PA16 - Front Wall Mount**

15.0  
25.0  
13.0

**CP6/RMD - REMOTE MOUNT DRIVER**  
MOUNTS DIRECTLY TO WALL OR OCTAGON STYLE J-BOX

Ø 4.7  
1.8

**PA15** 15.0  
9.8 8.3

**PA17** 17.0  
7.0

**PA22** 22.0  
7.5 5.0 12.5

**PA23** 23.0  
7.0

**PA23(xx)**  
SPECIFY LENGTH  
7.0  
EXAMPLE: PA2330 - 30" PA23

**PA24** 15.0  
18.0 9.5 24.0

**PA26** 28.5  
12.7

**SP90(xx)**  
Designed for Straight Arm Mounting  
SPECIFY LENGTH

EXAMPLE: SP9024 - STRAIGHT PIPE 24" LONG

**PA90 (Wxx)(Dxx)**  
SPECIFY LENGTH (Wxx)  
SPECIFY DROP (6.5 Minimum) (Dxx)  
EXAMPLE: PA90W20D07 - 90° PIPE 20 LONG 7" DEEP THREADED AT FIXTURE END

**PA32** 32.6  
19.5 30.0 32.2

**PA36** 36.0  
7.0

**PA48** 48.0  
7.0

**PA16F - Back Wall Mount**

20.0  
25.0  
13.0

**PA901212**

12.0  
12.0

## CEILING MOUNTING

<p><b>RDC5 - SMALL DRIVER CANOPY (STANDARD)</b> MOUNTS TO 4" OCTO J-BOX</p> <p>Ø 5.3 2.5</p>	<p><b>HM*</b> HANG STRAIGHT 45° SWIVEL 1/2" STEM - 3/8" NPT</p> <p>45°</p> <p>ORDER: <b>HM</b> (Length) SPECIFY LENGTH: HM3 - 3"    HM24 - 24" HM6 - 6"    HM36 - 36" HM12 - 12"    HM48 - 48" HM18 - 18"    HM72 - 72" <b>HMLC(XX)</b> Custom Length (Specify in Inches)</p>	<p><b>AT**</b> HANG STRAIGHT ALL THREAD 45° SWIVEL 1/2" STEM - 1/4" IP</p> <p>45°</p> <p>ORDER: <b>AT</b> (Length) SPECIFY LENGTH: AT12 - 12"    AT48 - 48" AT24 - 24"    AT60 - 60" AT36 - 36"    AT72 - 72"</p> <p><small>FIELD-CUT THREADED PIPE TO LENGTH NEEDED* CUT 1/8" OVER 1/4" SHORTER THAN THREADED PIPE SLIP PIPE COVER OVER THREADED PIPE</small></p>	<p><b>PM*</b> RIGID PENDANT MOUNT RIGID 1/2" STEM - 3/8" NPT</p> <p>0°</p> <p>ORDER: <b>PM</b> (Length) SPECIFY LENGTH: PM3 - 3"    PM24 - 24" PM6 - 6"    PM36 - 36" PM12 - 12"    PM48 - 48" PM18 - 18"    PM72 - 72" <b>PMLLC(XX)</b> Custom Length (Specify in Inches)</p>	<p><b>CD</b> CORD / CABLE MOUNT SJ CORD WITH 1/16 SS CABLE</p> <p>ADJUST AND LOCKS</p> <p>ORDER: <b>CD</b> (Length) SPECIFY LENGTH: CD36 - 36" CD72 - 72" CD144 - 144" <b>CDLC(XX)</b> Custom Length (Specify in Inches)</p>	<p><b>CM</b> CORD MOUNT SJ CORD WITH STRAIN RELIEF</p> <p>ORDER: <b>CM</b> (Length) SPECIFY LENGTH: CM36 - 36" CM72 - 72" CM144 - 144" <b>CMLC(XX)</b> Custom Length (Specify in Inches)</p>
--	---	--	--	--	--

\*MAXIMUM ONE PIECE STEM LENGTH IS 72". \*\*MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS.  
\*\*ORDER IN 12" INCREMENTS, ODD SIZES MAY BE FIELD CUT

