



CORTADO
INCANDESCENT
 CAFÉS

PROJECT: _____
 QUANTITY: _____ TYPE: _____



RB70INC - INTERIOR ONLY / DAMP LOCATION

APPLICATION

Cafe series offers a playful variety of fixture shapes. INC Series is designed for covered or indoor dry/damp locations.

FEATURES

Spectrum Lighting's RLM Series are interpretations of classic lighting fixtures reimagined with modern INC light sources and materials. The wide range of options for illumination, mounting and finishes allows for creative fixture specification and design.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. Variety of standard and custom finishes are available. Interior is Matte White unless specified.

ELECTRONICS


E26 Edison medium base 120V socket for incandescent or LED lamps.

CONSTRUCTION

Fixture shades are spun in our factory from 0.063 high purity aluminum. Wall mount canopies are die-cast aluminum with stainless steel hardware. Wall arms are formed 3/4 NPT aluminum pipe.

CODE COMPLIANCE

BAA Compliant. ETL listed for dry/damp locations. Manufactured and tested to UL standards No. 1598/8750.



A	B
6.0	7.5
152.4 mm	190.5 mm

SERIES	MOUNTING ¹	INTERIOR FINISH ⁴	EXTERIOR FINISH ⁴
RB70INC	WALL MOUNT CP6 Wall Pipe Interface CP3 CP6 Decorative Cover PA_2 Mounting Arm Style SP90_2 Straight Arm	MW ⁵ Matte White CCI Custom Color FCI Fixture Color Interior	MW ⁵ Matte White MB ⁵ Matte Black PT ⁵ Platinum Silver CC Custom Color
	CEILING MOUNT HM_3 Hang Straight Pendant AT_3 Hang Straight All Thread PM_3 Pendant/Straight Mount HC_3 Hook/Cord CD_3 Cord and Cable Mount CM_3 Cord Mount CHN_3 Chain Mount		

EXAMPLE: RB70INC/CD96/MWIOR

NOTES:
 1 See Mounting Pages Options and Details on Components and Finishes 2 See Mounting Page for Available Arm Options
 3 Specify Length in Inches: See Mounting Page for Available Lengths 4 See Color Page for More Options/Consult Factory for Special Finishes 5 Standard Finish



MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.
NOTE: THIS IS TYPICAL OF RLM SPECIFICATION FOR MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.



WALL MOUNTING

CP6 - MOUNTS DIRECTLY TO WALL OR OCTAGON STYLE J-BOX

CUSTOM AND OTHER WALL ARMS AVAILABLE - CONTACT FACTORY. ARMS MAY BE FIELD CUT ON WALL SIDE - FIXTURE SIDE THREADED 3/4" NPT REQUIRES SEALANT FOR WET LOCATION.

<p>PA15 15.0 9.8 8.3</p> <p>PA17 17.0 7.0</p> <p>PA22 22.0 7.5 12.5</p> <p>PA23 23.0 7.0</p> <p>PA23(xx) SPECIFY LENGTH 7.0 EXAMPLE: PA2330 - 30" PA23</p>	<p>PA24 15.0 18.0 9.5 24.0</p> <p>PA26 28.5 12.7</p> <p>SP9012 FIELD CUTTABLE 12</p> <p>SP9024 FIELD CUTTABLE 24</p> <p>PA90 (Wxx)(Dxx) SPECIFY LENGTH (Wxx) SPECIFY DROP (6.5 Minimum) (Dxx) EXAMPLE: PA90W20D07 - 90° PIPE 20 LONG 7" DEEP THREADED AT FIXTURE END</p>	<p>PA32 32.6 19.5 30.0 10.5 32.2</p> <p>PA36 36.0 7.0</p> <p>PA48 48.0 7.0</p>	<p>PA16 - Front Wall Mount 15.0 25.0 13.0</p> <p>PA16F - Back Wall Mount 20.0 25.0 13.0</p> <p>PA901212 12.0 12.0</p>
---	---	---	--

CEILING MOUNTING

<p>HM* HANG STRAIGHT 45° SWIVEL 5/8" OD STEM - 3/8" IP</p> <p>ORDER: HM (Length) SPECIFY LENGTH: HM3 - 3" HM24 - 24" HM6 - 6" HM36 - 36" HM12 - 12" HM48 - 48" HM18 - 18" HM72 - 72" HMLC(XX) Custom Length (Specify in Inches)</p>	<p>PM* RIGID PENDANT MOUNT RIGID 5/8" OD STEM - 3/8" IP</p> <p>ORDER: PM (Length) SPECIFY LENGTH: PM3 - 3" PM24 - 24" PM6 - 6" PM36 - 36" PM12 - 12" PM48 - 48" PM18 - 18" PM72 - 72" PMLC(XX) Custom Length (Specify in Inches)</p>	<p>AT** HANG STRAIGHT ALL THREAD 45° SWIVEL 5/8" OD STEM - 1/4" IP</p> <p>ORDER: AT (Length) SPECIFY LENGTH: AT12 - 12" AT48 - 48" AT24 - 24" AT60 - 60" AT36 - 36" AT72 - 72" <small>FIELD CUT THREADED PIPE TO FINISH HEIGHT OD PIPE COUPLER 3/8" BORE 1/4" THREADED PIPE 1/8" PIPE COUPLER OVER THREADED PIPE</small></p>	<p>HC HOOK & CORD FOR INDEPENDENT MOUNTING</p> <p>ORDER: HC (Length) SPECIFY LENGTH: HC36 - 36" HC72 - 72" HC144 - 144" HCLC(XX) Custom Length (Specify in Inches) PLUG LP120 - 120V Twist Lock LP277 - 277V Twist Lock</p>	<p>CD CORD / CABLE MOUNT SJ CORD WITH 1/16 SS CABLE</p> <p>ORDER: CD (Length) SPECIFY LENGTH: CD36 - 36" CD72 - 72" CD144 - 144" CDLC(XX) Custom Length (Specify in Inches)</p>	<p>CM CORD MOUNT SJ CORD WITH STRAIN RELIEF</p> <p>ORDER: CM (Length) SPECIFY LENGTH: CM36 - 36" CM72 - 72" CM144 - 144" CMLC(XX) Custom Length (Specify in Inches)</p>	<p>CHN CHAIN MOUNT SJ CORD / DECORATIVE CHAIN</p> <p>ORDER: CHN (Length) SPECIFY LENGTH: CHN36 - 36" CHN72 - 72" CHN144 - 144" CHNLC(XX) Custom Length (Specify in Inches)</p>
---	--	---	---	--	--	---

*MAXIMUM ONE PIECE STEM LENGTH IS 72". **MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS.
**ORDER IN 12" INCREMENTS, ODD SIZES MAY BE FIELD CUT



COLOR OPTIONS - POWDER COAT PAINT FINISHES

NOTE: NO PRINTED IMAGE CAN EQUAL THE EXACT COLOR OF FINISH ON METAL.
SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.



STANDARD CORD / STEM / CANOPY FINISHES

FIXTURE COLOR	STANDARD CORD COLOR	STANDARD CANOPY / STEM COLOR
Matte White, Textured White	Matte White	Matte White
Gloss White	Matte White	Gloss White
Matte Black, Gloss Black, Textured Black	Matte Black	Matte Black
All Others	Matte Black	Same Color as Fixture
Custom Color	Contact Factory	Contact Factory

PAINT TIMES

TIER	COST	AVERAGE PAINT TIME*
Tier 1 - Standard Finishes	\$	⓪
Tier 2 - Typical Finishes	\$\$	⓪⓪
Tier 3 - Special Metal Finishes	\$\$\$	⓪⓪⓪
Custom Color	Contact Factory	Contact Factory

*CONTACT FACTORY FOR SPECIFIC PRODUCT LEAD TIMES


TIER 1 - STANDARD FINISHES



TIER 2 - TYPICAL FINISHES



TIER 3 - SPECIAL METAL FINISHES



CUSTOM COLOR FINISHES

CONTACT FACTORY

CC
Custom Color



*UNAVAILABLE FOR WET LOCATION

**UNAVAILABLE FOR INTERIOR

