



**15" SHORT WAREHOUSE SHADE**  
**DAMP / WET LOCATION**  
 CLASSIC SHAPES

PROJECT: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_ TYPE: \_\_\_\_\_



SW1509GV  
 BZ - Bronze



SW1509GV  
 MW - Matte White



SW1509GV  
 MB - Matte Black



SW1509GV  
 PT - Platinum Silver

SERIES	LUMENS <sup>1</sup>	CCT	DRIVER / DIMMING <sup>2</sup>	ACCESSORIES <sup>4</sup>	MOUNTING <sup>6</sup>	INTERIOR <sup>10</sup>	FINISH <sup>10</sup>	WET KIT	
SW1509GV	15L 27L	1500 Lm	80 CRI	<b>EX</b> Electronic Driver, 120V/277V 1%, 0-10V, 120V/277V <b>DLTE1<sup>3</sup></b> Lutron® 2-Wire Forward Phase (MLV), 120V 1%, Lutron® EcoSystem®, Fades to Black, 120V/277V <b>DL3EX<sup>3</sup></b>	<b>ENCLOSURES</b> <b>TF1<sup>1</sup></b> 3" Frosted Dome <b>TG1</b> 3" Dome Wire Guard <b>MF1</b> 3" Frosted Mini <b>MG1</b> 3" Short Wire Guard <b>FJ1</b> 3" Frosted Tall <b>FG1</b> 3" Tall Wire Guard	<b>WALL MOUNT</b> <b>CP104</b> Small Driver Canopy <b>CP104KO</b> Small Driver Canopy w/ Knockouts <b>CP106</b> Large Driver Canopy <b>CP6/RMD</b> Remote Mount Driver <b>SP90<sup>7</sup></b> Straight Arm <b>PA<sup>7</sup></b> Mounting Arm Style	<b>MW1<sup>11</sup></b> Matte White <b>CCI</b> Custom Color <b>FCI</b> Fixture Color Interior	<b>MW<sup>11</sup></b> Matte White <b>MB<sup>11</sup></b> Matte Black <b>PT<sup>11</sup></b> Platinum Silver <b>CC</b> Custom Color	<b>WLKA</b> Wet Location Kit
		2700 Lm	2700K 3000K 3500K 4000K						
		90 CRI							
		2700K 3000K 3500K 4000K							

EXAMPLE: SW1509GV27L35KEXTF1/RDC5HM36MWIMB

**NOTES:**  
 1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 Available with CP106/CP13 Only 4 Enclosure, Wire Guard Required - Choose One Option  
 5 Standard Enclosure 6 See Mounting Page for Details on Components and Finishes 7 See Mounting Page for Available Arm Options 8 Specify Length in Inches:  
 See Mounting Page for Available Lengths 9 EMCR Replaces RDC5 or CP13 10 Reference Color Sheet Located on Product Webpage for Full List of Available Colors 11 Standard Finishes






# 15" SHORT WAREHOUSE SHADE DAMP / WET LOCATION CLASSIC SHAPES

LUMENS / WATTAGE DATA				
PART NUMBER	SOURCE LUMENS <sup>1</sup>	DELIVERED LUMENS <sup>2</sup>	SYSTEM WATTS	LPW
SW1509GV15L	1500	1150	10	115
SW1509GV27L	2700	2008	18	112

<sup>1</sup>Nominal Source Lumens at 35K    <sup>2</sup> Nominal Delivered Lumens at 35K

## HOUSING DIMENSIONS



A	B
14.5 368.3 mm	9.0 228.6 mm

## APPLICATION

The Short Warehouse Shade is a shallow version of our most popular Warehouse Shades.

## FEATURES

Spectrum Lighting's RLM Classics are inspired by vintage lighting fixtures redesigned with modern LED light sources and materials. The wide range of options for illumination, mounting, enclosures, guards and finishes allows for creative fixture specification and design. LED module and driver are serviceable for future replacement.

## FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. Variety of standard and custom finishes are available. Interior is Matte White unless specified. Custom Color interior finishes available.

## ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 80+. Higher CRI, R9 and custom LED configurations are available; consult factory. Choice of electronic 120V/277V and dimming drivers.

## CONSTRUCTION

Fixture shades are spun in our factory from 0.063 high purity aluminum. Wall mount canopies are die-cast aluminum with stainless steel hardware. Wall arms are formed 3/4 NPT aluminum pipe and may be field cut.

## CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Wet Location Option. Manufactured and tested to UL standards No. 1598/8750.

## ENCLOSURES

### TF1

3" FROSTED DOME



### MF1

3" FROSTED MINI



### FJ1

3" FROSTED TALL



### TG1

3" FROSTED DOME  
WIRE GUARD - FITS TF1



### MG1

3" FROSTED MINI  
WIRE GUARD - FITS MF1



### FG1

3" FROSTED TALL  
WIRE GUARD - FITS FJ1



## WALL MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & DIMENSIONS.)

### PA\_

MOUNTING ARM STYLE



SW1509GV SHOWN WITH CP104PA23

## CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

### HM / AT / PM

HANG STRAIGHT / ALL THREAD / PENDANT



SW1509GV SHOWN WITH RDC5PM

### CD

CORD / CABLE MOUNT



SW1509GV SHOWN WITH RDC5CD

### CM

CORD MOUNT



SW1509GV SHOWN WITH RDC5CM





# 15" SHORT WAREHOUSE SHADE

## DAMP / WET LOCATION

### CLASSIC SHAPES / PHOTOMETRIC DATA

SW1509GV-27L-35K-EX-TF1-MWI

CANDLEPOWER CURVE	INTENSITY	ZONAL LUMENS		SINGLE UNIT: PERFORMANCE INITIAL FOOTCANDLES BASED ON IES BEAM ANGLE				MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT						
		0° - 10°	80	4%	Mounting Height AFF	FC at Center on Floor	Beam Diameter	FC at Beam Edge	Ceiling Height	Fixture Spacing	RCR 2		RCR 4	
	0.00°													
	0.00°	847												
	5.00°	837							8'	8'	24	0.24	19	0.24
	10.00°	811			5.50'	28 fc	12.5'	12 fc	12'	10'	21	0.20	16	0.20
	15.00°	770			6.50'	20 fc	14.8'	8 fc	16'	12'	14	0.14	7	0.09
	20.00°	719			7.50'	15 fc	17.1'	6 fc	Delivered Illuminance Rating: (DIR)					
	30.00°	615			8.50'	12 fc	19.3'	5 fc	101 FC per W/Sq. Ft.    79 FC per W/Sq. Ft.					
	40.00°	511			10.00'	8 fc	22.7'	4 fc	2' Suspension Length Square rooms used for multiple units: - RCR 2: Length & Width = Ceiling Ht. - 4.5' x 5.00' - RCR 4: Length & Width = Ceiling Ht. - 4.5' x 2.50' * Average Footcandles at 2.5' Above Floor * Exceeds spacing criteria by 110% ** Exceeds spacing criteria by 22% *** Exceeds spacing criteria by -4%					
	50.00°	392			12.00'	6 fc	27.3'	2 fc						
	60.00°	260			14.00'	4 fc	31.8'	2 fc						
	70.00°	148			16.00'	3 fc	36.4'	1 fc						
	80.00°	69												
	90.00°	4												
	<b>Total</b>	<b>2,007</b>	<b>100%</b>											

Delivered Lumens: 2,007  
Luminaire Watts: 18  
LER: 111.50

CP at 0deg (Nadir): 847  
CRI: 85+

Beam Angle: 97.93  
Spacing Ratio: 1.09

Lamp Multiplier: 15L x 0.5728  
CCT Multiplier: 27K x 0.971, 30K x 0.985, 40K x 1.03




# MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION. NOTE: THIS IS TYPICAL OF RLM SPECIFICATION FOR MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.




## WALL MOUNTING

**CP104 - SMALL DRIVER CANOPY (STANDARD)**  
MAY BE USED AS SPLICE BOX FOR DIRECT FEED  
NOT AVAILABLE W/ PA16 & PA16F




**CP106 - LARGE DRIVER CANOPY**  
MAY BE USED AS SPLICE BOX FOR DIRECT FEED



**CP6/RMD - REMOTE MOUNT DRIVER**  
MOUNTS DIRECTLY TO WALL OR OCTAGON STYLE J-BOX




CUSTOM AND OTHER WALL ARMS AVAILABLE - CONTACT FACTORY. ARMS MAY BE FIELD CUT ON WALL SIDE - FIXTURE SIDE THREADED 3/4" NPT REQUIRES SEALANT FOR WET LOCATION.




## CEILING MOUNTING


**RDC5 - SMALL DRIVER CANOPY (STANDARD)**  
MOUNTS TO 4" OCTO J-BOX



**CP13 - LARGE DRIVER CANOPY**




**HM\***  
HANG STRAIGHT  
45° SWIVEL 5/8" OD STEM - 3/8" IP




ORDER: HM (Length)  
SPECIFY LENGTH:  
HM3 - 3" HM24 - 24"  
HM6 - 6" HM36 - 36"  
HM12 - 12" HM48 - 48"  
HM18 - 18" HM72 - 72"  
HMLC(XX)  
Custom Length  
(Specify in Inches)

**PM\***  
RIGID PENDANT MOUNT  
RIGID 5/8" OD STEM - 3/8" IP




ORDER: PM (Length)  
SPECIFY LENGTH:  
PM3 - 3" PM24 - 24"  
PM6 - 6" PM36 - 36"  
PM12 - 12" PM48 - 48"  
PM18 - 18" PM72 - 72"  
PMLC(XX)  
Custom Length  
(Specify in Inches)

**AT\*\***  
HANG STRAIGHT ALL THREAD  
45° SWIVEL 5/8" OD STEM - 1/4" IP



ORDER: AT (Length)  
SPECIFY LENGTH:  
AT12 - 12"  
AT24 - 24"  
AT36 - 36"  
AT48 - 48"  
AT60 - 60"  
AT72 - 72"

**CD**  
CORD / CABLE MOUNT  
SJ CORD WITH 1/16" SS CABLE



ORDER: CD (Length)  
SPECIFY LENGTH:  
CD36 - 36"  
CD72 - 72"  
CD144 - 144"  
CDLC(XX)  
Custom Length  
(Specify in Inches)

**CM**  
CORD MOUNT  
SJ CORD WITH STRAIN RELIEF




ORDER: CM (Length)  
SPECIFY LENGTH:  
CM36 - 36"  
CM72 - 72"  
CM144 - 144"  
CMLC(XX)  
Custom Length  
(Specify in Inches)

\*MAXIMUM ONE PIECE STEM LENGTH IS 72". \*\*MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS.  
\*\*ORDER IN 12" INCREMENTS, ODD SIZES MAY BE FIELD CUT


## EMERGENCY BATTERY OPTIONS

**EMCR - LARGE DRIVER CANOPY FOR 10W EMERGENCY BATTERY**




## REMOTE EMERGENCY BATTERY OPTIONS

**EMRM\* - 7W REMOTE EMERGENCY BATTERY (50' MAX)**



**EMEN\* - 7W REMOTE EMERGENCY BATTERY WITH ENCLOSURE (50' MAX)**



\*OTHER EM BATTERY SIZES AVAILABLE. CONTACT FACTORY.

