



6" ROUND DIRECT
WET LOCATION
 GAMMA SERIES

PROJECT: _____
 QUANTITY: _____ TYPE: _____



CW0606PC



CW0612PC



CW0618PC

SERIES	LUMENS ¹	CCT	OPTICS	DRIVER / DIMMING ²	LENS	MOUNTING ³	FINISH ⁶
CW0606PC 6" x 6"	10L 700 Lm	80 CRI	ND 14°	EX Electronic Driver, 120V/277V DO10X 1%, 0-10V, 120V/277V DS2W1 ELV/MLV, 120V	CL Clear Lens SO Micro Prism Solite™ Lens	HM^{4/5} Hang Straight PM^{4/5} Rigid Pendant Mount SM Surface Mount	MW⁷ Matte White MB⁷ Matte Black PT⁷ Platinum Silver CC Custom Color
	15L 1050 Lm		MD 31°				
CW0612PC 6" x 12"	20L 1400 Lm	30K 3000K	WD 52°				
	30L 2100 Lm		35K 3500K				
CW0618PC 6" x 18"	40L 2850 Lm	90 CRI				EMERGENCY BATTERY OPTIONS EMRM 7W Remote EM EMEN 7W Remote with Enclosure	See Page 5 for Full Range of Color Options (83-90165)
			27HK 2700K				

EXAMPLE: CW0606PC10L35KNDEX/CL/HM36/MW

NOTES:
 1 Nominal Delivered Lumens at 3500K 2 Consult Factory for Additional Options 3 See Mounting Page for Details on Components and Finishes 4 Specify Length in Inches: See Mounting Page for Available Lengths
 5 Not for Use in Locations with Wind Exposure 6 See Color Page for More Options/Consult Factory for Special Finishes 7 Standard Finishes






6" ROUND DIRECT WET LOCATION GAMMA SERIES

LUMENS / WATTAGE DATA			
PART NUMBER	DELIVERED LUMENS ¹	SYSTEM WATTS	LPW
CW0612PC 10L	707	6.5	109
CW0612PC 15L	1046	9.5	110
CW0612PC 20L	1413	12.9	110
CW0612PC 30L	2120	19.9	107
CW0612PC 40L	2827	27.4	103

¹ Nominal Delivered Lumens at 3500K, 80 CRI, Medium Optic with Clear Lens

DIMENSIONS



Dimensioned with **CW0612PC**

SERIES	A	B
CW0606PC	6.1	6.4
CW0612PC	6.1	12.4
CW0618PC	6.1	18.4

APPLICATION

The Gamma Family of Cylinders are a robust offering of point source LED luminaires featuring high efficacies, an assortment of optical control, and installation flexibility, which make them suitable for a wide range of commercial and institutional applications.

ELECTRONICS

Solid-state light engine available in various color temperatures and lumen outputs. Specifiable in 2700K, 3000K, 3500K, 4000K in CRI 80 (Typ.), or 2700K, 3000K in CRI 90 (Typ.), color accuracy ≤ 3 SDCM. Selection of integral electronic constant current, dimmable drivers available, power factor > 0.9 (Typ). Driver and light engine are field serviceable for future replacement or upgrades. Emergency battery options provide 7W for 90 minutes.

CONSTRUCTION

Seamless cylinder body machined from 6063 extruded aluminum. Trim and top cap are die-cast aluminum. Self-locating trim is secured with self-sealing stainless steel hardware. Nitrile rubber o-rings provide additional ingress protection from water. Passive aluminum heatsink optimized for emitter life and performance. Specular reflectors offered in variety of beam spreads. Lens type must be specified. Luminaire will not exceed 10 lbs.

MOUNTING

All pendant options are specified in inches. Mounting bracket and canopies provided for direct installation with 4" octagonal junction boxes. Hang Mount (3/8"NPT) and Rigid Stem (3/8"IP) are 1/2" diameter and produced from steel pipe. Hang Mount option provides up to 45° tilt correction. Surface mount kit provided with aluminum mounting plate to install directly to junction box. See mounting page for additional information. Contact factory for special installation circumstances.

FINISH

Multi-stage polyester powder-coat process applied on our in-house finishing department. Custom colors also available (contact factory with RAL#). Canopy and stems will match cylinder finish specification.

CODE COMPLIANCE

ETL Listed. Suitable for wet locations with operation in ambient conditions up to 25°C. 5 year limited warranty on all components. Proudly designed and manufactured in Massachusetts, USA.

SERIES SIZES

CW0606PC



CW0612PC



CW0618PC



STANDARD FINISHES SHOWN WITH CW0612PC

MW
Matte White



MB
Matte Black



PT
Platinum Silver



CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

HM / PM
HANG STRAIGHT / PENDANT



CW0612PC SHOWN WITH PM

SM
SURFACE MOUNT



CW0612PC SHOWN WITH SM





6" ROUND DIRECT

GAMMA SERIES / PHOTOMETRIC DATA

CW06XXPC 40L 35K ND XX CL XX

CANDLEPOWER CURVE TEST SP-01077	INTENSITY CANDELA 0° AZIMUTH	ZONAL LUMENS	SINGLE UNIT: PERFORMANCE DIRECT FOOTCANDLES BASED ON DOWNLIGHT ONLY				MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT					
			Mounting Height AFF	FC at Center on Floor	Beam Diameter	FC at Beam Edge	Ceiling Height	Fixture Spacing	RCR 4		RCR 6	
	0°	0° - 10° 894 31%	10'	173 fc	2.4'	85 fc	18'	3'	271	2.81	272	3.12
	0°	0° - 20° 1453 50%	10'	173 fc	2.4'	85 fc	22'	4"	156	1.61	156	1.79
	5°	0° - 30° 2001 69%	12'	120 fc	2.9'	59 fc	26'	5"	101	1.04	101	1.16
	15°	0° - 40° 2620 90%	14'	88 fc	3.4'	43 fc	Delivered Illuminance Rating: (DIR)					
	25°	0° - 60° 2890 100%	16'	68 fc	3.9'	33 fc	97 FC per W/Sq. Ft. 87 FC per W/Sq. Ft.					
	35°	0° - 80° 2893 100%	20'	43 fc	4.8'	21 fc	3' Suspension Length to luminous aperture Square rooms used for multiple units: RCR 4: Length & Width = Ceiling Ht. - 5.5' x 2.50 RCR 6: Length & Width = Ceiling Ht. - 5.5' x 1.66					
	45°	0° - 90° 2895 100%	24'	30 fc	5.8'	15 fc	* Average Footcandles at 2.5' Above Floor					
	55°	0° - 90° 2895 100%	28'	22 fc	6.7'	11 fc	** Exceeds Spacing Ratio by 1%					
	90°	1	Total 2895 100%	32'	17 fc	7.7'	8 fc	*** Exceeds Spacing Ratio by 2%				

Delivered Lumens: 2895
Luminaire Watts: 27.4
LER: 105.66

CP at 0° (Nadir): 17337
CRI: 80

Beam Angle: 14°
Spacing Ratio: 0.24

Lumen Multiplier: 10L x 0.25, 15L x 0.37, 20L x 0.50, 30L x 0.75
CCT Multiplier: 27K x 0.97, 30K x 0.98, 40K x 1.04
27HK x 0.78, 30HK x 0.82
See Page 1 for System Watts for all outputs

CW06XXPC 40L 35K MD XX CL XX

CANDLEPOWER CURVE TEST SP-01076	INTENSITY CANDELA 0° AZIMUTH	ZONAL LUMENS	SINGLE UNIT: PERFORMANCE DIRECT FOOTCANDLES BASED ON DOWNLIGHT ONLY				MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT					
			Mounting Height AFF	FC at Center on Floor	Beam Diameter	FC at Beam Edge	Ceiling Height	Fixture Spacing	RCR 3		RCR 5	
	0°	0° - 10° 484 17%	8'	89 fc	4.4'	40 fc	14'	4'	172	1.75	164	1.90
	0°	0° - 20° 1284 45%	10'	57 fc	5.5'	26 fc	18'	6'	65	0.66	52	0.60
	5°	0° - 30° 1907 67%	12'	40 fc	6.5'	18 fc	22'	8'	39	0.40	31	0.36
	15°	0° - 40° 2543 90%	14'	29 fc	7.6'	13 fc	Delivered Illuminance Rating: (DIR)					
	25°	0° - 60° 2814 100%	16'	22 fc	8.7'	10 fc	98 FC per W/Sq. Ft. 87 FC per W/Sq. Ft.					
	35°	0° - 80° 2825 100%	20'	14 fc	10.9'	6 fc	2' Suspension Length to luminous aperture Square rooms used for multiple units: RCR 3: Length & Width = Ceiling Ht. - 4.5' x 3.33 RCR 5: Length & Width = Ceiling Ht. - 4.5' x 2.00					
	45°	0° - 90° 2827 100%	24'	10 fc	13.1'	4 fc	* Average Footcandles at 2.5' Above Floor					
	55°	8	Total 2827 100%	28'	7 fc	15.3'	3 fc					

Delivered Lumens: 2827
Luminaire Watts: 27.4
LER: 103.18

CP at 0° (Nadir): 5721
CRI: 80

Beam Angle: 31°
Spacing Ratio: 0.50

Lumen Multiplier: 10L x 0.25, 15L x 0.37, 20L x 0.50, 30L x 0.75
CCT Multiplier: 27K x 0.97, 30K x 0.98, 40K x 1.04
27HK x 0.78, 30HK x 0.82
See Page 1 for System Watts for all outputs

CW06XXPC 40L 35K WD XX CL XX

CANDLEPOWER CURVE TEST SP-01290_M-40L	INTENSITY CANDELA 0° AZIMUTH	ZONAL LUMENS	SINGLE UNIT: PERFORMANCE DIRECT FOOTCANDLES BASED ON DOWNLIGHT ONLY				MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT					
			Mounting Height AFF	FC at Center on Floor	Beam Diameter	FC at Beam Edge	Ceiling Height	Fixture Spacing	RCR 2		RCR 4	
	0°	0° - 10° 319 11%	8'	54 fc	7.9'	20 fc	14'	6'	82	0.77	72	0.77
	0°	0° - 20° 1077 37%	10'	35 fc	9.8'	13 fc	18'	8'	41	0.38	35	0.38
	5°	0° - 30° 1921 67%	12'	24 fc	11.8'	9 fc	22'	10'	31	0.29	21	0.23
	15°	0° - 40° 2597 90%	14'	18 fc	13.8'	6 fc	Delivered Illuminance Rating: (DIR)					
	25°	0° - 60° 2851 99%	16'	14 fc	15.7'	5 fc	106 FC per W/Sq. Ft. 93 FC per W/Sq. Ft.					
	35°	0° - 80° 2870 99%	20'	9 fc	19.7'	3 fc	2' Suspension Length to luminous aperture Square rooms used for multiple units: RCR 2: Length & Width = Ceiling Ht. - 4.5' x 5.00 RCR 4: Length & Width = Ceiling Ht. - 4.5' x 2.50					
	45°	0° - 90° 2873 100%	24'	6 fc	23.6'	2 fc	* Average Footcandles at 2.5' Above Floor					
	55°	22	Total 2885 100%	28'	4 fc	27.5'	2 fc					

Delivered Lumens: 2885
Luminaire Watts: 27.2
LER: 106.07

CP at 0° (Nadir): 3480
CRI: 80

Beam Angle: 52°
Spacing Ratio: 0.78

Lumen Multiplier: 10L x 0.25, 15L x 0.36, 20L x 0.50, 30L x 0.75
CCT Multiplier: 27K x 0.97, 30K x 0.98, 40K x 1.04
27HK x 0.78, 30HK x 0.83
See Page 1 for System Watts for all outputs





6" ROUND DIRECT

GAMMA SERIES / PHOTOMETRIC DATA

CW06XXPC 40L 35K XW XX CL XX

CANDLEPOWER CURVE TEST SP-01078	INTENSITY CANDELA 0° AZIMUTH	ZONAL LUMENS		SINGLE UNIT: PERFORMANCE DIRECT FOOTCANDLES BASED ON DOWNLIGHT ONLY				MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT							
		0° - 10°	205	7%	Mounting Height AFF	FC at Center on Floor	Beam Diameter	FC at Beam Edge	Ceiling Height	Fixture Spacing	RCR 1		RCR 3		
	0°	2156													
	5°	2123													
	15°	2021													
	25°	1842													
	35°	1303													
	45°	287													
	55°	28													
	90°	0													
		Total	2752	100%											
					6'	60 fc	9.2'	15 fc							
				8'	34 fc	12.3'	8 fc								
				10'	22 fc	15.4'	5 fc								
				12'	15 fc	18.5'	4 fc								
				14'	11 fc	21.5'	3 fc								
				16'	8 fc	24.6'	2 fc								
				20'	5 fc	30.8'	1 fc								
				24'	4 fc	36.9'	1 fc								
				Delivered Illuminance Rating: (DIR)				108 FC per W/Sq. Ft.		92 FC per W/Sq. Ft.					
				2' Suspension Length to luminous aperture Square rooms used for multiple units: RCR 1: Length & Width = Ceiling Ht. - 4.5' x 10.00 RCR 3: Length & Width = Ceiling Ht. - 4.5' x 3.33 * Average Footcandles at 2.5' Above Floor											

Delivered Lumens: 2752
Luminaire Watts: 27.4
LER: 100.44

CP at 0° (Nadir): 2156
CRI: 80

Beam Angle: 75°
Spacing Ratio: 1.14

Lumen Multiplier: 10L x 0.25, 15L x 0.37, 20L x 0.50, 30L x 0.75
CCT Multiplier: 27K x 0.97, 30K x 0.98, 40K x 1.04
27HK x 0.78, 30HK x 0.82

See Page 1 for System Watts for all outputs

STANDARD MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.
NOTE: THIS IS TYPICAL OF CYLINDERS SPECIFICATION FOR PENDANT MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.



CANOPY DIMENSIONS

HM / PM CANOPY HANG STRAIGHT / PENDANT		SM CANOPY SURFACE MOUNT
A	B	A
5.0 127.0 mm	1.5 38.1 mm	4.9 124.5 mm

MOUNTING TYPES

HM* HANG STRAIGHT 45° SWIVEL 5/8" OD STEM - 3/8" IP	PM* RIGID PENDANT MOUNT RIGID 5/8" OD STEM - 3/8" IP	SM SURFACE MOUNT
<p>ORDER: HM (Length)</p> <p>SPECIFY LENGTH:</p> <p>HM3 - 3" HM24 - 24"</p> <p>HM6 - 6" HM36 - 36"</p> <p>HM12 - 12" HM48 - 48"</p> <p>HM18 - 18" HM72 - 72"</p> <p>HMLC(XX) Custom Length (Specify in Inches)</p>	<p>ORDER: PM (Length)</p> <p>SPECIFY LENGTH:</p> <p>PM3 - 3" PM24 - 24"</p> <p>PM6 - 6" PM36 - 36"</p> <p>PM12 - 12" PM48 - 48"</p> <p>PM18 - 18" PM72 - 72"</p> <p>PMLC(XX) Custom Length (Specify in Inches)</p>	<p>ORDER: SM (Flush to Ceiling)</p>

REMOTE EMERGENCY BATTERY OPTIONS

EMRM* - 7W REMOTE EMERGENCY BATTERY (50' MAX)	EMEN* - 7W REMOTE EMERGENCY BATTERY WITH ENCLOSURE (50' MAX)												
<table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>1.3</td> <td>12.6</td> <td>13.0</td> </tr> </tbody> </table>	A	B	C	1.3	12.6	13.0	<table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>2.0</td> <td>17.0</td> <td>6.2</td> </tr> </tbody> </table>	A	B	C	2.0	17.0	6.2
A	B	C											
1.3	12.6	13.0											
A	B	C											
2.0	17.0	6.2											

*OTHER EM BATTERY SIZES AVAILABLE, CONSULT FACTORY



COLOR OPTIONS - POWDER COAT PAINT FINISHES

NOTE: NO PRINTED IMAGE CAN EQUAL THE EXACT COLOR OF FINISH ON METAL.
SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.



STANDARD CORD / STEM / CANOPY FINISHES


FIXTURE COLOR	STANDARD CORD COLOR	STANDARD CANOPY / STEM COLOR
Matte White, Textured White	Matte White	Matte White
Gloss White	Matte White	Gloss White
Matte Black, Textured Black	Matte Black	Matte Black
All Others	Matte Black	Same Color as Fixture
Custom Color	Contact Factory	Contact Factory

PAINT TIMES

TIER	COST	AVERAGE PAINT TIME*
Tier 1 - Standard Finishes	\$	⌚
Tier 2 - Typical Finishes	\$\$	⌚⌚
Custom Color	Contact Factory	Contact Factory

*CONTACT FACTORY FOR SPECIFIC PRODUCT LEAD TIMES

TIER 1 - STANDARD FINISHES



TIER 2 - TYPICAL FINISHES



CUSTOM COLOR FINISHES

CONTACT FACTORY

CC
Custom Color



*UNAVAILABLE FOR WET LOCATION

