



**ESPRESSO DIRECT PENDANT**  
**DAMP LOCATION**  
**GV SERIES**

PROJECT: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_ TYPE: \_\_\_\_\_



ME1314DGV  
 AM - Anodic Malachite  
 MWI - Matte White Interior



ME1314DGV  
 CO - Copper Metallic  
 PTI - Platinum Silver Interior



ME1314DGV  
 MW - Matte White  
 FCI - Fixture Color Interior



ME1314DGV  
 AL - Almond  
 DR13AFO - Door w/ White Optical Lens

SERIES	LUMENS <sup>1</sup>	CCT	DRIVER / DIMMING <sup>2</sup>	DIFFUSER <sup>3</sup>	OPTIONS <sup>4</sup>	MOUNTING <sup>6</sup>	INTERIOR <sup>5</sup>	FINISH <sup>8</sup>
<b>ME1314DGV</b> <b>ME1816DGV</b>	<b>15L</b> 1500 Lm <b>27L</b> 2700 Lm <b>37L</b> 3700 Lm <b>55L</b> 5500 Lm	<b>27K</b> 2700K <b>30K</b> 3000K <b>35K</b> 3500K <b>40K</b> 4000K <b>50K</b> 5000K	<b>EX</b> Electronic Driver, 120V/277V <b>DO10X</b> 1% 0-10V, 120V/277V <b>DLTE1</b> Lutron® 2-Wire Forward Phase (MLV), 120V <b>DL3EX</b> 1%, Lutron® EcoSystem®, Fades to Black, 120V/277V	<b>ENCLOSURES</b> <b>TF2</b> 4" Frosted Dome (Standard) <b>DOORS &amp; LENSES</b> <b>DR</b> Door (See 2 <sup>nd</sup> Page for Ordering Details)	<b>ENL</b> <sup>5</sup> 0-10V Control Module <b>FS</b> Fusing	<b>HM</b> <sub>7</sub> Hang Straight <b>AT</b> <sub>7</sub> Hang Straight All Thread <b>CD</b> <sub>7</sub> Cord / Cable Mount <b>CM</b> <sub>7</sub> Cord Mount <b>CD3X</b> <sub>7</sub> 3 Cable Mount with Cord <b>EMCR</b> 10W Canopy Mounted EM <b>EMRM</b> 7W Remote EM <b>EMEN</b> 7W Remote with Enclosure	<b>MWI</b> <sup>9</sup> Matte White <b>CCI</b> Custom Color <b>FCI</b> Fixture Color Interior	<b>MW</b> <sup>9</sup> Matte White <b>MB</b> <sup>9</sup> Matte Black <b>PT</b> <sup>9</sup> Platinum Silver <b>CC</b> Custom Color

EXAMPLE: ME1314DGV15L27KEX/TF2/HM36LGIMW

**NOTES:**  
 1 Normal Source Lumens at 35K 2 Contact Factory for Additional Options 3 TF2 Enclosure or Door & Lens Required - Choose One Option 4 See Product Options Page For Details 5 Not Available with EM Options 6 See Mounting Page for Details 7 Specify Length in Inches: See Mounting Page for Available Lengths 8 Reference Color Sheet Located on Product Webpage for Full List of Available Colors 9 Standard Finishes





DECORATIVE

# ESPRESSO DIRECT PENDANT


## DAMP LOCATION

### GV SERIES

LUMENS / WATTAGE DATA				
PART NUMBER	SOURCE LUMENS <sup>1</sup>	DELIVERED LUMENS <sup>2</sup>	SYSTEM WATTS	LPW
ME1314DGV15L	1500	1135	10	114
ME1314DGV27L	2700	1934	18	107
ME1314DGV37L	3700	2859	26	110
ME1314DGV55L	5500	4205	39	108

<sup>1</sup> Nominal Source Lumens at 35K <sup>2</sup> Nominal Delivered Lumens at 35K

### HOUSING DIMENSIONS



Dimensioned with ME1314DGV

SERIES	A	B
ME1314DGV	13.9	14.4
ME1816DGV	16.7	18.1

### APPLICATION

Espresso Pendant features a unique hourglass shape for direct down lighting.

### FEATURES

SpecLume series fixtures offer contemporary style with functional luminaire performance. Fixtures are designed and manufactured in our factory. Espresso Pendant is available in two sizes for direct lighting. Passive integral heat sink. LED module and driver are serviceable for future replacement. Variety of mounting and lens options.

### FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. See mounting and color pages for standard finishes. Interior is Matte White unless specified. Custom Color interior finish available.

### ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 80+. Higher CRI, R9 and custom LED configurations are available; consult factory. Variety of electronic 120V/277V and dimming drivers.

### CONSTRUCTION

Fixtures are spun in our factory from 0.063 high purity aluminum. Passive machined aluminum heat sink for optimal thermal management.

### CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.

### SERIES SIZES

ME1314DGV



ME1314DGV SHOWN WITH TF2

ME1816DGV



ME1816DGV SHOWN WITH TF2

### CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

**HM / AT**  
HANG STRAIGHT / ALL THREAD



ME1314DGV SHOWN WITH HM

**CD**  
CORD / CABLE MOUNT



ME1314DGV SHOWN WITH CD

**CM**  
CORD MOUNT



ME1314DGV SHOWN WITH CM

**CD3X**  
3X CORD / CABLE MOUNT



ME1314DGV SHOWN WITH CD3X

### DOORS

**DR13A** - 13" Ø  
**DR16B** - 16" Ø

### LENSES

**FO** - WHITE OPTICAL LENS  
**SO** - SOLITE™ LENS



ME1314DGV SHOWN WITH DR13AFO





**ESPRESSO DIRECT PENDANT**  
**DAMP LOCATION**  
 GV SERIES / PHOTOMETRIC DATA

**DECORATIVE**

ME1314DGV 55L 35K EX TF2

CANDLEPOWER CURVE TEST SP-00255_53	INTENSITY CANDELA 0° AZIMUTH	ZONAL LUMENS	SINGLE UNIT: PERFORMANCE INITIAL FOOTCANDLES BASED ON IES BEAM ANGLE				MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT									
			Mounting Height AFF	FC at Center on Floor	Beam Diameter	FC at Beam Edge	Ceiling Height	Fixture Spacing	RCR 2		RCR 4					
	0.00°	0.00%														
	0.00°	1,798	0° - 10°	173	4%	6.5'	43 fc	13.7'	18 fc	9'	6'	83	0.83	67	0.83	
	5.00°	1,793	0° - 20°	671	16%	7.5'	32 fc	15.8'	14 fc	12'	8'	54	0.54	28	0.35	
	10.00°	1,778	0° - 30°	1,461	35%	8.5'	25 fc	18.0'	11 fc	16'	10'	36	0.36	29	0.36	
	15.00°	1,759	0° - 40°	2,451	58%	10.0'	18 fc	21.1'	8 fc	Delivered Illuminance Rating: (DIR)		100 FC per W/Sq. Ft.		81 FC per W/Sq. Ft.		
	20.00°	1,737	0° - 60°	3,690	88%	12.0'	12 fc	25.3'	5 fc	1' Suspension Length Square rooms used for multiple units: - RCR 2: Length & Width = Ceiling Ht. - 3.5' x 5.00 - RCR 4: Length & Width = Ceiling Ht. - 3.5' x 2.50 * Average Footcandles at 2.5' Above Floor						
	30.00°	1,677	0° - 80°	4,160	99%	14.0'	9 fc	29.6'	4 fc							
	40.00°	1,398	0° - 90°	4,204	100%	16.0'	7 fc	33.8'	3 fc							
	50.00°	684	Total	4,205	100%	20.0'	4 fc	42.2'	2 fc							
	60.00°	375														
	70.00°	233														
	80.00°	97														
90.00°	10															

Delivered Lumens: **4,205**  
 Luminaire Watts: **39**  
 LER: **107.82**

CP at 0deg (Nadir): **1,798**  
 CRI: **80+**

Beam Angle: **93.13**  
 Spacing Ratio: **1.37**

Lumen Multiplier: **15L x 0.27, 27L x 0.46, 37L x 0.68**  
 CCT Multiplier: **27K x 0.97, 30K x 0.98, 40K x 1.03**








# MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.  
NOTE: THIS IS TYPICAL OF SPECULUME SPECIFICATION FOR PENDANT MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.




## CEILING MOUNTING

<p><b>HM*</b> HANG STRAIGHT 45° SWIVEL 1/2" STEM - 3/8" NPT</p>  <p>ORDER: <b>HM</b> (Length) SPECIFY LENGTH: <b>HM3</b> - 3"    <b>HM24</b> - 24" <b>HM6</b> - 6"    <b>HM36</b> - 36" <b>HM12</b> - 12"    <b>HM48</b> - 48" <b>HM18</b> - 18"    <b>HM72</b> - 72" <b>HMLC(XX)</b> Custom Length (Specify in Inches)</p>	<p><b>AT**</b> HANG STRAIGHT ALL THREAD 45° SWIVEL 1/2" STEM - 1/4" IP</p>  <p>ORDER: <b>AT</b> (Length) SPECIFY LENGTH: <b>AT12</b> - 12"    <b>AT48</b> - 48" <b>AT24</b> - 24"    <b>AT60</b> - 60" <b>AT36</b> - 36"    <b>AT72</b> - 72" <small>FIELD CUT - THREADED PIPE TO LENGTH ORDERED - 1/4" GAUETTE CUT - THE CODE IS LESS THAN THREADED PIPE - 1/4" PIPE COVER CHECK</small></p>	<p><b>CD</b> CORD / CABLE MOUNT SJ CORD WITH 1/16 SS CABLE</p>  <p>ORDER: <b>CD</b> (Length) SPECIFY LENGTH: <b>CD36</b> - 36" <b>CD72</b> - 72" <b>CD144</b> - 144" <b>CDLC(XX)</b> Custom Length (Specify in Inches)</p>	<p><b>CM</b> CORD MOUNT SJ CORD WITH STRAIN RELIEF</p>  <p>ORDER: <b>CM</b> (Length) SPECIFY LENGTH: <b>CM36</b> - 36" <b>CM72</b> - 72" <b>CM144</b> - 144" <b>CMLC(XX)</b> Custom Length (Specify in Inches)</p>	<p><b>CD3X</b> 3X CORD / CABLE MOUNT SJ CORD WITH 1/16 SS CABLE</p>  <p>ORDER: <b>CD3X</b> (Length) SPECIFY LENGTH: <b>CD3x36</b> - 36" <b>CD3x72</b> - 72" <b>CD3x144</b> - 144" <b>CD3XLC(XX)</b> Custom Length (Specify in Inches)</p>
--	--	---	---	--



\*MAXIMUM ONE PIECE STEM LENGTH IS 72". \*\*MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS.  
\*\*ORDER IN 12" INCREMENTS. ODD SIZES MAY BE FIELD CUT

## EMERGENCY BATTERY OPTIONS

**EMCR** - LARGE DRIVER CANOPY FOR TOW EMERGENCY BATTERY (FOR ROUND CEILING MOUNT TYPES)



## REMOTE EMERGENCY BATTERY OPTIONS

<p><b>EMRM*</b> - 7W REMOTE EMERGENCY BATTERY (50' MAX)</p>  <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>1.3</td> <td>12.6</td> <td>13.0</td> </tr> </tbody> </table>	A	B	C	1.3	12.6	13.0	<p><b>EMEN*</b> - 7W REMOTE EMERGENCY BATTERY WITH ENCLOSURE (50' MAX)</p>  <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>2.0</td> <td>17.0</td> <td>6.2</td> </tr> </tbody> </table>	A	B	C	2.0	17.0	6.2
A	B	C											
1.3	12.6	13.0											
A	B	C											
2.0	17.0	6.2											

\*OTHER EM BATTERY SIZES AVAILABLE, CONSULT FACTORY

