



| A | B | C | D | E |
|------------------|----------------|------------------|------------------|------------------|
| 13.0 330.2 mm | 0.6 15.8 mm | 10.0 254.0 mm | 19.0 482.6 mm | 12.0 304.8 mm |

10" INCANDESCENT SERIES LENSED SPLAY

200 WATT MAX INCANDESCENT



SG10IN

APPLICATION

Series features a deep reflector and a wide variety of lenses and splays.

FEATURES

- Efficient reflector design with a variety of lens options.
- Posi-lock reflector attachment.
- Integral 5/8" (0.625) plaster ring.
- Maximum wattage label (MWL) for low wattage Incandescent or LED lamps.
- Tool-less ballast access.
- Multi-bar adjustable mounting brackets.

FINISH

Variety of powdercoat and anodized finishes available on reflector.
Eco Black (EB) finish available on frame/ housing.

ELECTRONICS

120 Volt is standard. Use option T277 for 277V supply feed.

CONSTRUCTION

Frame constructed of 20 ga. galvanized steel.
Reflectors spun from .063 high purity aluminum and finished to specification.

LABELS

UL/ ETL Listed for Damp locations. Wet location available.
Manufactured and tested to UL Standard No. 1598.

| | |
|------------------------|---------------------|
| Max Ceiling Thickness: | 1.0 (25.4 mm) |
| Ceiling Cutout: | 10.3 Ø (261.6 mm Ø) |
| Fixture Weight: | 9.0 lbs |

| SERIES | OPTIONS | SPLAY | TRIM OPTIONS | FIXTURE LAMPING* | | | | | | | | | | |
|--|--|--|--|---|------|--------------|-----|------|------|------|-------|------|------------------|------|
| SG10IN- Spectrum Gold 10" Vertical | BH27 - 27" Bar Hangers (Supplied) CB24 - C-Channel Bars CCEA - Chicago Ceiling Plenum CR - Corrosion Resistant T277 - Step Down Transformer 277V to 120V FS - Fuse Holder and Fuse PR - Plaster Ring (Special Depth) TBC - T-bar Clips (Fit BH27) MWL - Max Wattage Label (Specify Wattage) EB - Eco Black Housing Finish | AR1020-WS - White w/ White Flange (Standard) CS - Clear Alzak w/ White Flange CSPF - Clear Alzak w/ Polished Flange SGS - Semi-Diffuse Low-Iridescent w/ White Flange SGSPF - Semi-Diffuse Low-Iridescent w/ Polished Flange RB - Regressed Black Baffled w/ White Flange RBBF - Regressed Black Baffled w/ Black Flange RW - Regressed White Baffled w/ White Flange CC - Custom Color | PG - Prismatic (T73) Lens (Standard) FG - Frosted Glass FL - Fresnel Lens GL - Clear Glass Lens GS - Gasket XB¹ - Cross Blade Louver WL - Wet Location (Consult Factory) | <table border="1"> <thead> <tr> <th>LAMP</th> <th>MAX. WATTAGE</th> </tr> </thead> <tbody> <tr> <td>A21</td> <td>200w</td> </tr> <tr> <td>PS25</td> <td>200w</td> </tr> <tr> <td>PAR38</td> <td>150w</td> </tr> <tr> <td>R40¹</td> <td>200w</td> </tr> </tbody> </table> <p>*Medium Base</p> <p>NOTE: This lamping is for NON-IC only.</p> | LAMP | MAX. WATTAGE | A21 | 200w | PS25 | 200w | PAR38 | 150w | R40 ¹ | 200w |
| LAMP | MAX. WATTAGE | | | | | | | | | | | | | |
| A21 | 200w | | | | | | | | | | | | | |
| PS25 | 200w | | | | | | | | | | | | | |
| PAR38 | 150w | | | | | | | | | | | | | |
| R40 ¹ | 200w | | | | | | | | | | | | | |

¹ For WS, CS, CSPF, SGS and SGSPF Trims Only

EXAMPLE: SG10IN/ AR1020 WS PG

Dimensions shown are nominal. Spectrum Lighting is continually improving products and reserves the right to make changes that will not alter performance or appearance with or without written notice.



| | |
|-----------|-------|
| PROJECT: | TYPE: |
| CAT. NO.: | |

