



| A            | B       | C        | D        | E        |
|--------------|---------|----------|----------|----------|
| 10L-20L: 5.3 | .625    | 6.0      | 13.2     | 9.5      |
| 30L-50L: 6.2 | 15.2 mm | 152.4 mm | 335.3 mm | 241.3 mm |

## RWZO6XT - TRIMLESS / NON-IC RATED

### APPLICATION

Versatile 6" Round aperture recessed LED wall wash with flangeless trim and a wide range of lumens and control options.

### FEATURES

Two-stage optical system for smooth light distribution and focus control. Quick change LED module with interchangeable optics for job site adjustment and fixture maintenance. Shallow plenum design. Tool-less driver and j-box access. Posi-lock trim retention torsion springs.

### TRIM FINISH

A variety of architectural powdercoat and anodized finishes are available. Plaster mesh fitter included.

### ELECTRONICS

LED system features Xicato LED module with proprietary phosphor technology that provides consistent, stable color with CCT control of +/- 100K over life of the light engine. Base CRI is 83 with 2-step MacAdam Ellipse binning. High CRI is 98 with 1x2-step MacAdam Ellipse binning. Variety of electronic 120V/277V and dimming drivers.

### CONSTRUCTION

Housing/frame constructed of #20 ga. galvanized steel to resist corrosion. Flangeless one piece trim spun from 0.063" thick high purity aluminum and finished to specification.

### CODE COMPLIANCE

BAA Compliant. Non-IC rated. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Optional Wet location. Manufactured and tested to UL standards No. 1598/8750.

| WATTAGE TO LUMENS UPDATE    |                              |                            |                               |              |      |
|-----------------------------|------------------------------|----------------------------|-------------------------------|--------------|------|
| CURRENT PART NUMBER EXAMPLE | PREVIOUS PART NUMBER EXAMPLE | SOURCE LUMENS <sup>1</sup> | DELIVERED LUMENS <sup>2</sup> | SYSTEM WATTS | LPW  |
| RWZO6XT10L                  | RWZO6LEDXI15W                | 1000                       | 593                           | 11.1         | 53.4 |
| RWZO6XT13L                  | RWZO6LEDXI20W                | 1300                       | 798                           | 15.0         | 53.2 |
| RWZO6XT20L                  | RWZO6LEDXI33W                | 2000                       | 1228                          | 23.7         | 51.8 |
| RWZO6XT30L                  | RWZO6LEDXI52W                | 3000                       | 1842                          | 34.6         | 53.2 |
| RWZO6XT40L                  | N/A                          | 4000                       | 2364                          | 39.9         | 59.2 |
| RWZO6XT50L                  | N/A                          | 5000                       | 3070                          | 54.0         | 56.9 |

| SERIES  | LUMENS <sup>1</sup> | CCT     | OPTICS                   | DRIVER / DIMMING / VOLTAGE <sup>3</sup>  | OPTIONS <sup>6</sup> | TRIM  | FINISH              | TRIM OPTIONS <sup>12</sup>   |   |      |       |
|---------|---------------------|---------|--------------------------|--|----------------------|---|---------------------|--|---|------|-------|
| RWZO6XT | 83 CRI              |         | WD Wide<br>XW Extra Wide | E Electronic Driver<br>DS10_ 10% 0-10V<br>DO10_ 1% 0-10V<br>DS2W1 1% ELV/MLV, 120V<br>DL3E_4 1% Lutron® EcoSystem®, Fade<br>EL10_ 1%, eldoLED<br>EDO1_ 0.1%, eldoLED<br>DALI_ DALI Control<br>DMXS_5 DMX Standard Configuration<br>DMXC_5 DMX Non-Standard Custom<br>AWN Athena Wireless Node (RF Module Only) | 1 120V<br>2 277V     | BH27 <sup>7</sup> 27" Solid Bars<br>H12 12" - 24" Expandable Bars<br>H06 6" - 12" Expandable Bars<br>CB24 24" C-Channel Bars<br>EM Integral Emergency Battery<br>FS Fusing<br>EB Black Housing<br>CR Corrosion Resistant<br>PR <sup>8</sup> Deep Ceiling Extension<br>AMB Anti Microbial Finish | RW6NXT <sup>9</sup> | SG <sup>10</sup> Semi-Diffuse<br>HZ Haze Full Diffuse<br>MW Matte White<br>MB Matte Black<br>PT Platinum Silver<br>OB Oil Rubbed Bronze<br>CH Charcoal<br>AC Anodic Champagne<br>AS Anodic Sapphire<br>AM Anodic Malachite<br>SN Sun Gold<br>CO Copper Metallic<br>GH Graphite<br>AMB Anti Microbial Finish<br>CC <sup>11</sup> Custom Color | SKX <sup>13</sup> Linear Wall Wash Lens<br>SKW Linear Wall Wash Lens Wet Location |      |       |
|         | 10L                 | 1000 Lm |                          |  |                      |   |                     |  |   | 27K  | 2700K |
|         | 13L                 | 1300 Lm |                          |  |                      |   |                     |  |   | 30K  | 3000K |
|         | 20L                 | 2000 Lm |                          |  |                      |   |                     |  |   | 35K  | 3500K |
|         | 30L                 | 3000 Lm |                          |  |                      |   |                     |  |   | 40K  | 4000K |
|         | 40L                 | 4000 Lm |                          |  |                      |   |                     |  |   |      |       |
|         | 50L                 | 5000 Lm |                          |  |                      |   |                     |  |   |      |       |
|         | 98 CRI              |         |                          |  |                      |   |                     |  |   |      |       |
|         | 10L                 | 1000 Lm |                          |  |                      |   |                     |  |   | 27HK | 2700K |
|         | 13L                 | 1300 Lm |                          |  |                      |   |                     |  |   | 30HK | 3000K |
| 20L     | 2000 Lm             | 35HK    | 3500K                    |  |                      |   |                     |  |   |      |       |
| 30L     | 3000 Lm             | 40HK    | 4000K                    |  |                      |   |                     |  |   |      |       |

### EXAMPLE: RWZO6XT13L35KXWE1/H12/RW6NXTSGSKX

**NOTES:**  
 1 Nominal Source Lumens at Any CCT 2 Nominal Delivered Lumens 83 CRI at Any CCT with XW-SG-SKX 3 Contact Factory for Additional Options 4 50L Not Available with Lutron Drivers 5 Contact Factory 6 See Product Options Page for Details  
 7 Standard Bar Hangers 8 Contact Factory 9 "N" Indicates Flangeless Trim 10 Standard Finish 11 Contact Factory for Special Finishes 12 Contact factory for Special Lenses/Louvers 13 Standard Lens

PROJECT: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_ TYPE: \_\_\_\_\_

