






**MOUNTING BRACKETS**



POWDERCOATED 20 GA.  
ALUMINUM HOUSING



Weight: 24 Lbs

**RC2009FTLEDGV - FLUSH FLAT TRIM / NON-IC RATED**

**APPLICATION**

Recessed square high lumen 2' x 2' fixture for high ceiling area lighting.

**FEATURES**

Designed for recessed dry wall ceiling installation. May be installed from above or below ceiling. Fixture is available from 11000-24000 lumens. Produces even glare free illumination. Lens is mechanically attached to trim.

**TRIM FINISH**

Multi-stage polyester powdercoat process applied on our dedicated paint lines. A wide variety of standard and custom finishes are available. All exposed materials are chromate pretreated to resist corrosion.

**ELECTRONICS**

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 85+. Higher CRI, R9 and custom LED configurations are available; consult factory. A variety of electronic 120V/277V and dimming drivers available.

**CONSTRUCTION**

Housing constructed of #20 ga. aluminum and powdercoated to resist corrosion. Trim fabricated from aluminum and finished to specification.

**CODE COMPLIANCE**

BAA Compliant. Non-IC rated. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE / LUMENS DATA				
PART NUMBER	SOURCE LUMENS <sup>1</sup>	DELIVERED LUMENS <sup>2</sup>	SYSTEM WATTS	LPW
RC2009FTLEDGV110L	11000	8122	88	96.7
RC2009FTLEDGV150L	15000	10828	117	96.7
RC2009FTLEDGV220L	22000	16009	174	92.8
RC2009FTLEDGV240L	24000	17342	188	92.0

SERIES	STYLE	LUMENS <sup>1</sup>	CCT	DRIVER / VOLTAGE <sup>3</sup>	OPTIONS <sup>4</sup>	TRIM	FINISH <sup>5</sup>	TRIM OPTIONS		
RC2009	FT Flush Flanged Trim	LEDGV110L	11000 Lm	27K 2700K	E Electronic Driver DS10 10%, 0-10V DO101 1%, 0-10V DS2W1 1%, ELV/MLV, 120V DALI DALI Control	1 120V 2 277V	FS Fusing EM Emergency Battery	FT2222GV	MW <sup>6</sup> Matte White	FO90 <sup>7</sup> PC <sup>8</sup> White Optical Acrylic Clear Polycarbonate Safety Underlay
		LEDGV150L	15000 Lm	30K 3000K					MB <sup>6</sup> Matte Black	
		LEDGV220L	22000 Lm	35K 3500K					PT <sup>6</sup> Platinum	
		LEDGV240L	24000 Lm	40K 4000K					GW <sup>6</sup> Gloss White	
				50K 5000K					BZ Bronze	
			CH Charcoal							
			GH Graphite							
			SN Sun Gold							
			CC Custom Color							

**EXAMPLE:** RC2009FTLEDGV220L40KE1/FT2222GVMWFO90PC

**NOTES:**  
 1 Nominal Source Lumens at 40K 2 Nominal Delivered Lumens at 40K at 85 CRI with FO Lens. For PC Overlay Apply 0.92 Multiplier by Default 3 Contact Factory for Additional Options  
 4 See Product Options Page For Details 5 Contact Factory for Special Finishes 6 Standard Finishes 7 Standard Lens 8 Supplied



PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.