



**GLASS REFLECTOR PENDANT**  
**DAMP LOCATION**  
**XT SERIES**

PROJECT: \_\_\_\_\_

QUANTITY: \_\_\_\_\_ TYPE: \_\_\_\_\_



GPEXT1014XT  
OR - Orange



GPEXT1014XT  
TQ - Turquoise



GPEXT1014XT  
PG - Pub Green



GPEXT1014XT  
PL - Purple

SERIES	LUMENS <sup>1</sup>	CCT	DRIVER / DIMMING <sup>2</sup>	MOUNTING <sup>3</sup>	FINISH <sup>5</sup>		
GPEXT1014XT GPEXT1214XT	83 CRI		<b>EX</b> Electronic Driver, 120V/277V <b>DO10X</b> 1% 0-10V, 120V/277V <b>DS2W1</b> ELV/MLV, 120V <b>DLTE1</b> Lutron® 2-Wire Forward Phase (MLV), 120V <b>DL3EX</b> 1%, Lutron® EcoSystem®, 120V/277V	<b>HM<sup>4</sup></b> Hang Straight <b>AT<sup>4</sup></b> Hang Straight All Thread <b>PM<sup>4</sup></b> Rigid Pendant Mount <b>CD<sup>4</sup></b> Cord / Cable Mount <b>CM<sup>4</sup></b> Cord Mount <b>EMRM</b> 7W Remote EM <b>EMEN</b> 7W Remote with Enclosure	<b>MW<sup>6</sup></b> Matte White <b>MB<sup>6</sup></b> Matte Black <b>PT<sup>6</sup></b> Platinum Silver <b>CC</b> Custom Color		
	<b>10L</b>	1000 Lm				<b>27K</b>	2700K
	<b>13L</b>	1300 Lm				<b>30K</b>	3000K
	<b>20L</b>	2000 Lm				<b>35K</b>	3500K
	<b>30L</b>	3000 Lm				<b>40K</b>	4000K
	<b>40L</b>	4000 Lm					
	98 CRI						
	<b>10L</b>	1000 Lm				<b>27HK</b>	2700K
	<b>13L</b>	1300 Lm				<b>30HK</b>	3000K
	<b>20L</b>	2000 Lm				<b>35HK</b>	3500K
<b>30L</b>	3000 Lm	<b>40HK</b>	4000K				

EXAMPLE: GPEXT1014XT10L30KEX/CD36MW

**NOTES:**

**1** Nominal Source Lumens at Any CCT **2** Contact Factory for Additional Options **3** See Mounting Page for Details on Components and Finishes **4** Specify Length in Inches: See Mounting Page for Available Lengths **5** Reference Color Sheet Located on Product Webpage for Full List of Available Colors/Consult Factory for Special Finishes **6** Standard Finishes





# GLASS REFLECTOR PENDANT


## DAMP LOCATION

### XT SERIES

LUMENS / WATTAGE DATA				
PART NUMBER	SOURCE LUMENS <sup>1</sup>	DELIVERED LUMENS <sup>2</sup>	SYSTEM WATTS	LPW
GPEXT1014XT10L	1000	881	9.1	96.8
GPEXT1014XT13L	1300	1187	13.0	91.3
GPEXT1014XT20L	2000	1826	21.7	84.1
GPEXT1014XT30L	3000	2740	32.6	84.0
GPEXT1014XT40L	4000	3517	37.9	92.8

<sup>1</sup>Nominal Source Lumens at Any CCT <sup>2</sup> Nominal Delivered Lumens at Any CCT

### HOUSING DIMENSIONS



Dimensioned with **GPEXT1014XT**

SERIES	A	B
GPEXT1014XT	11.2	20.0
GPEXT1214XT	13.3	22.4

### APPLICATION

The Glass Reflector Pendant's distinctive styling will enhance any space with efficient lighting and a bold design.

### FEATURES

Speculume series fixtures offer simple contemporary style with functional luminaire performance. All fixtures are designed and manufactured in our factory. Reflector pendant is available in two sizes with direct lighting. Separate finishes may be chosen for fixture and mounting. Interchangeable LED module for ease of maintenance and upgradable. A variety of mounting and finish options available.

### FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. A wide variety of standard and custom finishes are available. All exposed materials are chromate pretreated to resist corrosion.

### ELECTRONICS

LED system features Xicato LED module with proprietary phosphor technology that provides consistent stable color with CCT control of +/- 100K over life of the light engine. Base CRI is 83 with 1 x 2-step MacAdam Ellipse binning. High CRI is 98 with 1 x 2-step MacAdam Ellipse binning. Variety of electronic 120V/277V and dimming drivers.

### CONSTRUCTION

Glass is molded blown white cased inside and soft etched outside for even glare free illumination. Passive extruded aluminum heatsink for optimal thermal management. OSD diffusion optic lens standard

### CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.

### SERIES SIZES

GPEXT1014XT



GPEXT1214XT




### CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

**HM / AT / PM**

HANG STRAIGHT / ALL THREAD / PENDANT



GPEXT1014XT SHOWN WITH PM

**CD**

CORD / CABLE MOUNT



GPEXT1014XT SHOWN WITH CD

**CM**

CORD MOUNT



GPEXT1014XT SHOWN WITH CM



# MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION. NOTE: THIS IS TYPICAL OF SPECULUME SPECIFICATION FOR PENDANT MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.



## CEILING MOUNTING

<p><b>RDC5</b> - SMALL DRIVER CANOPY (STANDARD) MOUNTS TO 4" OCTO J-BOX</p> <p><b>CP13</b> - LARGE DRIVER CANOPY</p>	<p><b>HM*</b> HANG STRAIGHT 45° SWIVEL 1/2" STEM - 3/8" NPT</p> <p>ORDER: <b>HM</b> (Length) SPECIFY LENGTH: HM3 - 3"    HM24 - 24" HM6 - 6"    HM36 - 36" HM12 - 12"    HM48 - 48" HM18 - 18"    HM72 - 72" <b>HMLC(XX)</b> Custom Length (Specify in Inches)</p>	<p><b>AT**</b> HANG STRAIGHT ALL THREAD 45° SWIVEL 1/2" STEM - 1/4" IP</p> <p>ORDER: <b>AT</b> (Length) SPECIFY LENGTH: AT12 - 12"    AT48 - 48" AT24 - 24"    AT60 - 60" AT36 - 36"    AT72 - 72" <small>FIELD-CUT, THREADED PIPE TO LENGTH REQUIRED. CUT PIPE COVER - 3/4" SHORTER THAN THREADED PIPE. SUP. PIPE COVER OVER THREADED PIPE.</small></p>	<p><b>PM*</b> RIGID PENDANT MOUNT RIGID 1/2" STEM - 3/8" NPT</p> <p>ORDER: <b>PM</b> (Length) SPECIFY LENGTH: PM3 - 3"    PM24 - 24" PM6 - 6"    PM36 - 36" PM12 - 12"    PM48 - 48" PM18 - 18"    PM72 - 72" <b>PMLLC(XX)</b> Custom Length (Specify in Inches)</p>	<p><b>CD</b> CORD / CABLE MOUNT SJ CORD WITH 1/16 SS CABLE</p> <p>ORDER: <b>CD</b> (Length) SPECIFY LENGTH: CD36 - 36" CD72 - 72" CD144 - 144" <b>CDLC(XX)</b> Custom Length (Specify in Inches)</p>	<p><b>CM</b> CORD MOUNT SJ CORD WITH STRAIN RELIEF</p> <p>ORDER: <b>CM</b> (Length) SPECIFY LENGTH: CM36 - 36" CM72 - 72" CM144 - 144" <b>CMLC(XX)</b> Custom Length (Specify in Inches)</p>
--	--	--	--	--	--

\*MAXIMUM ONE PIECE STEM LENGTH IS 72". \*\*MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS. \*\*ORDER IN 12" INCREMENTS. ODD SIZES MAY BE FIELD CUT

## EMERGENCY BATTERY OPTIONS

**EMCR** - LARGE DRIVER CANOPY FOR 10W EMERGENCY BATTERY (FOR ROUND CEILING MOUNT TYPES)

## REMOTE EMERGENCY BATTERY OPTIONS

<p><b>EMRM*</b> - 7W REMOTE EMERGENCY BATTERY (50' MAX)</p> <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>1.3</td> <td>12.6</td> <td>13.0</td> </tr> </tbody> </table>	A	B	C	1.3	12.6	13.0	<p><b>EMEN*</b> - 7W REMOTE EMERGENCY BATTERY WITH ENCLOSURE (50' MAX)</p> <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>2.0</td> <td>17.0</td> <td>6.2</td> </tr> </tbody> </table>	A	B	C	2.0	17.0	6.2
A	B	C											
1.3	12.6	13.0											
A	B	C											
2.0	17.0	6.2											

\*OTHER EM BATTERY SIZES AVAILABLE. CONSULT FACTORY

