



DECORATIVE

**ICON 8" GLASS PENDANT**  
**DAMP LOCATION**  
**XT SERIES**

PROJECT: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_ TYPE: \_\_\_\_\_



DP8XT  
 EG - Evergreen



DP8XT  
 OR - Orange



DP8XT  
 BZ - Bronze



DP8XT  
 PT - Platinum Silver

SERIES	LUMENS <sup>1</sup>	CCT	DRIVER / DIMMING <sup>2</sup>	MOUNTING <sup>4</sup>	FINISH <sup>8</sup>
DP8XT	10L 1000 Lm	83 CRI	<b>EX</b> Electronic Driver, 120V/277V <b>DO10X</b> 1%, 0-10V, 120V/277V <b>DS2W1</b> ELV/MLV, 120V <b>DLTE1</b> <sup>3</sup> Lutron® 2-Wire Forward Phase (MLV), 120V <b>DL3EX</b> <sup>3</sup> 1%, Lutron® EcoSystem®, 120V/277V	<b>RDC5</b> <sup>5</sup> Small Driver Canopy <b>CP13</b> <sup>3</sup> Large Driver Canopy <b>HM</b> <sup>6</sup> Hang Straight <b>AT</b> <sup>6</sup> Hang Straight All Thread <b>PM</b> <sup>6</sup> Rigid Pendant Mount <b>CD</b> <sup>6</sup> Cord / Cable Mount <b>CM</b> <sup>6</sup> Cord Mount <b>EMCR</b> <sup>7</sup> 10W Canopy Mounted EM <b>EMRM</b> 7W Remote EM <b>EMEN</b> 7W Remote with Enclosure	<b>MW</b> <sup>9</sup> Matte White <b>MB</b> <sup>9</sup> Matte Black <b>PT</b> <sup>9</sup> Platinum Silver <b>CC</b> Custom Color  See Page 4 for Full Range of Color Options (83-90081)
	13L 1300 Lm	27K 2700K			
	20L 2000 Lm	30K 3000K			
	30L 3000 Lm	35K 3500K			
		40K 4000K			
		98 CRI			
		27HK 2700K			
		30HK 3000K			
		35HK 3500K			
		40HK 4000K			

EXAMPLE: DP8XT10L35KEX/RDC5CD36MW

**NOTES:**

1 Nominal Source Lumens at Any CCT 2 Contact Factory for Additional Options 3 CP13 Required for Lutron Drivers 4 See Mounting Page for Details on Components and Finishes  
 5 Required for All Drivers Excluding Lutron Drivers 6 Specify Length in Inches; See Mounting Page for Available Lengths 7 EMCR Replaces RDC5 or CP13 8 See Color Page for More Options/Consult Factory for Special Finishes 9 Standard Finishes





DECORATIVE

# ICON 8" GLASS PENDANT


## DAMP LOCATION

### XT SERIES

LUMENS / WATTAGE DATA				
PART NUMBER	SOURCE LUMENS <sup>1</sup>	DELIVERED LUMENS <sup>2</sup>	SYSTEM WATTS	LPW
DP8XT10L	1000	782	9.1	85.9
DP8XT13L	1300	1053	13.0	81.0
DP8XT20L	2000	1620	20.7	78.3
DP8XT30L	3000	2430	32.6	74.5

<sup>1</sup> Nominal Source Lumens at Any CCT    <sup>2</sup> Nominal Delivered Lumens at Any CCT

## HOUSING DIMENSIONS



A	B
8.6	14.8
218.4 mm	375.9 mm

### APPLICATION

The Icon Pendant series features a classic glass shade for decorative area lighting.

### FEATURES

SpecLume series fixtures offer contemporary style with functional luminaire performance. Separate finishes may be chosen for fixture and mounting. Interchangeable LED module for ease of maintenance. Electronic LED Driver in canopy for thermal management. A variety of mounting and finish options available.

### FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. A wide variety of standard and custom finishes are available. All exposed materials are chromate pretreated to resist corrosion.

### ELECTRONICS

LED system features Xicato LED module with proprietary phosphor technology that provides consistent stable color with CCT control of +/- 100K over life of the light engine. Base CRI is 83 with 1 x 2-step MacAdam Ellipse binning. High CRI is 98 with 1 x 2-step MacAdam Ellipse binning. Variety of electronic 120V/277V and dimming drivers.

### CONSTRUCTION

Glass is molded blown white cased inside and soft etched outside for even glare free illumination. Passive extruded aluminum heatsink for optimal thermal management. OSD diffusion optic lens standard.

### CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.

## CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

### HM / AT / PM

HANG STRAIGHT / ALL THREAD / PENDANT



DP8XT SHOWN WITH RDC5PM

### CD

CORD / CABLE MOUNT



DP8XT SHOWN WITH RDC5CD

### CM

CORD MOUNT



DP8XT SHOWN WITH RDC5CM



# MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION. NOTE: THIS IS TYPICAL OF SPECULUME SPECIFICATION FOR PENDANT MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.



## CEILING MOUNTING

<p><b>RDC5</b> - SMALL DRIVER CANOPY (STANDARD) MOUNTS TO 4" OCTO J-BOX</p> <p><b>CP13</b> - LARGE DRIVER CANOPY</p>	<p><b>HM*</b> HANG STRAIGHT 45° SWIVEL 1/2" STEM - 3/8" NPT</p> <p>ORDER: <b>HM</b> (Length) SPECIFY LENGTH: HM3 - 3" HM24 - 24" HM6 - 6" HM36 - 36" HM12 - 12" HM48 - 48" HM18 - 18" HM72 - 72" <b>HMLC(XX)</b> Custom Length (Specify in Inches)</p>	<p><b>AT**</b> HANG STRAIGHT ALL-THREAD 45° SWIVEL 1/2" STEM - 1/4" IP</p> <p>ORDER: <b>AT</b> (Length) SPECIFY LENGTH: AT12 - 12" AT24 - 24" AT36 - 36" <small>FIELD CUT: INCREASED PIPE TO LENGTH NEEDED. CUT PIPE COVER 3/4" SHORTER THAN INCREASED PIPE. SUPPLY PIPE COVER OVER INCREASED PIPE.</small></p>	<p><b>PM*</b> RIGID PENDANT MOUNT RIGID 1/2" STEM - 3/8" NPT</p> <p>ORDER: <b>PM</b> (Length) SPECIFY LENGTH: PM3 - 3" PM24 - 24" PM6 - 6" PM36 - 36" PM12 - 12" PM48 - 48" PM18 - 18" PM72 - 72" <b>PMLC(XX)</b> Custom Length (Specify in Inches)</p>	<p><b>CD</b> CORD / CABLE MOUNT SJ CORD WITH 1/16 SS CABLE</p> <p>ORDER: <b>CD</b> (Length) SPECIFY LENGTH: CD36 - 36" CD72 - 72" CD144 - 144" <b>CDLC(XX)</b> Custom Length (Specify in Inches)</p>	<p><b>CM</b> CORD MOUNT SJ CORD WITH STRAIN RELIEF</p> <p>ORDER: <b>CM</b> (Length) SPECIFY LENGTH: CM36 - 36" CM72 - 72" CM144 - 144" <b>CMLC(XX)</b> Custom Length (Specify in Inches)</p>
--	--	---	---	--	--

\*MAXIMUM ONE PIECE STEM LENGTH IS 72". \*\*MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS. \*\*ORDER IN 12" INCREMENTS. ODD SIZES MAY BE FIELD CUT

## EMERGENCY BATTERY OPTIONS

**EMCR** - LARGE DRIVER CANOPY FOR 10W EMERGENCY BATTERY (FOR ROUND CEILING MOUNT TYPES)

## REMOTE EMERGENCY BATTERY OPTIONS

<p><b>EMRM*</b> - 7W REMOTE EMERGENCY BATTERY (50' MAX)</p> <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>1.3</td> <td>12.6</td> <td>13.0</td> </tr> </tbody> </table>	A	B	C	1.3	12.6	13.0	<p><b>EMEN*</b> - 7W REMOTE EMERGENCY BATTERY WITH ENCLOSURE (50' MAX)</p> <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>2.0</td> <td>17.0</td> <td>6.2</td> </tr> </tbody> </table>	A	B	C	2.0	17.0	6.2
A	B	C											
1.3	12.6	13.0											
A	B	C											
2.0	17.0	6.2											

\*OTHER EM BATTERY SIZES AVAILABLE. CONSULT FACTORY



# COLOR OPTIONS - POWDER COAT PAINT FINISHES

NOTE: NO PRINTED IMAGE CAN EQUAL THE EXACT COLOR OF FINISH ON METAL.  
SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.



## STANDARD CORD / STEM / CANOPY FINISHES

FIXTURE COLOR	STANDARD CORD COLOR	STANDARD CANOPY / STEM COLOR
Matte White, Textured White	Matte White	Matte White
Gloss White	Matte White	Gloss White
Matte Black, Gloss Black, Textured Black	Matte Black	Matte Black
All Others	Matte Black	Same Color as Fixture
Custom Color	Contact Factory	Contact Factory

## PAINT TIMES

TIER	COST	AVERAGE PAINT TIME*
Tier 1 - Standard Finishes	\$	⌚
Tier 2 - Typical Finishes	\$\$	⌚⌚
Custom Color	Contact Factory	Contact Factory

\*CONTACT FACTORY FOR SPECIFIC PRODUCT LEAD TIMES

## TIER 1 - STANDARD FINISHES



## TIER 2 - TYPICAL FINISHES



## CUSTOM COLOR FINISHES

CONTACT FACTORY

**CC**  
Custom Color



\*UNAVAILABLE FOR WET LOCATION

