



ICON 8" ALUMINUM PENDANT

DAMP LOCATION

XT SERIES

PROJECT: _____
 QUANTITY: _____ TYPE: _____



AP8XT
 SN - Sun Gold
 MBI - Matte Black Interior



AP8XT
 PT - Platinum Silver
 MWI - Matte White Interior



AP8XT
 MW - Matte White
 MBI - Matte Black Interior



AP8XT
 CH - Charcoal
 PTI - Platinum Silver

SERIES	LUMENS ¹	CCT	DRIVER / DIMMING ²	MOUNTING ⁴	INTERIOR ⁸	FINISH ⁹	
AP8XT	10L	1000 Lm	83 CRI	EX Electronic Driver, 120V/277V DO10X 1%, 0-10V, 120V/277V DS2W1 ELV/MLV, 120V DLTE1¹ Lutron® 2-Wire Forward Phase (MLV), 120V DL3EX³ 1%, Lutron® EcoSystem®, 120V/277V	RDC5⁵ Small Driver Canopy CP13³ Large Driver Canopy HM⁵ Hang Straight AT⁶ Hang Straight All Thread PM⁶ Rigid Pendant Mount CD⁶ Cord / Cable Mount CM⁶ Cord Mount EMCR⁷ 10W Canopy Mounted EM EMRM 7W Remote EM EMEN 7W Remote with Enclosure	MWI⁹ Matte White CCI Custom Color FCI Fixture Color Interior	MW⁹ Matte White MB⁹ Matte Black PT⁹ Platinum Silver CC Custom Color
	13L	1300 Lm	27K 2700K				
	20L	2000 Lm	30K 3000K				
	30L	3000 Lm	35K 3500K				
			40K 4000K				
			98 CRI				
			27HK 2700K				
			30HK 3000K				
			35HK 3500K				
			40HK 4000K				

EXAMPLE: AP8XT10L35KEX/RDC5CD36MWIGH

NOTES:
 1 Nominal Source Lumens at Any CCT 2 Contact Factory for Additional Options 3 CP13 Required for Lutron Drivers 4 See Mounting Page for Details on Components and Finishes 5 Required for All Drivers Excluding Lutron Drivers 6 Specify Length in Inches: See Mounting Page for Available Lengths 7 EMCR Replaces RDC5 or CP13 8 Reference Color Sheet Located on Product Webpage for Full List of Available Colors/Consult Factory for Special Finishes 9 Standard Finishes





ICON 8" ALUMINUM PENDANT


DAMP LOCATION

XT SERIES

LUMENS / WATTAGE DATA				
PART NUMBER	SOURCE LUMENS ¹	DELIVERED LUMENS ²	SYSTEM WATTS	LPW
AP8XT10L	1000	435	8	56
AP8XT13L	1300	585	11	52
AP8XT20L	2000	897	18	50
AP8XT30L	3000	1359	30	45

¹ Nominal Source Lumens at Any CCT ² Nominal Delivered Lumens at 83 CRI at Any CCT with MWI Finish

HOUSING DIMENSIONS



A	B
8.4 213.4 mm	14.8 375.9 mm

APPLICATION

The Icon Pendant series features a classic curved hand spun aluminum shade for decorative area lighting.

FEATURES

Speculume series fixtures offer contemporary style with functional luminaire performance. Separate finishes may be chosen for fixture and mounting. Interchangeable LED module for ease of maintenance. Electronic LED Driver in canopy for thermal management. A variety of mounting and finish options available.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. A wide variety of standard and custom finishes are available. Specify inside and outside finish. Matte white interior is standard.

ELECTRONICS

LED system features Xicato LED module with proprietary phosphor technology that provides consistent stable color with CCT control of +/- 100K over life of the light engine. Base CRI is 83 with 1 x 2-step MacAdam Ellipse binning. High CRI is 98 with 1 x 2-step MacAdam Ellipse binning. Variety of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Shade is spun in our factory from 0.063 high purity aluminum. Passive extruded aluminum heatsink for optimal thermal management. OSD diffusion optic lens standard.

CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.

CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

HM / AT / PM

HANG STRAIGHT / ALL THREAD / PENDANT



AP8XT SHOWN WITH RDC5PM

CD

CORD / CABLE MOUNT



AP8XT SHOWN WITH RDC5CD

CM

CORD MOUNT



AP8XT SHOWN WITH RDC5CM





ICON 8" ALUMINUM PENDANT

XT SERIES / PHOTOMETRIC DATA

DECORATIVE

AP8XT 30L 35K XX MWI

CANDLEPOWER CURVE TEST SP-00589_5	INTENSITY CANDELA 0° AZIMUTH	ZONAL LUMENS		SINGLE UNIT: PERFORMANCE INITIAL FOOTCANDLES BASED ON IES BEAM ANGLE				MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT							
		0°	0° - 10°	122	9%	Mounting Height AFF	FC at Center on Floor	Beam Diameter	FC at Beam Edge	Ceiling Height	Fixture Spacing	RCR 3		RCR 5	
	0°	1,311	0° - 10°	423	31%	6.5'	31 fc	6.3'	11 fc	12'	6'	31	0.77	18	0.54
	5°	1,284	0° - 20°	738	54%	7.5'	23 fc	7.3'	9 fc	15'	8'	16	0.40	21	0.62
	15°	1,091	0° - 30°	962	71%	8.5'	18 fc	8.2'	7 fc	18'	10'	9	0.24	12	0.37
	25°	690	0° - 40°	1,239	91%	10.0'	13 fc	9.7'	5 fc	Delivered Illuminance Rating: (DIR)					
	35°	353	0° - 60°	1,351	99%	12.0'	9 fc	11.6'	3 fc	39 FC per W/Sq. Ft. 33 FC per W/Sq. Ft.					
	45°	205	0° - 80°	1,359	100%	14.0'	7 fc	13.5'	2 fc	2' Suspension Length to luminous height midpoint Square rooms used for multiple units: RCR 3: Length & Width = Ceiling Ht. - 5.5' x 3.33 RCR 5: Length & Width = Ceiling Ht. - 5.5' x 2.00 * Average Footcandles at 2.5' Above Floor					
	55°	129	Downlight	1,359	100%	16.0'	5 fc	15.5'	2 fc						
	90°	1	Total	1,359	100%	20.0'	3 fc	19.3'	1 fc						

Delivered Lumens: 1,359
Luminaire Watts: 30.2
LER: 45.00

CRI: 80

Beam Angle: 52°
Spacing Ratio: 0.81

Lumen Multiplier: 10L x 0.32, 13L x 0.43, 20L x 0.67
CCT Multiplier: Same for all available CCT's

AP8XT 30L 35HK XX MWI

CANDLEPOWER CURVE TEST SP-00589_3	INTENSITY CANDELA 0° AZIMUTH	ZONAL LUMENS		SINGLE UNIT: PERFORMANCE INITIAL FOOTCANDLES BASED ON IES BEAM ANGLE				MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT							
		0°	0° - 10°	123	9%	Mounting Height AFF	FC at Center on Floor	Beam Diameter	FC at Beam Edge	Ceiling Height	Fixture Spacing	RCR 3		RCR 5	
	0°	1,333	0° - 10°	429	30%	6.5'	32 fc	6.4'	11 fc	12'	6'	32	0.92	19	0.64
	5°	1,301	0° - 20°	754	53%	7.5'	24 fc	7.3'	9 fc	15'	8'	16	0.47	21	0.73
	15°	1,104	0° - 30°	989	70%	8.5'	18 fc	8.3'	7 fc	18'	10'	10	0.28	13	0.44
	25°	713	0° - 40°	1,283	91%	10.0'	13 fc	9.8'	5 fc	Delivered Illuminance Rating: (DIR)					
	35°	370	0° - 60°	1,403	99%	12.0'	9 fc	11.8'	3 fc	34 FC per W/Sq. Ft. 29 FC per W/Sq. Ft.					
	45°	217	0° - 80°	1,411	100%	14.0'	7 fc	13.7'	2 fc	2' Suspension Length to luminous height midpoint Square rooms used for multiple units: RCR 3: Length & Width = Ceiling Ht. - 5.5' x 3.33 RCR 5: Length & Width = Ceiling Ht. - 5.5' x 2.00 * Average Footcandles at 2.5' Above Floor					
	55°	137	Downlight	1,411	100%	16.0'	5 fc	15.7'	2 fc						
	90°	1	Total	1,411	100%	20.0'	3 fc	19.6'	1 fc						

Delivered Lumens: 1,411
Luminaire Watts: 35.9
LER: 39.30

CRI: 98

Beam Angle: 52°
Spacing Ratio: 0.82

Lumen Multiplier: 10L x 0.32, 13L x 0.43, 20L x 0.67
CCT Multiplier: Same for all available CCT's



MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION. NOTE: THIS IS TYPICAL OF SPECLUME SPECIFICATION FOR PENDANT MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.



CEILING MOUNTING

<p>RDC5 - SMALL DRIVER CANOPY (STANDARD) MOUNTS TO 4" OCTO J-BOX</p> <p>CP13 - LARGE DRIVER CANOPY</p>	<p>HM* HANG STRAIGHT 45° SWIVEL 1/2" STEM - 3/8" NPT</p> <p>ORDER: HM (Length) SPECIFY LENGTH: HM3 - 3" HM24 - 24" HM6 - 6" HM36 - 36" HM12 - 12" HM48 - 48" HM18 - 18" HM72 - 72" HMLC(XX) Custom Length (Specify in Inches)</p>	<p>AT** HANG STRAIGHT ALL THREAD 45° SWIVEL 1/2" STEM - 1/4" IP</p> <p>ORDER: AT (Length) SPECIFY LENGTH: AT12 - 12" AT48 - 48" AT24 - 24" AT60 - 60" AT36 - 36" AT72 - 72" <small>FIELD-CUT, THREADED PIPE TO LENGTH REQUIRED; CUT PIPE COVER - 3/4" SHORTER THAN THREADED PIPE; SUP. PIPE COVER OVER THREADED PIPE</small></p>	<p>PM* RIGID PENDANT MOUNT RIGID 1/2" STEM - 3/8" NPT</p> <p>ORDER: PM (Length) SPECIFY LENGTH: PM3 - 3" PM24 - 24" PM6 - 6" PM36 - 36" PM12 - 12" PM48 - 48" PM18 - 18" PM72 - 72" PMLLC(XX) Custom Length (Specify in Inches)</p>	<p>CD CORD / CABLE MOUNT SJ CORD WITH 1/16 SS CABLE</p> <p>ORDER: CD (Length) SPECIFY LENGTH: CD36 - 36" CD72 - 72" CD144 - 144" CDLC(XX) Custom Length (Specify in Inches)</p>	<p>CM CORD MOUNT SJ CORD WITH STRAIN RELIEF</p> <p>ORDER: CM (Length) SPECIFY LENGTH: CM36 - 36" CM72 - 72" CM144 - 144" CMLC(XX) Custom Length (Specify in Inches)</p>
--	--	---	--	--	--

*MAXIMUM ONE PIECE STEM LENGTH IS 72". **MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS. **ORDER IN 12" INCREMENTS. ODD SIZES MAY BE FIELD CUT

EMERGENCY BATTERY OPTIONS

EMCR - LARGE DRIVER CANOPY FOR 10W EMERGENCY BATTERY (FOR ROUND CEILING MOUNT TYPES)

REMOTE EMERGENCY BATTERY OPTIONS

<p>EMRM* - 7W REMOTE EMERGENCY BATTERY (50' MAX)</p> <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>1.3</td> <td>12.6</td> <td>13.0</td> </tr> </tbody> </table>	A	B	C	1.3	12.6	13.0	<p>EMEN* - 7W REMOTE EMERGENCY BATTERY WITH ENCLOSURE (50' MAX)</p> <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>2.0</td> <td>17.0</td> <td>6.2</td> </tr> </tbody> </table>	A	B	C	2.0	17.0	6.2
A	B	C											
1.3	12.6	13.0											
A	B	C											
2.0	17.0	6.2											

*OTHER EM BATTERY SIZES AVAILABLE. CONSULT FACTORY

