





Α	В	С	D	E	F		
1.6	40.0	30.0	20.0	18.4	8.0		
40.6 mm	1016 mm	762 mm	508 mm	467.4 mm	203.2 mm		

PROJECT:	
QUANTITY:	TYPE:

3XCY0830RDFALEDGV

APPLICATION

Cylindro 8" Pendant cluster features a clean design with a 3 luminaire grouping. 18" diameter central canopy with adjustable cord lengths for ease of installation.

FEATURES

Fixtures are designed and manufactured in our factory. Cylindro series acrylic pendant are fabricated from opal acrylic. LED module is upgradable for ease of maintenance. Electronic LED Driver in canopy for thermal management. A variety of finishes and mounting is available.

Multi-stage polyester powder-coat process applied on our dedicated paint lines. See mounting and color pages for standard finishes.

ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3 step MacAdam Ellipse binning. Standard CRI: 85+. Higher CRI, R9 and custom LED configurations are available; consult factory. Variety of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Fixtures constructed of machined and formed aluminum and opal acrylic. Carbon gasket for optimal thermal management.

CODE COMPLIANCE

BAA Compliant. ETL listed for damp locations. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE / LUMENS DATA								
PART NUMBER	SOURCE LUMENS ¹	SYSTEM WATTS						
3XCY0830RDFALEDGV15L	4500	27						
3XCY0830RDFALEDGV27L	8100	48						

SERIES	LU	MENS ¹	сст		DRIVER / DIMMING ²		MOUNTING ³		OPTIONS ⁵		FINISH ⁷	
3XCY0830RDFALEDGV		1500 Lm 2700 Lm	30K 35K	2700K 3000K 3500K 4000K	DO10X	Electronic Driver, 120V/277V 1% 0-10V Dimming, 120V/277V 2 Wire Phase Dimming, 120V		Driver Housing / Ceiling Canopy	_	Cord Mounting Adjustable Length Pendant Mount	MB ⁸ PT ⁸	Matte White Matte Black Platinum Silver Custom Color

EXAMPLE: 3XCY0830RDFALEDGV15L30KEXCP18CMX36MW

NOTES:

1 Nominal Source Lumens at 3500K 2 Contact Factory for Additional Options 3 See Mounting Page for Details on Components and Finishes 4 Required for Driver 5 See Product Options Page for Details 6 Specify Length in Inches: See Mounting Page for Available Lengths 7 Reference Color Sheet Located on Product Webpage for Full List of Available Colors 8 Standard Finishes



