



12" LAYERED GLASS PENDANT
DAMP LOCATION
 XT SERIES

PROJECT: _____
 QUANTITY: _____ TYPE: _____



LG1212XT
 LG - Lime Green



LG1212XT
 VE - Verde Green



LG1212XT
 MT - Textured Silver



LG1212XT
 AY - Aero Yellow

SERIES	LUMENS ¹	CCT	DRIVER / DIMMING ²	MOUNTING ⁴	FINISH ⁸	
LG1212XT	10L	1000 Lm	EX Electronic Driver, 120V/277V DO10X 1% 0-10V, 120V/277V DS2W1 ELV/MLV, 120V DLTE1³ Lutron® 2-Wire Forward Phase (MLV), 120V DL3EX³ 1%, Lutron® EcoSystem®, 120V/277V	RDC5⁵ Small Driver Canopy CP13³ Driver Housing HM⁶ Hang Straight AT⁶ Hang Straight All Thread PM⁶ Rigid Pendant Mount CD⁶ Cord / Cable Mount CM⁶ Cord Mount EMCR⁷ 7W Canopy Mounted EM EMRM 7W Remote EM EMEN 7W Remote with Enclosure	MW⁹ Matte White MB⁹ Matte Black PT⁹ Platinum Silver CC Custom Color	
	13L	1300 Lm				
	20L	2000 Lm				
	30L	3000 Lm				
	83 CRI					
		27K				2700K
		30K				3000K
		35K				3500K
		40K				4000K
	98 CRI					
	27HK	2700K				
	30HK	3000K				
	35HK	3500K				
	40HK	4000K				

EXAMPLE: LG1212XT10L27KEXRDC5CD36MW

NOTES:
 1 Nominal Source Lumens At Any CCT 2 Contact Factory for Additional Options 3 CP13 Required for Lutron Drivers 4 See Mounting Page for Details on Components and Finishes
 5 Required for All Drivers Excluding Lutron Drivers 6 Specify Length in Inches: See Mounting Page for Available Lengths 7 EMCR Replaces RDC5 or CP13
 8 Reference Color Sheet Located on Product Webpage for Full List of Available Colors/Consult Factory for Special Finishes 9 Standard Finishes






DECORATIVE

12" LAYERED GLASS PENDANT DAMP LOCATION XT SERIES

LUMENS / WATTAGE DATA		
PART NUMBER	SOURCE LUMENS ¹	SYSTEM WATTS
LG1212XT10L	1000	8
LG1212XT13L	1300	12
LG1212XT20L	2000	20
LG1212XT30L	3000	30

¹ Nominal Source Lumens at 35K

HOUSING DIMENSIONS



A	B
11.5 292.1 mm	16.0 406.4 mm

APPLICATION

12" Layered Glass Pendant series features a classic curved molded glass shade for decorative area lighting.

FEATURES

Speculume series fixtures offer contemporary style with functional luminaire performance. Separate finishes may be chosen for fixture and mounting. Interchangeable LED module for ease of maintenance. Electronic LED Driver in canopy for thermal management. A variety of mounting and finish options available.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. A wide variety of standard and custom finishes are available. All exposed materials are chromate pretreated to resist corrosion.

ELECTRONICS

LED system features Xicato LED module with proprietary phosphor technology that provides consistent stable color with CCT control of +/- 100K over life of the light engine. Base CRI is 83 with 1 x 2-step MacAdam Ellipse binning. High CRI is 98 with 1 x 2-step MacAdam Ellipse binning. Variety of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Glass shade is white cased inside and soft etched outside for even glare free illumination. Passive extruded aluminum heatsink for optimal thermal management. OSD diffusion optic lens standard.

CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.

CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

HM / AT / PM

HANG STRAIGHT / ALL THREAD / PENDANT



LG1212XT SHOWN WITH PM

CD

CORD / CABLE MOUNT



LG1212XT SHOWN WITH CD

CM

CORD MOUNT



LG1212XT SHOWN WITH CM



MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION. NOTE: THIS IS TYPICAL OF SPECLUME SPECIFICATION FOR PENDANT MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.



CEILING MOUNTING

<p>RDC5 - SMALL DRIVER CANOPY (STANDARD) MOUNTS TO 4" OCTO J-BOX</p> <p>CP13 - LARGE DRIVER CANOPY</p>	<p>HM* HANG STRAIGHT 45° SWIVEL 1/2" STEM - 3/8" NPT</p> <p>ORDER: HM (Length) SPECIFY LENGTH: HM3 - 3" HM24 - 24" HM6 - 6" HM36 - 36" HM12 - 12" HM48 - 48" HM18 - 18" HM72 - 72" HMLC(XX) Custom Length (Specify in Inches)</p>	<p>AT** HANG STRAIGHT ALL THREAD 45° SWIVEL 1/2" STEM - 1/4" IP</p> <p>ORDER: AT (Length) SPECIFY LENGTH: AT12 - 12" AT48 - 48" AT24 - 24" AT60 - 60" AT36 - 36" AT72 - 72" <small>FIELD-CUT, THREADED PIPE TO LENGTH NEEDED. CUT PIPE COVER - 3/4" SHORTER THAN THREADED PIPE. SUP. PIPE COVER OVER THREADED PIPE.</small></p>	<p>PM* RIGID PENDANT MOUNT RIGID 1/2" STEM - 3/8" NPT</p> <p>ORDER: PM (Length) SPECIFY LENGTH: PM3 - 3" PM24 - 24" PM6 - 6" PM36 - 36" PM12 - 12" PM48 - 48" PM18 - 18" PM72 - 72" PMLLC(XX) Custom Length (Specify in Inches)</p>	<p>CD CORD / CABLE MOUNT SJ CORD WITH 1/16 SS CABLE</p> <p>ORDER: CD (Length) SPECIFY LENGTH: CD36 - 36" CD72 - 72" CD144 - 144" CDLC(XX) Custom Length (Specify in Inches)</p>	<p>CM CORD MOUNT SJ CORD WITH STRAIN RELIEF</p> <p>ORDER: CM (Length) SPECIFY LENGTH: CM36 - 36" CM72 - 72" CM144 - 144" CMLC(XX) Custom Length (Specify in Inches)</p>
--	--	--	--	--	--

*MAXIMUM ONE PIECE STEM LENGTH IS 72". **MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS. **ORDER IN 12" INCREMENTS. ODD SIZES MAY BE FIELD CUT

EMERGENCY BATTERY OPTIONS

EMCR - LARGE DRIVER CANOPY FOR 10W EMERGENCY BATTERY (FOR ROUND CEILING MOUNT TYPES)

REMOTE EMERGENCY BATTERY OPTIONS

<p>EMRM* - 7W REMOTE EMERGENCY BATTERY (50' MAX)</p> <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>1.3</td> <td>12.6</td> <td>13.0</td> </tr> </tbody> </table>	A	B	C	1.3	12.6	13.0	<p>EMEN* - 7W REMOTE EMERGENCY BATTERY WITH ENCLOSURE (50' MAX)</p> <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>2.0</td> <td>17.0</td> <td>6.2</td> </tr> </tbody> </table>	A	B	C	2.0	17.0	6.2
A	B	C											
1.3	12.6	13.0											
A	B	C											
2.0	17.0	6.2											

*OTHER EM BATTERY SIZES AVAILABLE. CONSULT FACTORY

