



**BARISTA**  
**DAMP LOCATION**  
 CAFÉS

PROJECT: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_ TYPE: \_\_\_\_\_



ET60GV  
 MB - Matte Black  
 MWI - Matte White Interior



ET60GV  
 AM - Anodic Malachite  
 MWI - Matte White Interior



ET60GV  
 BZ - Bronze  
 ANI - Anodic Natural Interior



ET60GV  
 MW - Matte White  
 FCI - Fixture Color Interior

| SERIES | LUMENS <sup>1</sup> | CCT       | DRIVER / DIMMING <sup>2</sup>  | ACCESSORIES   | MOUNTING <sup>4</sup>   | INTERIOR <sup>8</sup>  | FINISH <sup>9</sup>  |
|--------|---------------------|-----------|--|---|---|--|--|
| ET60GV | 15L 1500 Lm         | 27K 2700K | EX Electronic Driver, 120V/277V<br>ELV/MLV, 120V<br>1%, 0-10V, 120V/277V | FJO <sup>3</sup> 2" Frosted Tall<br>MFO 2" Frosted Mini | WALL MOUNT<br>CP104 <sup>5</sup> Small Driver Canopy<br>CP6/RMD Remote Mount Driver<br>PA_ <sup>6</sup> Mounting Arm Style<br>SP90_ <sup>6</sup> Straight Arm<br>CEILING MOUNT<br>RDC5 Small Driver Canopy<br>HM_ <sup>7</sup> Hang Straight<br>AT_ <sup>7</sup> Hang Straight All Thread<br>PM_ <sup>7</sup> Rigid Pendant Mount<br>CD_ <sup>7</sup> Cord / Cable Mount<br>CM_ <sup>7</sup> Cord Mount | MWI <sup>8</sup> Matte White<br>CCI Custom Color<br>FCI Fixture Color Interior | MW <sup>9</sup> Matte White<br>MB <sup>9</sup> Matte Black<br>PT <sup>9</sup> Platinum Silver<br>CC Custom Color |
|        |                     | 30K 3000K |  |   |   |  |  |

EXAMPLE: ET60GV15L35KEXFJO/RDC5PM24MWIMW

**NOTES:**  
 1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 Standard Enclosure 4 See Mounting Page for Details on Components and Finishes  
 5 Contact Factory for Knock Out Holes 6 See Mounting Page for Available Arm Options 7 Specify Length in Inches: See Mounting Page for Available Lengths  
 8 Reference Color Sheet Located on Product Webpage for Full List of Available Colors 9 Standard Finishes






**BARISTA**  
**DAMP LOCATION**  
**CAFÉS**

**DECORATIVE**

| LUMENS / WATTAGE DATA |                            |                               |              |     |
|-----------------------|----------------------------|-------------------------------|--------------|-----|
| PART NUMBER           | SOURCE LUMENS <sup>1</sup> | DELIVERED LUMENS <sup>2</sup> | SYSTEM WATTS | LPW |
| ET60GV15L             | 1500                       | 969                           | 11           | 88  |

<sup>1</sup> Nominal Source Lumens at 35K    <sup>2</sup> Nominal Delivered Lumens at 35K

**HOUSING DIMENSIONS**



| A        | B     |
|----------|-------|
| 6.5      | 7.9   |
| 165.1 mm | 200.7 |

**APPLICATION**

The Cafés offer a playful variety of fixture shapes. GV products are designed for damp or dry locations.

**FEATURES**

SpecLume series fixtures offer contemporary style with functional luminaire performance. Passive integral heat sink. LED module and drivers are replaceable and upgradable. Standard diffuser for visual comfort and to eliminate LED source visibility. A variety of mounting options are available.

**FINISH**

Multi-stage polyester powder-coat process applied on our dedicated paint lines. See mounting and color pages for standard finishes. Interior is Matte White unless specified. Custom Color interior finish available.

**ELECTRONICS**

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 80+. Higher CRI, R9 and custom LED configurations are available; consult factory. Variety of electronic 120V/277V and dimming drivers.

**CONSTRUCTION**

Fixtures are spun in our factory from 0.063 high purity aluminum. Die-cast aluminum heat sink for optimal thermal management. Low profile frosted diffuser over LEDs to eliminate direct source visibility.

**CODE COMPLIANCE**

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.

**SERIES SIZES**

ET60GV



**WALL MOUNT**

(SEE MOUNTING PAGES FOR MORE OPTIONS & DIMENSIONS.)

**PA\_**  
MOUNTING ARM STYLE



ET60GV SHOWN WITH CP104PA23

**CEILING MOUNT**

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

**HM / AT / PM**  
HANG STRAIGHT / ALL THREAD / PENDANT



ET60GV SHOWN WITH RDC5PM

**CD**  
CORD / CABLE MOUNT



ET60GV SHOWN WITH RDC5CD

**CM**  
CORD MOUNT



ET60GV SHOWN WITH RDC5CM





**BARISTA**  
**DAMP LOCATION**  
 CAFÉS / PHOTOMETRIC DATA

ET60GV 15L 35K XX MFO XX MWI

| CANDLEPOWER CURVE<br>TEST SP-00977 | INTENSITY<br>CANDELA<br>0° AZIMUTH | ZONAL LUMENS | SINGLE UNIT: PERFORMANCE<br>INITIAL FOOTCANDLES<br>BASED ON IES BEAM ANGLE | MULTIPLE UNITS: PERFORMANCE<br>80/50/20% REFLECTANCES<br>INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT |                     |                       |               |                 |   |                 |                     |           |                     |           |
|------------------------------------|------------------------------------|--------------|--|--|---------------------|-----------------------|---------------|-----------------|---|-----------------|---------------------|-----------|---------------------|-----------|
|                                    | 0.00°                              | 0° - 10°     | 33   | 3%   | Mounting Height AFF | FC at Center on Floor | Beam Diameter | FC at Beam Edge | Ceiling Height                                      | Fixture Spacing | RCR 2               |           | RCR 4               |           |
|                                    | 0.00°                              | 0° - 20°     | 130  | 13%  | 6.5'                | 8 fc                  | 17.6'         | 3 fc            | 9'  | 6'              | FC +                | W/Sq. Ft. | FC +                | W/Sq. Ft. |
|                                    | 5.00°                              | 0° - 30°     | 282  | 29%  | 7.5'                | 6 fc                  | 20.3'         | 2 fc            | 12'   | 8'              | 19                  | 0.23      | 15                  | 0.23      |
|                                    | 10.00°                             | 0° - 40°     | 478  | 49%  | 8.5'                | 5 fc                  | 23.1'         | 2 fc            | 16'   | 10'             | 12                  | 0.15      | 6                   | 0.10      |
|                                    | 15.00°                             | 0° - 60°     | 823  | 85%  | 10.0'               | 3 fc                  | 27.1'         | 1 fc            | Delivered Illuminance Rating: (DIR)                 |                 | 80 FC per W/Sq. Ft. |           | 63 FC per W/Sq. Ft. |           |
|                                    | 20.00°                             | 0° - 80°     | 958  | 99%  | 12.0'               | 2 fc                  | 32.6'         | 1 fc            | 1' Suspension Length                                |                 |                     |           |                     |           |
|                                    | 30.00°                             | 0° - 90°     | 969  | 100%   | 14.0'               | 2 fc                  | 38.0'         | 1 fc            | Square rooms used for multiple units:               |                 |                     |           |                     |           |
|                                    | 40.00°                             | Total        | 969  | 100%   | 16.0'               | 1 fc                  | 43.4'         | 0 fc            | - RCR 2: Length & Width = Ceiling Ht. - 3.5' x 5.00 |                 |                     |           |                     |           |
|                                    | 50.00°                             |              |  |  | 20.0'               | 1 fc                  | 54.3'         | 0 fc            | - RCR 4: Length & Width = Ceiling Ht. - 3.5' x 2.50 |                 |                     |           |                     |           |
|                                    | 60.00°                             |              |  |  |                     |                       |               |                 | + Average Footcandles at 2.5' Above Floor           |                 |                     |           |                     |           |
|                                    | 70.00°                             |              |  |  |                     |                       |               |                 |   |                 |                     |           |                     |           |
|                                    | 80.00°                             |              |  |  |                     |                       |               |                 |   |                 |                     |           |                     |           |
| 90.00°                             |                                    |              |  |  |                     |                       |               |                 |   |                 |                     |           |                     |           |

Delivered Lumens: **969**  
 Luminaire Watts: **11**  
 LER: **88.09**

CP at 0deg (Nadir): **346**  
 CRI: **80**

Beam Angle: **107.2**  
 Spacing Ratio: **1.4**

Lumen Multiplier: **N/A**  
 CCT Multiplier: **27K x 0.97, 30K x 0.99, 40K x 1.03**



# MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.  
NOTE: THIS IS TYPICAL OF SPECLUME SPECIFICATION FOR PENDANT MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.



## WALL MOUNTING

**CP104 - SMALL DRIVER CANOPY (STANDARD)**  
MAY BE USED AS SPLICE BOX FOR DIRECT FEED

Ø 5.5  
4.0

CUSTOM AND OTHER WALL ARMS AVAILABLE - CONTACT FACTORY. ARMS MAY BE FIELD CUT ON WALL SIDE - FIXTURE SIDE THREADED 3/4" NPT REQUIRES SEALANT FOR WET LOCATION.

**PA16 - Front Wall Mount**

15.0  
25.0  
13.0

**CP6/RMD - REMOTE MOUNT DRIVER**  
MOUNTS DIRECTLY TO WALL OR OCTAGON STYLE J-BOX

Ø 4.7  
1.8

**PA15** 15.0, 9.8, 8.3  
**PA17** 17.0, 7.0  
**PA22** 22.0, 7.5, 5.0, 12.5  
**PA23** 23.0, 7.0  
**PA23(xx)** SPECIFY LENGTH, 7.0  
**PA24** 15.0, 18.0, 9.5  
**PA26** 28.5, 12.7  
**SP90(xx)** Designed for Straight Arm Mounting  
SPECIFY LENGTH  
EXAMPLE: SP9024 - STRAIGHT PIPE 24" LONG  
**PA90 (Wxxx) (Dxx)** SPECIFY LENGTH (Wxxx), SPECIFY DROP (6.5 Minimum) (Dxx)  
EXAMPLE: PA90W20D07 - 90° PIPE 20 LONG 7" DEEP THREADED AT FIXTURE END  
**PA32** 32.6, 19.5, 10.5, 30.0, 32.2  
**PA36** 36.0, 7.0  
**PA48** 48.0, 7.0  
**PA901212** 12.0, 12.0

**PA16F - Back Wall Mount**

20.0  
25.0  
13.0

## CEILING MOUNTING

|  |  |   |  |   |   |
|--|--|---|--|---|---|
| <p><b>RDC5 - SMALL DRIVER CANOPY (STANDARD)</b><br/>MOUNTS TO 4" OCTO J-BOX</p> <p>Ø 5.3<br/>2.5</p> | <p><b>HM*</b><br/>HANG STRAIGHT<br/>45° SWIVEL 1/2" STEM - 3/8" NPT</p> <p>ORDER: <b>HM</b> (Length)<br/>SPECIFY LENGTH:<br/><b>HM3</b> - 3"    <b>HM24</b> - 24"<br/><b>HM6</b> - 6"    <b>HM36</b> - 36"<br/><b>HM12</b> - 12"    <b>HM48</b> - 48"<br/><b>HM18</b> - 18"    <b>HM72</b> - 72"<br/><b>HMLC(XX)</b><br/>Custom Length<br/>(Specify in Inches)</p> | <p><b>AT**</b><br/>HANG STRAIGHT ALL THREAD<br/>45° SWIVEL 1/2" STEM - 1/4" IP</p> <p>ORDER: <b>AT</b> (Length)<br/>SPECIFY LENGTH:<br/><b>AT12</b> - 12"    <b>AT48</b> - 48"<br/><b>AT24</b> - 24"    <b>AT60</b> - 60"<br/><b>AT36</b> - 36"    <b>AT72</b> - 72"<br/><small>FIELD-CUT THREADED PIPE TO LENGTH NEEDED! CUT 1/8" COUSE - 1/4" SHORTER THAN THREADED PIPE. SLIP "PIPE COVER" OVER THREADED PIPE.</small></p> | <p><b>PM*</b><br/>RIGID PENDANT MOUNT<br/>RIGID 1/2" STEM - 3/8" NPT</p> <p>0°</p> <p>ORDER: <b>PM</b> (Length)<br/>SPECIFY LENGTH:<br/><b>PM3</b> - 3"    <b>PM24</b> - 24"<br/><b>PM6</b> - 6"    <b>PM36</b> - 36"<br/><b>PM12</b> - 12"    <b>PM48</b> - 48"<br/><b>PM18</b> - 18"    <b>PM72</b> - 72"<br/><b>PMLLC(XX)</b><br/>Custom Length<br/>(Specify in Inches)</p> | <p><b>CD</b><br/>CORD / CABLE MOUNT<br/>SJ CORD WITH 1/16 SS CABLE</p> <p>ADJUST AND LOCKS</p> <p>ORDER: <b>CD</b> (Length)<br/>SPECIFY LENGTH:<br/><b>CD36</b> - 36"<br/><b>CD72</b> - 72"<br/><b>CD144</b> - 144"<br/><b>CDLC(XX)</b><br/>Custom Length<br/>(Specify in Inches)</p> | <p><b>CM</b><br/>CORD MOUNT<br/>SJ CORD WITH STRAIN RELIEF</p> <p>ORDER: <b>CM</b> (Length)<br/>SPECIFY LENGTH:<br/><b>CM36</b> - 36"<br/><b>CM72</b> - 72"<br/><b>CM144</b> - 144"<br/><b>CMLC(XX)</b><br/>Custom Length<br/>(Specify in Inches)</p> |
|--|--|---|--|---|---|

\*MAXIMUM ONE PIECE STEM LENGTH IS 72". \*\*MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS.  
\*\*ORDER IN 12" INCREMENTS, ODD SIZES MAY BE FIELD CUT

