




**EXPRESS PENDANT**  
**INCANDESCENT**  
 DOMO SHADES

PROJECT: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_ TYPE: \_\_\_\_\_



EP1010INC  
 PT - Platinum Silver  
 MWI - Matte White Interior

EP1414INC  
 BL - Blue Streak  
 PT1 - Platinum Silver Interior



SERIES	A	B
EP1010INC	10.0	10.0
EP1414INC	14.0	14.0

**EP-INC**

**APPLICATION**

Express is a popular European styled pendant fixture. INC Series is designed for indoor damp locations or outdoor wet locations.

**FEATURES**

Speculume series fixtures offer simple contemporary style with functional luminaire performance. All fixtures are designed and manufactured in our factory. The wide range of combinations for illumination, mounting, enclosures, guards and finishes allows for creative fixture specification and design. Fixtures may be wall or pendant mounted with standard or custom wall arm (goosenecks) and pendants.

**FINISH**

Multi-stage polyester powder-coat process applied on our dedicated paint lines. A wide variety of standard and custom finishes are available. All exposed materials are chromate pretreated to resist corrosion. Interior is Matte White unless specified. Custom Color interior finishes available.

**ELECTRONICS**

E26 Edison medium base 120V socket for incandescent or LED lamps.

**CONSTRUCTION**

Fixture shades are spun in our factory from 0.063 high purity aluminum. Gaskets are machine cut neoprene.

**CODE COMPLIANCE**

ETL listed for damp locations. Optional Wet location. Manufactured and tested to UL standard No. 1598.

SERIES	ACCESSORIES <sup>1</sup>	MOUNTING <sup>3</sup>	INTERIOR <sup>6</sup>	FINISH <sup>6</sup>	WET KIT
EP1010INC EP1414INC	<b>ENCLOSURES</b> <b>FJ1<sup>2</sup></b> 3"x 6.5" Frosted Glass <b>GJ1</b> 3"x 6.5" Clear Glass <b>CG1</b> Cast Wire Guard	<b>WALL MOUNT</b> <b>CP6<sup>3</sup></b> Wall Pipe Interface <b>CP3</b> CP6 Decorative Cover <b>PA_<sup>4</sup></b> Mounting Arm Style <b>SP90_<sup>4</sup></b> Straight Arm	<b>MW1<sup>7</sup></b> Matte White <b>CCI</b> Custom Color <b>FCI</b> Fixture Color Interior	<b>MW<sup>7</sup></b> Matte White <b>MB<sup>7</sup></b> Matte Black <b>PT<sup>7</sup></b> Platinum Silver <b>CC</b> Custom Color	<b>WLKA</b> Wet Location Kit
		<b>CEILING MOUNT</b> <b>HM_<sup>5</sup></b> Hang Straight Pendant <b>AT_<sup>5</sup></b> Hang Straight All Thread <b>PM_<sup>5</sup></b> Pendant/Straight Mount <b>CD_<sup>5</sup></b> Cord and Cable Mount <b>CM_<sup>5</sup></b> Cord Mount			

**EXAMPLE:** EP1414INC/FJ1/HM36MW1PT

NOTES:  
 1 See Enclosures & Guards Page for Wire Guards and Additional Options 2 Standard Enclosure 3 See Mounting Pages Options and Details on Components and Finishes  
 4 See Mounting Page for Available Arm Options 5 Specify Length in Inches : See Mounting Page for Available Lengths 6 Reference Color Sheet Located on Product  
 Webpage for Full List of Available Colors/Consult Factory for Special Finishes 7 Standard Finish



# MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.  
NOTE: THIS IS TYPICAL OF RLM SPECIFICATION FOR MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.



## WALL MOUNTING

**CP6 - MOUNTS DIRECTLY TO WALL OR OCTAGON STYLE J-BOX**

**CUSTOM AND OTHER WALL ARMS AVAILABLE - CONTACT FACTORY. ARMS MAY BE FIELD CUT ON WALL SIDE - FIXTURE SIDE THREADED 3/4" NPT REQUIRES SEALANT FOR WET LOCATION.**

<p><b>PA15</b> 15.0, 9.8, 8.3</p> <p><b>PA17</b> 17.0, 7.0</p> <p><b>PA22</b> 22.0, 7.5, 5.0, 12.5</p> <p><b>PA23</b> 23.0, 7.0</p> <p><b>PA23(xx)</b> SPECIFY LENGTH, 7.0 EXAMPLE: PA2330 - 30" PA23</p>	<p><b>PA24</b> 15.0, 18.0, 24.0, 9.5</p> <p><b>PA26</b> 28.5, 12.7</p> <p><b>SP9012</b> FIELD CUTTABLE, 12</p> <p><b>SP9024</b> FIELD CUTTABLE, 24</p> <p><b>PA90 (Wxx)(Dxx)</b> SPECIFY LENGTH (Wxx), SPECIFY DROP (6.5 Minimum) (Dxx) EXAMPLE: PA90W20D07 - 90° PIPE 20 LONG 7" DEEP THREADED AT FIXTURE END</p>	<p><b>PA32</b> 32.6, 19.5, 10.5, 30.0, 32.2</p> <p><b>PA36</b> 36.0, 7.0</p> <p><b>PA48</b> 48.0, 7.0</p>	<p><b>PA16 - Front Wall Mount</b> 15.0, 25.0, 13.0</p> <p><b>PA16F - Back Wall Mount</b> 20.0, 25.0, 13.0</p> <p><b>PA901212</b> 12.0, 12.0</p>
---	--	---	---

## CEILING MOUNTING

<p><b>HM*</b> HANG STRAIGHT 45° SWIVEL 5/8" OD STEM - 3/8" IP</p> <p>ORDER: HM (Length) SPECIFY LENGTH: <b>HM3</b> - 3"    <b>HM24</b> - 24" <b>HM6</b> - 6"    <b>HM36</b> - 36" <b>HM12</b> - 12"    <b>HM48</b> - 48" <b>HM18</b> - 18"    <b>HM72</b> - 72" <b>HMLC(XX)</b> Custom Length (Specify in Inches)</p>	<p><b>PM*</b> RIGID PENDANT MOUNT RIGID 5/8" OD STEM - 3/8" IP</p> <p>ORDER: PM (Length) SPECIFY LENGTH: <b>PM3</b> - 3"    <b>PM24</b> - 24" <b>PM6</b> - 6"    <b>PM36</b> - 36" <b>PM12</b> - 12"    <b>PM48</b> - 48" <b>PM18</b> - 18"    <b>PM72</b> - 72" <b>PMLC(XX)</b> Custom Length (Specify in Inches)</p>	<p><b>AT**</b> HANG STRAIGHT ALL THREAD 45° SWIVEL 5/8" OD STEM - 1/4" IP</p> <p>ORDER: AT (Length) SPECIFY LENGTH: <b>AT12</b> - 12"    <b>AT48</b> - 48" <b>AT24</b> - 24"    <b>AT60</b> - 60" <b>AT36</b> - 36"    <b>AT72</b> - 72" FIELD CUT, THREADED PIPE TO LENGTH REQUIRED, CUT PIPE COVER 1/4" SHORTER THAN THREADED PIPE, SLIP PIPE COVER OVER THREADED PIPE</p>	<p><b>CD</b> CORD / CABLE MOUNT SJ CORD WITH 1/16 SS CABLE</p> <p>ORDER: CD (Length) SPECIFY LENGTH: <b>CD36</b> - 36" <b>CD72</b> - 72" <b>CD144</b> - 144" <b>CDLC(XX)</b> Custom Length (Specify in Inches)</p>	<p><b>CM</b> CORD MOUNT SJ CORD WITH STRAIN RELIEF</p> <p>ORDER: CM (Length) SPECIFY LENGTH: <b>CM36</b> - 36" <b>CM72</b> - 72" <b>CM144</b> - 144" <b>CMLC(XX)</b> Custom Length (Specify in Inches)</p>
---	--	--	--	--

\*MAXIMUM ONE PIECE STEM LENGTH IS 72". \*\*MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS.  
\*\*ORDER IN 12" INCREMENTS. ODD SIZES MAY BE FIELD CUT

