

Indoor Distribution Test Report

Spectrum Lighting Inc.

994 Jefferson Street
Fall River, MA 02721
+1.508.678.2303

Spectrum Lighting Photometric Lab

Luminaire

IF03SMx IC DWDD1015 DLNFGPMW

Nom 3" Infinium Square Downlight, 15L dim to warm 27HK emitter

Test Number

SP-00944_2_M-15L

Test Date

11/6/2019

The results contained in this report pertain only to this IES file.

Summary of Results

Power

Input Watts	15.2 W
-------------	--------

Lumen Output

Output Lumens	726
Efficacy	47.78 lm/W

Luminous Dimensions

0° - 180° Size	0.16
90° - 270° Size	0.16
Height	0

Spacing Criterion

Two luminaires, plane 0°	0.45
Two luminaires, plane 90°	0.45
Four luminaires	0.51


Full Beam Angle

0° - 180°	28°
90° - 270°	28°

IES File Header Contents

Keyword	Value
TEST	SP-00944_2_M-15L
TESTLAB	Spectrum Lighting Photometric Lab, VLS-245-981
MANUFAC	Spectrum Lighting
TESTDATE	11/6/2019
ISSUEDATE	11/15/2019
LUMCAT	IF03SMx IC DWDD1015 DLNFGPMW
LUMINAIRE	Nom 3" Infinium Square Downlight, 15L dim to warm 27HK emitter
OTHER	Beam angle: 27.8 degrees
OTHER	Shallow IC
LAMPCAT	N/A
LAMP	N/A
OTHER	CCT Output Multipliers: N/A dim to warm
OTHER	Total luminaire wattage is approximate
OTHER	This report prepared by Spectrum Lighting
_CRI	95
_CCTMULT	N/A, dim to warm emitter
_LAMPMULT	7L x 0.38, 10L x 0.49, 15L x 0.8

Candela Polar Plot



Zonal Lumen Summary

Zone	Lumens	% Fixture	Zone	Lumens	% Fixture
0.00° - 10.00°	172.48	23.75%	90.00° - 100.00°	0.08	0.01%
10.00° - 20.00°	270.92	37.30%	100.00° - 110.00°	0.00	0.00%
20.00° - 30.00°	172.63	23.77%	100.00° - 120.00°	0.00	0.00%
30.00° - 40.00°	53.78	7.41%	120.00° - 130.00°	0.00	0.00%
40.00° - 50.00°	19.21	2.64%	130.00° - 140.00°	0.00	0.00%
50.00° - 60.00°	14.39	1.98%	140.00° - 150.00°	0.00	0.00%
60.00° - 70.00°	12.40	1.71%	150.00° - 160.00°	0.00	0.00%
70.00° - 80.00°	8.20	1.13%	160.00° - 170.00°	0.00	0.00%
80.00° - 90.00°	2.21	0.30%	170.00° - 180.00°	0.00	0.00%
0.00° - 90.00°	726.20	99.99%	0.00° - 180.00°	726.28	100.00%

Candela Distribution

	0.00°	22.50°	45.00°	67.50°	90.00°	112.50°	135.00°	157.50°	180.00°	202.50°	225.00°	247.50°	270.00°	292.50°	315.00°	337.50°	360.00°
0.00°	2,191.30	2,191.30	2,191.30	2,191.30	2,191.30	2,191.30	2,191.30	2,191.30	2,191.30	2,191.30	2,191.30	2,191.30	2,191.30	2,191.30	2,191.30	2,191.30	2,191.30
2.50°	2,105.76	2,108.75	2,108.61	2,114.63	2,108.94	2,111.68	2,107.62	2,117.59	2,103.65	2,112.07	2,098.60	2,113.69	2,095.29	2,093.60	2,103.51	2,111.29	2,105.76
5.00°	1,993.08	1,966.39	1,984.03	1,955.28	1,996.04	1,999.85	1,961.93	1,976.99	1,987.15	1,977.98	1,966.81	1,965.97	1,972.34	1,967.23	1,962.82	1,953.86	1,993.08
7.50°	1,737.94	1,727.83	1,720.33	1,723.51	1,738.90	1,743.19	1,727.40	1,746.79	1,738.89	1,732.26	1,711.10	1,734.45	1,722.62	1,716.00	1,717.91	1,726.51	1,737.94
10.00°	1,483.04	1,457.97	1,456.92	1,442.00	1,481.32	1,485.22	1,458.23	1,495.98	1,489.62	1,479.28	1,438.56	1,478.80	1,470.25	1,462.38	1,468.78	1,458.16	1,483.04
12.50°	1,230.65	1,207.62	1,194.29	1,189.47	1,221.56	1,220.90	1,209.08	1,226.19	1,232.82	1,215.28	1,189.18	1,204.05	1,218.12	1,213.95	1,214.08	1,212.88	1,230.65
15.00°	986.51	961.94	960.40	953.35	978.39	975.76	965.83	998.01	987.34	984.50	941.45	977.75	970.92	971.35	994.31	978.66	986.51
17.50°	794.16	781.24	788.69	777.34	792.64	797.14	800.99	800.79	799.40	795.03	791.12	782.31	782.19	794.19	812.82	795.29	794.16
20.00°	608.38	611.13	643.61	628.19	617.34	632.05	652.79	641.91	620.26	635.45	643.87	623.93	597.89	621.94	669.62	630.86	608.38
22.50°	451.91	472.54	544.08	500.47	470.36	503.66	551.70	505.91	472.86	506.38	548.84	484.35	443.16	482.24	560.40	492.25	451.91
25.00°	308.16	337.25	447.05	380.13	334.35	381.66	457.62	387.27	336.30	387.05	453.84	361.17	298.48	348.51	453.51	360.87	308.16
27.50°	205.59	238.87	353.44	275.01	221.41	273.10	365.37	277.11	229.11	275.77	359.17	244.73	198.68	241.30	348.30	257.33	205.59
30.00°	121.39	142.69	263.03	173.95	132.62	180.46	273.28	193.17	140.34	189.12	266.40	163.91	113.66	147.54	254.15	159.62	121.39
32.50°	82.48	100.76	176.27	115.32	84.06	114.36	197.57	119.21	91.59	118.87	185.61	94.24	77.48	97.26	166.55	108.60	82.48
35.00°	52.82	60.45	112.44	64.65	50.74	67.07	123.30	79.44	55.82	76.52	112.99	63.70	48.56	56.93	108.20	63.96	52.82
37.50°	41.57	47.42	69.78	46.59	38.42	45.73	84.23	49.48	42.35	49.46	75.31	42.08	38.15	41.99	63.56	48.08	41.57
40.00°	32.57	35.20	44.96	32.37	29.72	31.85	47.18	36.91	32.29	36.36	44.17	33.54	29.67	30.46	42.60	34.28	32.57
42.50°	27.12	29.55	33.45	27.03	25.05	26.28	35.45	28.08	26.93	29.28	34.26	27.12	25.06	25.69	30.25	29.09	27.12
45.00°	23.05	24.28	26.39	22.25	20.84	22.26	24.79	24.59	23.15	25.15	26.35	24.30	21.34	21.76	24.38	24.17	23.05
47.50°	20.75	21.05	22.09	19.16	17.05	19.65	21.48	21.85	21.19	21.99	23.37	21.82	19.03	19.14	20.34	21.88	20.75
50.00°	18.47	18.08	19.35	16.16	15.16	17.41	18.63	19.50	19.78	20.45	20.99	19.60	17.09	17.30	18.23	19.67	18.47
52.50°	16.23	16.15	17.39	14.63	14.68	15.46	17.89	17.18	18.88	19.32	19.75	17.41	15.60	16.47	16.52	18.39	16.23
55.00°	14.96	14.89	16.16	13.26	13.89	14.58	17.09	16.57	17.44	18.12	18.53	16.35	14.42	15.47	15.84	17.02	14.96
57.50°	14.52	15.51	15.21	13.34	12.91	14.36	16.09	16.01	15.59	16.92	17.36	15.31	13.56	14.29	15.30	15.06	14.52
60.00°	14.04	15.75	14.67	13.36	12.37	13.31	15.02	15.29	14.30	15.76	15.94	14.48	13.07	13.17	13.88	13.38	14.04
62.50°	13.53	15.15	14.25	12.97	12.03	11.85	13.74	14.51	13.36	14.61	14.23	13.58	12.92	12.10	12.39	13.04	13.53
65.00°	13.06	14.32	13.46	12.46	11.35	11.49	12.59	13.05	12.53	14.25	12.91	12.09	11.93	11.25	11.45	12.71	13.06
67.50°	12.63	13.09	12.59	11.50	10.53	11.56	11.68	11.77	11.76	13.79	11.98	10.79	10.36	10.56	10.52	12.39	12.63
70.00°	11.36	12.07	11.21	10.47	9.43	10.06	10.34	11.34	10.61	11.65	10.55	10.11	8.81	9.74	9.73	11.78	11.36
72.50°	9.82	11.25	9.84	9.33	8.19	8.31	8.59	10.36	9.33	10.05	8.88	9.04	7.27	8.83	8.94	10.73	9.82
75.00°	8.13	9.14	8.74	8.19	6.30	6.71	8.04	8.71	7.78	9.44	8.43	7.55	5.78	6.90	8.12	8.82	8.13
77.50°	6.29	6.84	7.59	6.86	5.19	5.71	6.82	6.89	6.28	7.00	6.94	5.99	4.70	5.34	6.04	6.47	6.29
80.00°	4.33	4.80	6.05	4.69	4.51	4.65	4.27	5.20	4.68	5.05	4.73	4.64	3.68	4.04	3.84	3.77	4.33
82.50°	2.67	2.98	3.30	3.25	2.77	2.29	2.50	3.60	2.88	3.85	3.03	3.20	2.22	2.53	2.19	2.55	2.67
85.00°	1.44	1.05	1.38	1.54	1.38	1.70	1.35	1.91	1.44	2.28	1.63	1.63	1.51	1.29	1.08	1.35	1.44
87.50°	1.06	1.15	1.14	1.31	1.40	0.94	1.01	1.09	1.23	1.46	1.37	1.63	1.17	1.01	0.89	1.12	1.06
90.00°	1.25	1.00	1.16	1.37	1.22	1.08	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.05	1.04	1.25
92.50°	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
95.00°	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
97.50°	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100.00°	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
102.50°	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
105.00°	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
107.50°	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
110.00°	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
112.50°	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Coefficients of Utilization – Zonal Cavity Method

Values are lumens delivered to the workplane.

RCR	pfc	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	0%
	pcc	80%	80%	80%	80%	70%	70%	70%	70%	50%	50%	50%	30%	30%	30%	10%	10%	0%
	pw	70%	50%	30%	10%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	30%
	0	865	865	865	865	844	844	844	844	807	807	807	773	773	773	741	741	726
	1	827	808	791	776	809	792	777	763	763	751	740	736	727	718	711	704	697
	2	791	759	732	709	776	746	722	701	723	703	686	702	686	671	682	669	658
	3	758	716	684	658	744	706	676	653	688	663	642	670	650	632	654	637	625
	4	727	679	643	616	715	671	638	613	656	628	606	642	618	599	629	608	597
	5	699	646	609	582	688	639	605	579	627	597	574	615	589	569	604	582	572
	6	672	616	579	552	662	611	576	550	601	570	547	591	564	543	582	558	549
	7	647	590	552	526	638	585	550	525	576	545	522	568	540	520	561	536	527
	8	624	565	529	503	616	562	527	502	554	523	500	547	519	498	541	515	507
	9	603	543	507	483	595	540	505	482	534	502	480	528	499	479	522	496	489
	10	582	523	488	464	576	520	486	463	515	484	462	510	481	461	505	479	472

Cone of Light

Mtg Height	Light Level	Beam Diameter
5.5 ft	72.4 fc	2.7 ft
6.5 ft	51.9 fc	3.2 ft
7.5 ft	39.0 fc	3.7 ft
8.0 ft	34.2 fc	4.0 ft
10.0 ft	21.9 fc	4.9 ft
12.0 ft	15.2 fc	5.9 ft
14.0 ft	11.2 fc	6.9 ft
16.0 ft	8.6 fc	7.9 ft
20.0 ft	5.5 fc	9.9 ft
24.0 ft	3.8 fc	11.9 ft
28.0 ft	2.8 fc	13.8 ft

Average Luminaire Luminance [cd/m²]

	0.00°	45.00°	90.00°
0.00°	921,365	921,365	921,365
45.00°	13,709	15,694	12,391
55.00°	10,969	11,848	10,182
65.00°	12,998	13,390	11,288
75.00°	13,209	14,203	10,227
85.00°	6,953	6,636	6,639

UGR CIE 190:2010

Ceiling reflectance		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall reflectance		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Plane reflectance		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
2H	2H	14.4	15.4	14.8	15.7	16.0	14.1	15.1	14.5	15.4	15.7
	3H	17.0	17.9	17.4	18.2	18.6	16.3	17.1	16.6	17.5	17.9
	4H	18.0	18.8	18.4	19.2	19.5	17.0	17.8	17.4	18.1	18.5
	6H	18.5	19.3	18.9	19.6	20.0	17.5	18.2	17.9	18.6	19.0
	8H	18.6	19.3	19.0	19.7	20.1	17.6	18.3	18.1	18.7	19.1
	12H	18.6	19.3	19.1	19.7	20.1	17.7	18.4	18.1	18.8	19.2
4H	2H	15.1	15.9	15.5	16.2	16.6	14.9	15.7	15.3	16.1	16.5
	3H	17.9	18.6	18.3	19.0	19.4	17.2	17.9	17.7	18.3	18.7
	4H	19.0	19.6	19.5	20.1	20.5	18.1	18.7	18.5	19.1	19.6
	6H	19.6	20.2	20.1	20.6	21.1	18.7	19.2	19.2	19.7	20.2
	8H	19.8	20.2	20.2	20.7	21.2	18.9	19.4	19.4	19.8	20.3
	12H	19.8	20.2	20.3	20.7	21.2	19.0	19.4	19.5	19.9	20.4
8H	4H	19.3	19.8	19.8	20.3	20.7	18.5	19.0	19.0	19.4	19.9
	6H	20.1	20.4	20.6	20.9	21.4	19.3	19.7	19.8	20.2	20.7
	8H	20.2	20.6	20.8	21.1	21.6	19.5	19.9	20.1	20.4	20.9
	12H	20.3	20.6	20.9	21.1	21.7	19.7	20.0	20.2	20.5	21.0
12H	4H	19.3	19.7	19.8	20.2	20.7	18.5	18.9	19.0	19.4	19.9
	6H	20.1	20.4	20.6	20.9	21.4	19.4	19.7	19.9	20.2	20.7
	8H	20.3	20.6	20.8	21.1	21.7	19.6	19.9	20.1	20.4	21.0

Corrected UGR values based on total output lumens

SHR = 1.0