




DEDAL PENDANT
INCANDESCENT
 DOMO SHADES



| A | B |
|------------------|------------------|
| 15.9 403.9 mm | 17.9 545.7 mm |

PROJECT: _____
 QUANTITY: _____ TYPE: _____

APPLICATION

Dedal Pendant is perfect for decorative and retail lighting.

FEATURES

Spectrum Lighting's RLM Series are interpretations of classic lighting fixtures with modern INC light sources and materials. The wide range of combinations for illumination, mounting, enclosures, guards and finishes allows for creative fixture specification and design. A variety of lamp enclosures are available as well as guards and light shields. Fixtures may be wall or pendant mounted with standard or custom wall arm (goosenecks) and pendants. MR16 and LED lamping available.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. A wide variety of standard and custom finishes are available. All exposed materials are chromate pretreated to resist corrosion. Interior is Matte White unless specified. Custom Color interior finishes available.

ELECTRONICS

E26 Edison medium base 120V socket for incandescent or LED lamps.

CONSTRUCTION

Fixture shades are spun in our factory from 0.063 high purity aluminum. Wall enclosures and fittings are die-cast aluminum with stainless steel hardware. Wall arms are formed 3/4 NPT aluminum pipe. Gaskets are machine cut neoprene.

CODE COMPLIANCE

ETL listed for damp locations. Manufactured and tested to UL standard No. 1598.

| SERIES | MOUNTING ¹ | INTERIOR ⁴ | FINISH ⁵ |
|-----------|---|---|---|
| TD1617INC | WALL MOUNT | MW⁵ Matte White CCI Custom Color FCI Fixture Color Interior | MW⁵ Matte White MB⁵ Matte Black PT⁵ Platinum Silver CC⁵ Custom Color |
| | CP6¹ Wall Pipe Interface CP3 CP6 Decorative Cover PA² Mounting Arm Style SP90² Straight Arm | | |
| | CEILING MOUNT | | |
| | HM³ Hang Straight Pendant AT³ Hang Straight All Thread PM³ Pendant/Straight Mount CD³ Cord and Cable Mount CM³ Cord Mount | | |

EXAMPLE: TD1617INC/HM36/FCIMW

NOTES:
 1 See Mounting Pages Options and Details on Components and Finishes 2 See Mounting Page for Available Arm Options 3 Specify Length in Inches: See Mounting Page for Available Lengths 4 Reference Color Sheet Located on Product Webpage for Full List of Available Colors/Consult Factory for Special Finishes 5 Standard Finishes



MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.
NOTE: THIS IS TYPICAL OF RLM SPECIFICATION FOR MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.



WALL MOUNTING

CP6 - MOUNTS DIRECTLY TO WALL OR OCTAGON STYLE J-BOX

CUSTOM AND OTHER WALL ARMS AVAILABLE - CONTACT FACTORY. ARMS MAY BE FIELD CUT ON WALL SIDE - FIXTURE SIDE THREADED 3/4" NPT REQUIRES SEALANT FOR WET LOCATION.

| | | | |
|---|--|---|---|
| <p>PA15 15.0, 9.8, 8.3</p> <p>PA17 17.0, 7.0</p> <p>PA22 22.0, 7.5, 5.0, 12.5</p> <p>PA23 23.0, 7.0</p> <p>PA23(xx) SPECIFY LENGTH, 7.0 EXAMPLE: PA2330 - 30" PA23</p> | <p>PA24 15.0, 18.0, 24.0, 9.5</p> <p>PA26 28.5, 12.7</p> <p>SP9012 FIELD CUTTABLE, 12</p> <p>SP9024 FIELD CUTTABLE, 24</p> <p>PA90 (Wxx)(Dxx) SPECIFY LENGTH (Wxx), SPECIFY DROP (6.5 Minimum) (Dxx) EXAMPLE: PA90W20D07 - 90° PIPE 20 LONG 7" DEEP THREADED AT FIXTURE END</p> | <p>PA32 32.6, 19.5, 10.5, 30.0, 32.2</p> <p>PA36 36.0, 7.0</p> <p>PA48 48.0, 7.0</p> | <p>PA16 - Front Wall Mount 15.0, 25.0, 13.0</p> <p>PA16F - Back Wall Mount 20.0, 25.0, 13.0</p> <p>PA901212 12.0, 12.0</p> |
|---|--|---|---|

CEILING MOUNTING

| | | | | |
|---|--|--|--|--|
| <p>HM* HANG STRAIGHT 45° SWIVEL 5/8" OD STEM - 3/8" IP</p> <p>ORDER: HM (Length) SPECIFY LENGTH: HM3 - 3" HM24 - 24" HM6 - 6" HM36 - 36" HM12 - 12" HM48 - 48" HM18 - 18" HM72 - 72" HMLC(XX) Custom Length (Specify in Inches)</p> | <p>PM* RIGID PENDANT MOUNT RIGID 5/8" OD STEM - 3/8" IP</p> <p>ORDER: PM (Length) SPECIFY LENGTH: PM3 - 3" PM24 - 24" PM6 - 6" PM36 - 36" PM12 - 12" PM48 - 48" PM18 - 18" PM72 - 72" PMLC(XX) Custom Length (Specify in Inches)</p> | <p>AT** HANG STRAIGHT ALL THREAD 45° SWIVEL 5/8" OD STEM - 1/4" IP</p> <p>ORDER: AT (Length) SPECIFY LENGTH: AT12 - 12" AT48 - 48" AT24 - 24" AT60 - 60" AT36 - 36" AT72 - 72" <small>FIELD CUT, THREADED PIPE TO LENGTH REQUIRED. CUT PIPE COVER 1/4" SHORTER THAN THREADED PIPE. SLIP PIPE COVER OVER THREADED PIPE.</small></p> | <p>CD CORD / CABLE MOUNT SJ CORD WITH 1/16 SS CABLE</p> <p>ORDER: CD (Length) SPECIFY LENGTH: CD36 - 36" CD72 - 72" CD144 - 144" CDLC(XX) Custom Length (Specify in Inches)</p> | <p>CM CORD MOUNT SJ CORD WITH STRAIN RELIEF</p> <p>ORDER: CM (Length) SPECIFY LENGTH: CM36 - 36" CM72 - 72" CM144 - 144" CMLC(XX) Custom Length (Specify in Inches)</p> |
|---|--|--|--|--|

*MAXIMUM ONE PIECE STEM LENGTH IS 72". **MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS.
**ORDER IN 12" INCREMENTS. ODD SIZES MAY BE FIELD CUT