



**19" SHORT WAREHOUSE SHADE**  
**DAMP / WET LOCATION**  
 CLASSIC SHAPES

PROJECT: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_ TYPE: \_\_\_\_\_



SW1910GV  
 AN - Anodic Natural



SW1910GV  
 BZ - Bronze



SW1910GV  
 PT - Platinum Silver



SW1910GV  
 MB - Matte Black

SERIES	LUMENS <sup>1</sup>	CCT	DRIVER / DIMMING <sup>2</sup>	ACCESSORIES <sup>6</sup>	MOUNTING <sup>8</sup>	INTERIOR <sup>12</sup>	FINISH <sup>12</sup>	WET KIT		
SW1910GV	15L	1500 Lm	80 CRI	<b>EX<sup>3</sup></b> Electronic Driver, 120V/277V 1%, 0-10V, 120V/277V <b>DO10X</b> ELV/MLV, 120V <b>DS2W1<sup>4</sup></b> Lutron® 2-Wire Forward Phase (MLV), 120V <b>DLTE1<sup>5</sup></b> 1%, Lutron® EcoSystem®, Fades to Black, 120V/277V <b>DL3EX<sup>6</sup></b>	<b>ENCLOSURES</b> <b>TF2<sup>7</sup></b> 4" Frosted Dome <b>TG2</b> 4" Dome Wire Guard <b>MF2</b> 4" Frosted Mini <b>MG2</b> 4" Short Wire Guard <b>FJ2</b> 4" Frosted Tall <b>FG2</b> 4" Tall Wire Guard	<b>WALL MOUNT</b> <b>CP104</b> Small Driver Canopy <b>CP104KO</b> Small Driver Canopy w/ Knockouts <b>CP106</b> Large Driver Canopy <b>CP6/RMD</b> Remote Mount Driver <b>SP90<sup>9</sup></b> Straight Arm <b>PA<sup>9</sup></b> Mounting Arm Style <b>CEILING MOUNT</b> <b>RDC5</b> Small Driver Canopy <b>CP13</b> Large Driver Canopy <b>HM<sup>10</sup></b> Hang Straight <b>AT<sup>10</sup></b> Hang Straight All Thread <b>PM<sup>10</sup></b> Rigid Pendant Mount <b>CD<sup>10</sup></b> Cord / Cable Mount <b>CM<sup>10</sup></b> Cord Mount <b>EMCR<sup>11</sup></b> 10W Large Driver Canopy EM <b>EMRM</b> 7W Remote EM <b>EMEN</b> 7W Remote with Enclosure	<b>MW1<sup>13</sup></b> Matte White <b>CCI</b> Custom Color <b>FCI</b> Fixture Color Interior	<b>MW<sup>13</sup></b> Matte White <b>MB<sup>13</sup></b> Matte Black <b>PT<sup>13</sup></b> Platinum Silver <b>CC</b> Custom Color	<b>WLKA</b> Wet Location Kit	
	27L	2700 Lm	27K							2700K
	37L	3700 Lm	30K							3000K
	55L	5500 Lm	35K							3500K
			90 CRI							
			27HK	2700K						
			30HK	3000K						
			35HK	3500K						
			40HK	4000K						

EXAMPLE: SW1910GV37L35KEXTF2/RDC5HM36MWIMB

**NOTES:**  
 1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 37L Max with CP104 4 37L Max with CP104/RDC5, 55L Max with CP106/CP13  
 5 Available with CP106/CP13 Only 6 Enclosure, Wire Guard Required - Choose One Option 7 Standard Enclosure 8 See Mounting Page for Details on Components and Finishes  
 9 See Mounting Page for Available Arm Options 10 Specify Length in Inches; See Mounting Page for Available Lengths 11 EMCR Replaces RDC5 or CP13  
 12 Reference Color Sheet Located on Product Webpage for Full List of Available Colors 13 Standard Finishes





# 19" SHORT WAREHOUSE SHADE


## DAMP / WET LOCATION

### CLASSIC SHAPES

LUMENS / WATTAGE DATA				
PART NUMBER	SOURCE LUMENS <sup>1</sup>	DELIVERED LUMENS <sup>2</sup>	SYSTEM WATTS	LPW
SW1910GV15L	1500	1202	10	120
SW1910GV27L	2700	2100	18	117
SW1910GV37L	3700	3080	26	118
SW1910GV55L	5500	4536	39	116

<sup>1</sup> Nominal Source Lumens at 35K    <sup>2</sup> Nominal Delivered Lumens at 35K

### HOUSING DIMENSIONS



A	B
18.5	10.0
470.0 mm	254.0 mm

### APPLICATION

The Short Warehouse Shade is a shallow version of our most popular Warehouse Shades.

### FEATURES

Spectrum Lighting's RLM Classics are inspired by vintage lighting fixtures redesigned with modern LED light sources and materials. The wide range of options for illumination, mounting, enclosures, guards and finishes allows for creative fixture specification and design. LED module and driver are serviceable for future replacement.

### FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. Variety of standard and custom finishes are available. Interior is Matte White unless specified. Custom Color interior finishes available.

### ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 80+. Higher CRI, R9 and custom LED configurations are available; consult factory. Choice of electronic 120V/277V and dimming drivers.


### CONSTRUCTION

Fixture shades are spun in our factory from 0.063 high purity aluminum. Wall mount canopies are die-cast aluminum with stainless steel hardware. Wall arms are formed 3/4 NPT aluminum pipe and may be field cut.

### CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Wet Location Option. Manufactured and tested to UL standards No. 1598/8750.

### ENCLOSURES



### WALL MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & DIMENSIONS.)

**PA\_**  
MOUNTING ARM STYLE



SW1910GV SHOWN WITH CP104PA23

### CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

**HM / AT / PM**  
HANG STRAIGHT / ALL THREAD / PENDANT



SW1910GV SHOWN WITH RDC5PM

**CD**  
CORD / CABLE MOUNT



SW1910GV SHOWN WITH RDC5CD

**CM**  
CORD MOUNT



SW1910GV SHOWN WITH RDC5CM






# 19" SHORT WAREHOUSE SHADE

## DAMP / WET LOCATION

### CLASSIC SHAPES / PHOTOMETRIC DATA

SW1910GV-55L-35K-EX-TF2-MWI

#### CANDLEPOWER CURVE



Delivered Lumens: 4,534  
 Luminaire Watts: 39  
 LER: 116.26

#### INTENSITY

Intensity (cd)	Beam Angle (°)
0.00°	1,715
0.00°	1,715
5.00°	1,713
10.00°	1,682
15.00°	1,625
20.00°	1,549
30.00°	1,372
40.00°	1,177
50.00°	957
60.00°	701
70.00°	435
80.00°	190
90.00°	17

CP of 0deg (Nadir): 1,715  
 CRI: 85+

#### ZONAL LUMENS

Beam Angle Range (°)	Zonal Lumens	% of Total
0° - 10°	163	4%
0° - 20°	612	13%
0° - 30°	1,267	28%
0° - 40°	2,042	45%
0° - 60°	3,572	79%
0° - 80°	4,432	98%
0° - 90°	4,523	100%
Total	4,534	100%

Beam Angle: 106.45  
 Spacing Ratio: 1.19

#### SINGLE UNIT: PERFORMANCE

INITIAL FOOTCANDLES  
 BASED ON IES BEAM ANGLE

Mounting Height AFF	FC at Center on Floor	Beam Diameter	FC at Beam Edge
8.0'	27 fc	21.7'	9 fc
10.0'	17 fc	27.1'	6 fc
12.0'	12 fc	32.5'	4 fc
14.0'	9 fc	37.9'	3 fc
16.0'	7 fc	43.3'	2 fc
20.0'	4 fc	54.1'	1 fc
24.0'	3 fc	65.0'	1 fc
28.0'	2 fc	75.8'	1 fc

#### MULTIPLE UNITS: PERFORMANCE

80/50/20% REFLECTANCES  
 INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT

Ceiling Height	Fixture Spacing	RCR 1		RCR 3	
		FC *	W/Sq. Ft.	FC *	W/Sq. Ft.
17'	16' *	17	0.14	10	0.11
21'	18' **	15	0.13	12	0.13
25'	20' ***	12	0.10	8	0.08
Delivered Illuminance Rating: (DIR)		117 FC per W/Sq. Ft.		90 FC per W/Sq. Ft.	
* Suspension Length Square rooms used for multiple units: - RCR 1: Length & Width = Ceiling Ht. - 5.5' x 10.00 - RCR 3: Length & Width = Ceiling Ht. - 5.5' x 3.33 * Average Footcandles at 2.5' Above Floor ** Exceeds spacing criteria by 17% *** Exceeds spacing criteria by -2% **** Exceeds spacing criteria by -14%					

Lamp Multiplier: 15L x 0.265, 27L x 0.463, 37L x 0.679  
 CCT Multiplier: 27K x 0.971, 30K x 0.985, 40K x 1.03




# MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION. NOTE: THIS IS TYPICAL OF RLM SPECIFICATION FOR MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.




## WALL MOUNTING

**CP104 - SMALL DRIVER CANOPY (STANDARD)**  
MAY BE USED AS SPLICE BOX FOR DIRECT FEED  
NOT AVAILABLE W/ PA16 & PA16F




**CP106 - LARGE DRIVER CANOPY**  
MAY BE USED AS SPLICE BOX FOR DIRECT FEED



**CP6/RMD - REMOTE MOUNT DRIVER**  
MOUNTS DIRECTLY TO WALL OR OCTAGON STYLE J-BOX




CUSTOM AND OTHER WALL ARMS AVAILABLE - CONTACT FACTORY. ARMS MAY BE FIELD CUT ON WALL SIDE - FIXTURE SIDE THREADED 3/4" NPT REQUIRES SEALANT FOR WET LOCATION.




## CEILING MOUNTING


**RDC5 - SMALL DRIVER CANOPY (STANDARD)**  
MOUNTS TO 4" OCTO J-BOX



**CP13 - LARGE DRIVER CANOPY**




**HM\***  
HANG STRAIGHT  
45° SWIVEL 5/8" OD STEM - 3/8" IP




ORDER: HM (Length)  
SPECIFY LENGTH:  
HM3 - 3" HM24 - 24"  
HM6 - 6" HM36 - 36"  
HM12 - 12" HM48 - 48"  
HM18 - 18" HM72 - 72"  
HMLC(XX)  
Custom Length  
(Specify in Inches)

**PM\***  
RIGID PENDANT MOUNT  
RIGID 5/8" OD STEM - 3/8" IP




ORDER: PM (Length)  
SPECIFY LENGTH:  
PM3 - 3" PM24 - 24"  
PM6 - 6" PM36 - 36"  
PM12 - 12" PM48 - 48"  
PM18 - 18" PM72 - 72"  
PMLC(XX)  
Custom Length  
(Specify in Inches)

**AT\*\***  
HANG STRAIGHT ALL THREAD  
45° SWIVEL 5/8" OD STEM - 1/4" IP



ORDER: AT (Length)  
SPECIFY LENGTH:  
AT12 - 12"  
AT24 - 24"  
AT36 - 36"  
AT48 - 48"  
AT60 - 60"  
AT72 - 72"

**CD**  
CORD / CABLE MOUNT  
SJ CORD WITH 1/16" SS CABLE



ORDER: CD (Length)  
SPECIFY LENGTH:  
CD36 - 36"  
CD72 - 72"  
CD144 - 144"  
CDLC(XX)  
Custom Length  
(Specify in Inches)

**CM**  
CORD MOUNT  
SJ CORD WITH STRAIN RELIEF




ORDER: CM (Length)  
SPECIFY LENGTH:  
CM36 - 36"  
CM72 - 72"  
CM144 - 144"  
CMLC(XX)  
Custom Length  
(Specify in Inches)

\*MAXIMUM ONE PIECE STEM LENGTH IS 72". \*\*MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS.  
\*\*ORDER IN 12" INCREMENTS, ODD SIZES MAY BE FIELD CUT


## EMERGENCY BATTERY OPTIONS

**EMCR - LARGE DRIVER CANOPY FOR 10W EMERGENCY BATTERY**




## REMOTE EMERGENCY BATTERY OPTIONS

**EMRM\* - 7W REMOTE EMERGENCY BATTERY (50' MAX)**



**EMEN\* - 7W REMOTE EMERGENCY BATTERY WITH ENCLOSURE (50' MAX)**



\*OTHER EM BATTERY SIZES AVAILABLE. CONTACT FACTORY.

