



ALUMINUM DECO-REFLECTOR PENDANT DAMP LOCATION XT SERIES

PROJECT: _____

QUANTITY: _____ TYPE: _____



RPEXT1014XT
MT - Textured Silver
ORI - Orange Interior
FGR - Frosted Glass Ring



RPEXT1014XT
GB - Gloss Black
ALI - Almond Interior
CFG - Centered Frosted Glass Tier



RPEXT1014XT
AM - Anodic Malachite
GHI - Graphite Interior
FGR - Frosted Glass Ring



RPEXT1014XT
SN - Sun Gold
SFI - Sea Foam Interior
1MR - Single Metal Ring

SERIES	LUMENS ¹	CCT	DRIVER / DIMMING ²	MOUNTING ³	TIER OPTIONS	INTERIOR ⁷	FINISH ⁷		
RPEXT1014XT RPEXT1214XT	83 CRI		EX Electronic Driver, 120V/277V DO10X 1%, 0-10V, 120V/277V DS2W1 ELV/MLV, 120V DLTE1 Lutron® 2-Wire Forward Phase (MLV), 120V DL3EX 1%, Lutron® EcoSystem®, 120V/277V	HM⁴ Hang Straight AT⁴ Hang Straight All Thread PM⁴ Rigid Pendant Mount CD⁴ Cord / Cable Mount CM⁴ Cord Mount EMRM 7W Remote EM EMEN 7W Remote with Enclosure	CFG Center Frosted Glass Tier FGR Frosted Glass Ring 1MR⁵ Single Metal Ring TIER COLOR OPTIONS FC⁶ Fixture Color MW Matte White MB Matte Black PT Platinum Silver SN Sun Gold EG Evergreen RD Red Baron	MWI⁸ Matte White CCI Custom Color FCI Fixture Color Interior	MW⁸ Matte White MB⁸ Matte Black PT⁸ Platinum Silver CC Custom Color		
	10L	1000 Lm						27K	2700K
	13L	1300 Lm						30K	3000K
	20L	2000 Lm						35K	3500K
	30L	3000 Lm						40K	4000K
	40L	4000 Lm							
	98 CRI								
	10L	1000 Lm						27HK	2700K
	13L	1300 Lm						30HK	3000K
	20L	2000 Lm						35HK	3500K
30L	3000 Lm	40HK	4000K						

EXAMPLE: RPEXT1014XT30L30KEX/CD36PT1TCFG

NOTES:
 1 Nominal Source Lumens At Any CCT 2 Contact Factory for Additional Options 3 See Mounting Page for Details on Components and Finishes 4 Specify Length in Inches:
 See Mounting Page for Available Lengths 5 Tier to Match Fixture if Finish Not Specified 6 Same Finish as Housing 7 Reference Color Sheet Located on Product Webpage for
 Full List of Available Colors/Consult Factory for Special Finishes 8 Standard Finishes






ALUMINUM DECO-REFLECTOR PENDANT DAMP LOCATION XT SERIES

LUMENS / WATTAGE DATA				
PART NUMBER	SOURCE LUMENS ¹	DELIVERED LUMENS ²	SYSTEM WATTS	LPW
RP1014XT10L	1000	780	8	97.5
RP1014XT13L	1300	1014	12	84.5
RP1014XT20L	2000	1560	20	78
RP1014XT30L	3000	2340	30	78
RP1014XT40L	4000	3120	40	78

¹ Nominal Source Lumens at Any CCT ² Nominal Delivered Lumens at Any CCT

HOUSING DIMENSIONS



Dimensioned with RPEXT1014XT with Decorative Trim

SERIES	A	B
RPEXT1014XT	12.3	21.8
RPEXT1214XT	14.0	23.3

APPLICATION

The Aluminum Reflector Pendant's distinctive styling will enhance any space with efficient lighting and striking design. Deco series offers suspended glass and metal tier options.

FEATURES

SpecLume series fixtures offer simple contemporary style with functional luminaire performance. All fixtures are designed and manufactured in our factory. Reflector pendant is available in two sizes with direct lighting. Separate finishes may be chosen for fixture and mounting. Interchangeable LED module for ease of maintenance and upgradable. A variety of mounting and finish options available.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. A wide variety of standard and custom finishes are available. All exposed materials are chromate pretreated to resist corrosion. Matte white interior is standard.

ELECTRONICS

LED system features Xicato LED module with proprietary phosphor technology that provides consistent stable color with CCT control of +/- 100K over life of the light engine. Base CRI is 83 with 1 x 2-step MacAdam Ellipse binning. High CRI is 98 with 1 x 2-step MacAdam Ellipse binning. Variety of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Fixtures are machined in our factory from 0.125 thick aluminum and finished to specification. Passive machined aluminum heatsink for optimal thermal management. OSD diffusion optic lens standard.

CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750

SERIES SIZES

RPEXT1014XT



RPEXT1214XT



CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

HM / AT / PM

HANG STRAIGHT / ALL THREAD / PENDANT



RPEXT1014XT SHOWN WITH PM

CD

CORD / CABLE MOUNT



RPEXT1014XT SHOWN WITH CD

CM

CORD MOUNT



RPEXT1014XT SHOWN WITH CM



MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION. NOTE: THIS IS TYPICAL OF SPECULUME SPECIFICATION FOR PENDANT MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.



CEILING MOUNTING

<p>RDC5 - SMALL DRIVER CANOPY (STANDARD) MOUNTS TO 4" OCTO J-BOX</p> <p>CP13 - LARGE DRIVER CANOPY</p>	<p>HM* HANG STRAIGHT 45° SWIVEL 1/2" STEM - 3/8" NPT</p> <p>ORDER: HM (Length) SPECIFY LENGTH: HM3 - 3" HM24 - 24" HM6 - 6" HM36 - 36" HM12 - 12" HM48 - 48" HM18 - 18" HM72 - 72" HMLC(XX) Custom Length (Specify in Inches)</p>	<p>AT** HANG STRAIGHT ALL THREAD 45° SWIVEL 1/2" STEM - 1/4" IP</p> <p>ORDER: AT (Length) SPECIFY LENGTH: AT12 - 12" AT48 - 48" AT24 - 24" AT60 - 60" AT36 - 36" AT72 - 72" <small>FIELD-CUT THREADED PIPE TO LENGTH REQUIRED CUT PIPE COVER - 3/4" SHORTER THAN THREADED PIPE SLIP PIPE COVER OVER THREADED PIPE</small></p>	<p>PM* RIGID PENDANT MOUNT RIGID 1/2" STEM - 3/8" NPT</p> <p>ORDER: PM (Length) SPECIFY LENGTH: PM3 - 3" PM24 - 24" PM6 - 6" PM36 - 36" PM12 - 12" PM48 - 48" PM18 - 18" PM72 - 72" PMLLC(XX) Custom Length (Specify in Inches)</p>	<p>CD CORD / CABLE MOUNT SJ CORD WITH 1/16 SS CABLE</p> <p>ORDER: CD (Length) SPECIFY LENGTH: CD36 - 36" CD72 - 72" CD144 - 144" CDLC(XX) Custom Length (Specify in Inches)</p>	<p>CM CORD MOUNT SJ CORD WITH STRAIN RELIEF</p> <p>ORDER: CM (Length) SPECIFY LENGTH: CM36 - 36" CM72 - 72" CM144 - 144" CMLC(XX) Custom Length (Specify in Inches)</p>
--	--	--	--	--	--

*MAXIMUM ONE PIECE STEM LENGTH IS 72". **MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS. **ORDER IN 12" INCREMENTS. ODD SIZES MAY BE FIELD CUT

EMERGENCY BATTERY OPTIONS

EMCR - LARGE DRIVER CANOPY FOR 10W EMERGENCY BATTERY (FOR ROUND CEILING MOUNT TYPES)

REMOTE EMERGENCY BATTERY OPTIONS

<p>EMRM* - 7W REMOTE EMERGENCY BATTERY (50' MAX)</p> <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>1.3</td> <td>12.6</td> <td>13.0</td> </tr> </tbody> </table>	A	B	C	1.3	12.6	13.0	<p>EMEN* - 7W REMOTE EMERGENCY BATTERY WITH ENCLOSURE (50' MAX)</p> <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>2.0</td> <td>17.0</td> <td>6.2</td> </tr> </tbody> </table>	A	B	C	2.0	17.0	6.2
A	B	C											
1.3	12.6	13.0											
A	B	C											
2.0	17.0	6.2											

*OTHER EM BATTERY SIZES AVAILABLE. CONSULT FACTORY

