



GENE PENDANT
DAMP LOCATION
 GV SERIES

PROJECT: _____

QUANTITY: _____ TYPE: _____



AF0812COAFIAGV
 PT - Platinum Silver



AF0812COAFIAGV
 SN - Sun Gold



AF0812COAFIAGV
 BL - Blue Streak



AF0812COAFIAGV
 PG - Pub Green

SERIES	LUMENS ¹	CCT	DRIVER / DIMMING ²	MOUNTING ⁴	FINISH ⁷
AF0812COAFIAGV	15L 1500 Lm 27L 2700 Lm	27K 2700K 30K 3000K 35K 3500K 40K 4000K	EX Electronic Driver, 120V/277V DO10X 1% 0-10V, 120V/277V DS2W1 ELV/MLV, 120V DLTE1 ³ Lutron® 2-Wire Forward Phase (MLV), 120V DL3EX ³ 1%, Lutron® EcoSystem®, Fades to Black, 120V/277V	RDC5 Small Driver Canopy CP13 Large Driver Canopy HM ⁵ Hang Straight AT ⁵ Hang Straight All Thread PM ⁵ Rigid Pendant Mount CD ⁵ Cord / Cable Mount CM ⁵ Cord Mount EMCR ⁶ 10W Canopy Mounted EM EMRM 7W Remote EM EMEN 7W Remote with Enclosure	MWF ⁸ Matte White MB ⁸ Matte Black PT ⁸ Platinum Silver CC Custom Color

EXAMPLE: AF0812COAFIAGV15L35KEX/RDC5CD36PT

NOTES:
 1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 Available with CP13 Only 4 See Mounting Page for Details on Components and Finishes
 5 Specify Length in Inches: See Mounting Page for Available Lengths 6 EMCR Replaces RDC5 or CP13 7 Reference Color Sheet Located on Product Webpage for Full List of Available Colors 8 Standard Finishes





GENE PENDANT
DAMP LOCATION
 GV SERIES

DECORATIVE

LUMENS / WATTAGE DATA		
PART NUMBER	SOURCE LUMENS ¹	SYSTEM WATTS
AF0812COAFIAGV15L	1500	9
AF0812COAFIAGV27L	2700	16

¹ Nominal Source Lumens at 35K

APPLICATION

Gene Pendant features two layers of cast optical acrylic with conical aluminum shade to create a visually interesting area light.

FEATURES

SpecLume series fixtures offer contemporary style with functional luminaire performance. All fixtures are designed and manufactured in our factory. The Gene Pendant is one of the more complex designs with multiple layers of acrylic and aluminum. LED Driver in canopy for thermal management. A variety of mounting options are available. LED module and driver are serviceable for future replacement.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. See mounting and color pages for standard finishes.

ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 80+. Higher CRI, R9 and custom LED configurations are available; consult factory. Variety of electronic 120V/277V and dimming drivers.


CONSTRUCTION

Spun aluminum machined and fabricated UV stabilized acrylic.

CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.

HOUSING DIMENSIONS



A	B
8.5 215.9 mm	13.2 335.3 mm

CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

HM / AT / PM

HANG STRAIGHT / ALL THREAD / PENDANT



AF0812COAFIAGV SHOWN WITH RDC5PM

CD

CORD / CABLE MOUNT



AF0812COAFIAGV SHOWN WITH RDC5CD

CM

CORD MOUNT



AF0812COAFIAGV SHOWN WITH RDC5CM



MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.
NOTE: THIS IS TYPICAL OF SPECLUME SPECIFICATION FOR PENDANT MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.



CEILING MOUNTING

<p>RDC5 - SMALL DRIVER CANOPY (STANDARD) MOUNTS TO 4" OCTO J-BOX</p> <p>CP13 - LARGE DRIVER CANOPY</p>	<p>HM* HANG STRAIGHT 45° SWIVEL 1/2" STEM - 3/8" NPT</p> <p>ORDER: HM (Length) SPECIFY LENGTH: HM3 - 3" HM24 - 24" HM6 - 6" HM36 - 36" HM12 - 12" HM48 - 48" HM18 - 18" HM72 - 72" HMLC(XX) Custom Length (Specify in Inches)</p>	<p>AT** HANG STRAIGHT ALL THREAD 45° SWIVEL 5/8" OD STEM - 1/4" IP</p> <p>ORDER: AT (Length) SPECIFY LENGTH: AT12 - 12" AT48 - 48" AT24 - 24" AT60 - 60" AT36 - 36" AT72 - 72"</p> <p><small>FIELD CUTTABLE</small></p>	<p>PM* RIGID PENDANT MOUNT RIGID 1/2" STEM - 3/8" NPT</p> <p>ORDER: PM (Length) SPECIFY LENGTH: PM3 - 3" PM24 - 24" PM6 - 6" PM36 - 36" PM12 - 12" PM48 - 48" PM18 - 18" PM72 - 72" PMLLC(XX) Custom Length (Specify in Inches)</p>	<p>CD CORD / CABLE MOUNT SJ CORD WITH 1/16 SS CABLE</p> <p>ORDER: CD (Length) SPECIFY LENGTH: CD36 - 36" CD72 - 72" CD144 - 144" CDLC(XX) Custom Length (Specify in Inches)</p>	<p>CM CORD MOUNT SJ CORD WITH STRAIN RELIEF</p> <p>ORDER: CM (Length) SPECIFY LENGTH: CM36 - 36" CM72 - 72" CM144 - 144" CMLC(XX) Custom Length (Specify in Inches)</p>
--	---	---	---	---	---

*MAXIMUM ONE PIECE STEM LENGTH IS 72". **MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS.
**ORDER IN 12" INCREMENTS, ODD SIZES MAY BE FIELD CUT

EMERGENCY BATTERY OPTIONS

EMCR - LARGE DRIVER CANOPY FOR
TOW EMERGENCY BATTERY
(FOR ROUND CEILING MOUNT TYPES)

REMOTE EMERGENCY BATTERY OPTIONS

<p>EMRM* - 7W REMOTE EMERGENCY BATTERY (50' MAX)</p> <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>1.3</td> <td>12.6</td> <td>13.0</td> </tr> </tbody> </table>	A	B	C	1.3	12.6	13.0	<p>EMEN* - 7W REMOTE EMERGENCY BATTERY WITH ENCLOSURE (50' MAX)</p> <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>2.0</td> <td>17.0</td> <td>6.2</td> </tr> </tbody> </table>	A	B	C	2.0	17.0	6.2
A	B	C											
1.3	12.6	13.0											
A	B	C											
2.0	17.0	6.2											

*OTHER EM BATTERY SIZES AVAILABLE, CONSULT FACTORY

