



ALUMINUM DECO-REFLECTOR PENDANT DAMP LOCATION XT SERIES

PROJECT: _____
 QUANTITY: _____ TYPE: _____



RP1014XT
 GH - Graphite
 LGI - Lime Green Interior
 FGR - Frosted Glass Ring



RP1014XT
 AY - Aero Yellow
 EGI - Evergreen Interior
 CFG - Center Frosted Glass Tier



RP1014XT
 OR - Orange
 MWI - Matte White Interior
 FGR - Frosted Glass Tier



RP1014XT
 BR - Brecchia
 BZI - Bronze Interior
 1MR - Single Metal Ring

SERIES	LUMENS ¹	CCT	DRIVER / DIMMING ²	MOUNTING ⁴	TIER OPTIONS	INTERIOR ¹⁰	FINISH ¹⁰
RP1014XT RP1214XT	10L 1000 Lm	83 CRI	EX Electronic Driver, 120V/277V DO10X 1%, 0-10V, 120V/277V DS2W1 ELV/MLV, 120V DLTE1³ Lutron® 2-Wire Forward Phase (MLV), 120V DL3EX³ 1%, Lutron® EcoSystem®, 120V/277V	RDC5⁵ Small Driver Canopy CP13³ Large Driver Canopy HM⁶ Hang Straight AT⁶ Hang Straight All Thread PM⁶ Rigid Pendant Mount CD⁶ Cord / Cable Mount CM⁶ Cord Mount EMCR⁷ 10W Canopy Mounted EM EMRM⁷ 7W Remote EM EMEN⁷ 7W Remote with Enclosure	CFG Center Frosted Glass Tier FGR Frosted Glass Ring 1MR⁸ Single Metal Ring TIER COLOR OPTIONS FC⁹ Fixture Color MW Matte White MB Matte Black PT Platinum Silver SN Sun Gold EG Evergreen RD Red Baron	MWI¹¹ Matte White CCI Custom Color FCI Fixture Color Interior	MW¹¹ Matte White MB¹¹ Matte Black PT¹¹ Platinum Silver CC Custom Color
	13L 1300 Lm 20L 2000 Lm 30L 3000 Lm	27K 2700K 30K 3000K 35K 3500K 40K 4000K 98 CRI 27HK 2700K 30HK 3000K 35HK 3500K 40HK 4000K					

EXAMPLE: RP1014XT10L27KEX/RDC5CD24CFGMWIMB

NOTES:
 1 Nominal Source Lumens At Any CCT 2 Contact Factory for Additional Options 3 CP13 Required for Lutron Drivers 4 See Mounting Page for Details on Components and Finishes 5 Required for All Drivers Excluding Lutron Drivers 6 Specify Length in Inches: See Mounting Page for Available Lengths 7 EMCR Replaces RDC5 or CP13 8 Tier to Match Fixture if Finish Not Specified 9 Same Finish as Housing 10 Reference Color Sheet Located on Product Webpage for Full List of Available Colors/Consult Factory for Special Finishes 11 Standard Finishes






ALUMINUM DECO-REFLECTOR PENDANT DAMP LOCATION XT SERIES

LUMENS / WATTAGE DATA				
PART NUMBER	SOURCE LUMENS ¹	DELIVERED LUMENS ²	SYSTEM WATTS	LPW
RP1014XT10L	1000	675	8	84
RP1014XT13L	1300	877	12	73
RP1014XT20L	2000	1300	20	63.5
RP1014XT30L	3000	2025	30	67.5

¹ Nominal Source Lumens at Any CCT ² Nominal Delivered Lumens at Any CCT

HOUSING DIMENSIONS



Dimensioned with **RP1014XT with Decorative Trim**

SERIES	A	B
RP1014XT	12.3	15.3
RP1214XT	14.0	17.0

APPLICATION

Reflector Pendant's distinctive styling will enhance any space with efficient lighting and striking design. The Deco-Reflector features suspended glass and metal tier options.

FEATURES

SpecLume series fixtures offer simple contemporary style with functional luminaire performance. All fixtures are designed and manufactured in our factory. Reflector pendant is available in two sizes with direct lighting. Separate finishes may be chosen for fixture and mounting. Interchangeable LED module for ease of maintenance. Electronic LED Driver in canopy for thermal management. A variety of mounting and finish options available.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. A wide variety of standard and custom finishes are available. All exposed materials are chromate pretreated to resist corrosion. Specify inside and outside finish. Matte white interior is standard.

ELECTRONICS

LED system features Xicato LED module with proprietary phosphor technology that provides consistent stable color with CCT control of +/- 100K over life of the light engine. Base CRI is 83 with 1 x 2-step MacAdam Ellipse binning. High CRI is 98 with 1 x 2-step MacAdam Ellipse binning. Variety of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Fixtures are spun in our factory from 0.063 high purity aluminum. Passive extruded aluminum heatsink for optimal thermal management. Deco tier glass is tempered and finished to specification. OSD diffusion optic lens standard.

CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750

SERIES SIZES

RP1014XT



RP1214XT



CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

HM / AT / PM

HANG STRAIGHT / ALL THREAD / PENDANT



RP1014XT SHOWN WITH RDC5PM

CD

CORD / CABLE MOUNT



RP1014XT SHOWN WITH RDC5CD

CM

CORD MOUNT



RP1014XT SHOWN WITH RDC5CM



MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION. NOTE: THIS IS TYPICAL OF SPECULUME SPECIFICATION FOR PENDANT MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.



CEILING MOUNTING

<p>RDC5 - SMALL DRIVER CANOPY (STANDARD) MOUNTS TO 4" OCTO J-BOX</p> <p>CP13 - LARGE DRIVER CANOPY</p>	<p>HM* HANG STRAIGHT 45° SWIVEL 1/2" STEM - 3/8" NPT</p> <p>ORDER: HM (Length) SPECIFY LENGTH: HM3 - 3" HM24 - 24" HM6 - 6" HM36 - 36" HM12 - 12" HM48 - 48" HM18 - 18" HM72 - 72" HMLC(XX) Custom Length (Specify in Inches)</p>	<p>AT** HANG STRAIGHT ALL THREAD 45° SWIVEL 1/2" STEM - 1/4" IP</p> <p>ORDER: AT (Length) SPECIFY LENGTH: AT12 - 12" AT48 - 48" AT24 - 24" AT60 - 60" AT36 - 36" AT72 - 72" <small>FIELD-CUT THREADED PIPE TO LENGTH REQUIRED CUT PIPE COVER - 3/4" SHORTER THAN THREADED PIPE SLIP PIPE COVER OVER THREADED PIPE</small></p>	<p>PM* RIGID PENDANT MOUNT RIGID 1/2" STEM - 3/8" NPT</p> <p>ORDER: PM (Length) SPECIFY LENGTH: PM3 - 3" PM24 - 24" PM6 - 6" PM36 - 36" PM12 - 12" PM48 - 48" PM18 - 18" PM72 - 72" PMLLC(XX) Custom Length (Specify in Inches)</p>	<p>CD CORD / CABLE MOUNT SJ CORD WITH 1/16 SS CABLE</p> <p>ORDER: CD (Length) SPECIFY LENGTH: CD36 - 36" CD72 - 72" CD144 - 144" CDLC(XX) Custom Length (Specify in Inches)</p>	<p>CM CORD MOUNT SJ CORD WITH STRAIN RELIEF</p> <p>ORDER: CM (Length) SPECIFY LENGTH: CM36 - 36" CM72 - 72" CM144 - 144" CMLC(XX) Custom Length (Specify in Inches)</p>
--	--	--	--	--	--

*MAXIMUM ONE PIECE STEM LENGTH IS 72". **MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS. **ORDER IN 12" INCREMENTS. ODD SIZES MAY BE FIELD CUT

EMERGENCY BATTERY OPTIONS

EMCR - LARGE DRIVER CANOPY FOR 10W EMERGENCY BATTERY (FOR ROUND CEILING MOUNT TYPES)

REMOTE EMERGENCY BATTERY OPTIONS

<p>EMRM* - 7W REMOTE EMERGENCY BATTERY (50' MAX)</p> <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>1.3</td> <td>12.6</td> <td>13.0</td> </tr> </tbody> </table>	A	B	C	1.3	12.6	13.0	<p>EMEN* - 7W REMOTE EMERGENCY BATTERY WITH ENCLOSURE (50' MAX)</p> <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>2.0</td> <td>17.0</td> <td>6.2</td> </tr> </tbody> </table>	A	B	C	2.0	17.0	6.2
A	B	C											
1.3	12.6	13.0											
A	B	C											
2.0	17.0	6.2											

*OTHER EM BATTERY SIZES AVAILABLE. CONSULT FACTORY

