



4" ROUND DIRECT DAMP LOCATION GAMMA SERIES

PROJECT: _____
 QUANTITY: _____ TYPE: _____



CF0406PC



CF0412PC



CF0418PC

SERIES	LUMENS ¹	CCT	OPTICS	DRIVER / DIMMING ²	LENS	MOUNTING ³	EMERGENCY BATTERY OPTIONS	FINISH ⁶	MOUNTING ACCESSORIES ⁸	FINISH
CF0406PC 4" x 6"	10L 750 Lm	80 CRI	ND 20°	EX Electronic Driver, 120V/277V DS2W1 ELV/TRIAC, 120V	NL No Lens CL Clear Glass Lens SO Micro Prism Solite™ Lens HL Hex Louver	HM ¹ Hang Straight PM ¹ Rigid Pendant Mount AT ¹ Hang Straight All Thread SM Surface Mount	EMCRC 10W Canopy Mounted EM EMRM 7W Remote EM EMEN 7W Remote with Enclosure	MW ⁷ Matte White MB ⁷ Matte Black PT ⁷ Platinum Silver CC Custom Color	RDC5CB ⁸ Blank Canopy to match fixtures when ordering other CM & CD mounted fixtures with EMRM or EMEN CR9B ⁸ Blank EMCRD canopy to match when ordering other fixtures with the EMCRC option	MC Match Color
	15L 1150 Lm	27K 2700K	MD 26°							
CF0412PC 4" x 12"	20L 1550 Lm	30K 3000K	WD 51°							
		35K 3500K	XW 61°							
CF0418PC 4" x 18"		40K 4000K								
		90 CRI				CM ¹⁰ Cord Mount CD ¹⁰ Cord / Cable Mount CD72 ¹⁰ 72" Cord / Cable Mount	EMMRDRC5C 7W Remote EM with RDC5C EMENRDC5C 7W Remote EM with Enclosure & RDC5C			

GREEN TEXT INDICATES QUICK SHIP OPTIONS

EXAMPLE: CF0406PC15L35KNDEX/NL/HM36/MW

NOTES:


- 1 Nominal Delivered Lumens at 3500K
- 2 Consult Factory for Additional Options
- 3 See Mounting Page for Details on Components and Finishes
- 4 Specify Length in Inches: See Mounting Page for Available Lengths
- 5 EMRM & EMEN Option Comes with RDC5C Canopy with CD and CM Mounting
- 6 Reference color sheet located on product webpage for full list of available colors
- 7 Standard Finishes
- 8 Order These Canopies When Matching Mounting Between EM and non-EM Fixtures
- 9 Use RDC5CB When Looking to Match Mounting of CM or CD fixtures with EMRM/RDC5C & EMEN/RDC5C options
- 10 Use CR9B When Looking to Match Mounting EMCRC Equipped Fixtures





4" ROUND DIRECT DAMP LOCATION GAMMA SERIES

DIMENSIONS



Dimensioned with **CF0412PC**

SERIES	A	B
CF0406PC	4.0	6.4
CF0412PC	4.0	12.4
CF0418PC	4.0	18.4

LUMENS / WATTAGE DATA			
PART NUMBER	DELIVERED LUMENS ¹	SYSTEM WATTS	LPW
CF0412PC 10L	736	6.5	113
CF0412PC 15L	1089	9.5	115
CF0412PC 20L	1471	12.9	114

¹ Nominal Delivered Lumens at 3500K, 80 CRI, Medium Optic with Clear Lens

QUICK SHIP

Quick Ship highlights products that can ship in 5 - 10 working days.

APPLICATION

The Gamma Family of Cylinders are a robust offering of point source LED luminaires featuring high efficacies, an assortment of optical control, and installation flexibility, which make them suitable for a wide range of commercial and institutional applications.

ELECTRONICS

Solid-state light engine available in various color temperatures and lumen outputs. Specifiable in 2700K, 3000K, 3500K, 4000K in CRI 80 (Typ.), or 2700K, 3000K, 3500K, 4000K in CRI 90 (Typ.), color accuracy ≤ 3 SDCM. Selection of integral electronic constant current, dimmable drivers available, power factor > 0.9 (Typ). Driver and light engine are field serviceable for future replacement or upgrades. Emergency battery options provide 10W or 7W for 90 minutes.

CONSTRUCTION

Seamless cylinder body machined from 6063 extruded aluminum. Trim and top cap are die-cast aluminum. Twist and lock trim design for no visible fasteners. Passive aluminum heatsink optimized for LED life and performance. Specular reflectors offered in variety of beam spreads. Lens accessory options available (maximum of 2). Luminaire will not exceed 5 lbs.

MOUNTING

All pendant option lengths are specified in inches. Mounting bracket and canopies provided for direct installation with 4" octagonal junction boxes. Hang Mount (3/8"NPT), All-Thread (1/4"IP), and Rigid Stem (3/8"IP) are 1/2" diameter and produced from steel pipe. Hang Mount and All-Thread options provide up to 45° tilt correction. Cord/Cable Mount kit provided with adjustable aircraft cable and power cord, allows field-adjustable suspension length. Cord Mount provided with power cord and strain reliefs. Surface mount kit provided with aluminum mounting plate to install directly to junction box. Contact factory for special installation circumstances. All CM & CD mounted Gamma fixtures ordered with a remote emergency battery come standard with the RDC5C canopy, if you are also ordering non-remote emergency battery fixtures we recommend ordering them with the RDC5CB canopy as well to maintain visual consistency on site.

FINISH

Multi-stage polyester powder-coat process applied on our in-house finishing department. Custom colors also available (contact factory with RAL#). Canopy and stems will match cylinder finish specification.

CODE COMPLIANCE

ETL Listed. Suitable for dry or damp locations with operation in ambient conditions up to 25°C. 5 year limited warranty on all components. Proudly designed and manufactured in Massachusetts, USA.

SERIES SIZES

CF0406PC



CF0412PC



CF0418PC



STANDARD FINISHES SHOWN WITH CF0412PC

MW
Matte White



MB
Matte Black



PT
Platinum Silver



CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

HM / AT / PM

HANG STRAIGHT / ALL THREAD / PENDANT



CF0412PC SHOWN WITH PM

CD

CORD / CABLE MOUNT



CF0412PC SHOWN WITH CD

CD & RDC5C

CORD / CABLE MOUNT



CF0412PC SHOWN WITH CD & RDC5C CANOPY

CM

CORD MOUNT



CF0412PC SHOWN WITH CM

CM & RDC5C

CORD MOUNT



CF0412PC SHOWN WITH CM & RDC5C CANOPY

SM

SURFACE MOUNT



CF0412PC SHOWN WITH SM





4" ROUND DIRECT

GAMMA SERIES / PHOTOMETRIC DATA

CF04XXPC 20L 35K ND XX CL XX

CANDLEPOWER CURVE TEST SP-01069	INTENSITY CANDELA 0° AZIMUTH	ZONAL LUMENS	SINGLE UNIT: PERFORMANCE DIRECT FOOTCANDLES BASED ON DOWNLIGHT ONLY	MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT																																								
	0°	0° - 10° 486 34%	Mounting Height Aff	<table border="1"> <thead> <tr> <th rowspan="2">Ceiling Height</th> <th rowspan="2">Fixture Spacing</th> <th colspan="2">RCR 4</th> <th colspan="2">RCR 6</th> </tr> <tr> <th>FC *</th> <th>W/Sq. Ft.</th> <th>FC *</th> <th>W/Sq. Ft.</th> </tr> </thead> <tbody> <tr> <td>14'</td> <td>3'</td> <td>155</td> <td>1.46</td> <td>127</td> <td>1.30</td> </tr> <tr> <td>18'</td> <td>4'</td> <td>77</td> <td>0.72</td> <td>91</td> <td>0.92</td> </tr> <tr> <td>22'</td> <td>5'</td> <td>58</td> <td>0.55</td> <td>54</td> <td>0.55</td> </tr> <tr> <td colspan="2">Delivered Illuminance Rating: (DIR)</td> <td colspan="2">106 FC per W/Sq. Ft.</td> <td colspan="2">98 FC per W/Sq. Ft.</td> </tr> <tr> <td colspan="6"> 2' Suspension Length to luminous aperture Square rooms used for multiple units: RCR 4: Length & Width = Ceiling Ht. - 4.5' x 2.50 RCR 6: Length & Width = Ceiling Ht. - 4.5' x 1.66 * Average Footcandles at 2.5' Above Floor </td> </tr> </tbody> </table>	Ceiling Height	Fixture Spacing	RCR 4		RCR 6		FC *	W/Sq. Ft.	FC *	W/Sq. Ft.	14'	3'	155	1.46	127	1.30	18'	4'	77	0.72	91	0.92	22'	5'	58	0.55	54	0.55	Delivered Illuminance Rating: (DIR)		106 FC per W/Sq. Ft.		98 FC per W/Sq. Ft.		2' Suspension Length to luminous aperture Square rooms used for multiple units: RCR 4: Length & Width = Ceiling Ht. - 4.5' x 2.50 RCR 6: Length & Width = Ceiling Ht. - 4.5' x 1.66 * Average Footcandles at 2.5' Above Floor					
	Ceiling Height	Fixture Spacing	RCR 4				RCR 6																																					
			FC *		W/Sq. Ft.	FC *	W/Sq. Ft.																																					
	14'	3'	155		1.46	127	1.30																																					
	18'	4'	77		0.72	91	0.92																																					
	22'	5'	58		0.55	54	0.55																																					
	Delivered Illuminance Rating: (DIR)		106 FC per W/Sq. Ft.		98 FC per W/Sq. Ft.																																							
	2' Suspension Length to luminous aperture Square rooms used for multiple units: RCR 4: Length & Width = Ceiling Ht. - 4.5' x 2.50 RCR 6: Length & Width = Ceiling Ht. - 4.5' x 1.66 * Average Footcandles at 2.5' Above Floor																																											
	0° 7143	0° - 20° 945 66%	8' 112 fc 2.7' 53 fc																																									
	5° 5957	0° - 30° 1240 86%	10' 71 fc 3.4' 34 fc																																									
	15° 1567	0° - 40° 1408 98%	12' 50 fc 4.1' 24 fc																																									
25° 638	0° - 60° 1432 100%	14' 36 fc 4.8' 17 fc																																										
35° 275	0° - 80° 1437 100%	16' 28 fc 5.5' 13 fc																																										
45° 11	0° - 90° 1439 100%	20' 18 fc 6.8' 9 fc																																										
55° 10	Total 1439 100%	24' 12 fc 8.2' 6 fc																																										
90° 1		28' 9 fc 9.5' 4 fc																																										

Delivered Lumens: 1439
Luminaire Watts: 12.9
LER: 111.55

CP at 0° (Nadir): 7143
CRI: 80

Beam Angle: 20°
Spacing Ratio: 0.33

Lumen Multiplier: 10L x 0.5, 15L x 0.74
CCT Multiplier: 27K x 0.972, 30K x 0.981, 40K x 1.04
27HK x 0.78, 30HK x 0.82

CF04XXPC 20L 35K MD XX CL XX

CANDLEPOWER CURVE TEST SP-01068	INTENSITY CANDELA 0° AZIMUTH	ZONAL LUMENS	SINGLE UNIT: PERFORMANCE DIRECT FOOTCANDLES BASED ON DOWNLIGHT ONLY	MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT																																								
	0°	0° - 10° 371 25%	Mounting Height Aff	<table border="1"> <thead> <tr> <th rowspan="2">Ceiling Height</th> <th rowspan="2">Fixture Spacing</th> <th colspan="2">RCR 3</th> <th colspan="2">RCR 5</th> </tr> <tr> <th>FC *</th> <th>W/Sq. Ft.</th> <th>FC *</th> <th>W/Sq. Ft.</th> </tr> </thead> <tbody> <tr> <td>14'</td> <td>4'</td> <td>93</td> <td>0.82</td> <td>91</td> <td>0.89</td> </tr> <tr> <td>18'</td> <td>6"</td> <td>46</td> <td>0.41</td> <td>45</td> <td>0.44</td> </tr> <tr> <td>22'</td> <td>8"</td> <td>21</td> <td>0.19</td> <td>17</td> <td>0.17</td> </tr> <tr> <td colspan="2">Delivered Illuminance Rating: (DIR)</td> <td colspan="2">112 FC per W/Sq. Ft.</td> <td colspan="2">102 FC per W/Sq. Ft.</td> </tr> <tr> <td colspan="6"> 2' Suspension Length to luminous aperture Square rooms used for multiple units: RCR 3: Length & Width = Ceiling Ht. - 4.5' x 3.33 RCR 5: Length & Width = Ceiling Ht. - 4.5' x 2.00 * Average Footcandles at 2.5' Above Floor ** Exceeds Spacing Ratio by 3% *** Exceeds Spacing Ratio by 6% </td> </tr> </tbody> </table>	Ceiling Height	Fixture Spacing	RCR 3		RCR 5		FC *	W/Sq. Ft.	FC *	W/Sq. Ft.	14'	4'	93	0.82	91	0.89	18'	6"	46	0.41	45	0.44	22'	8"	21	0.19	17	0.17	Delivered Illuminance Rating: (DIR)		112 FC per W/Sq. Ft.		102 FC per W/Sq. Ft.		2' Suspension Length to luminous aperture Square rooms used for multiple units: RCR 3: Length & Width = Ceiling Ht. - 4.5' x 3.33 RCR 5: Length & Width = Ceiling Ht. - 4.5' x 2.00 * Average Footcandles at 2.5' Above Floor ** Exceeds Spacing Ratio by 3% *** Exceeds Spacing Ratio by 6%					
	Ceiling Height	Fixture Spacing	RCR 3				RCR 5																																					
			FC *		W/Sq. Ft.	FC *	W/Sq. Ft.																																					
	14'	4'	93		0.82	91	0.89																																					
	18'	6"	46		0.41	45	0.44																																					
	22'	8"	21		0.19	17	0.17																																					
	Delivered Illuminance Rating: (DIR)		112 FC per W/Sq. Ft.		102 FC per W/Sq. Ft.																																							
	2' Suspension Length to luminous aperture Square rooms used for multiple units: RCR 3: Length & Width = Ceiling Ht. - 4.5' x 3.33 RCR 5: Length & Width = Ceiling Ht. - 4.5' x 2.00 * Average Footcandles at 2.5' Above Floor ** Exceeds Spacing Ratio by 3% *** Exceeds Spacing Ratio by 6%																																											
	0° 4763	0° - 20° 909 62%	8' 74 fc 3.7' 34 fc																																									
	5° 4247	0° - 30° 1260 86%	10' 48 fc 4.6' 22 fc																																									
	15° 1954	0° - 40° 1438 98%	12' 33 fc 5.6' 15 fc																																									
25° 749	0° - 60° 1463 99%	14' 24 fc 6.5' 11 fc																																										
35° 286	0° - 80° 1469 100%	16' 19 fc 7.4' 9 fc																																										
45° 15	0° - 90° 1471 100%	20' 12 fc 9.3' 5 fc																																										
55° 6	Total 1471 100%	24' 8 fc 11.1' 4 fc																																										
90° 0		28' 6 fc 13.0' 3 fc																																										

Delivered Lumens: 1471
Luminaire Watts: 12.9
LER: 114.03

CP at 0° (Nadir): 4763
CRI: 80

Beam Angle: 26°
Spacing Ratio: 0.43

Lumen Multiplier: 10L x 0.5, 15L x 0.74
CCT Multiplier: 27K x 0.972, 30K x 0.981, 40K x 1.04
27HK x 0.78, 30HK x 0.82

CF04XXPC 20L 35K WD XX CL XX

CANDLEPOWER CURVE TEST SP-01070	INTENSITY CANDELA 0° AZIMUTH	ZONAL LUMENS	SINGLE UNIT: PERFORMANCE DIRECT FOOTCANDLES BASED ON DOWNLIGHT ONLY	MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT																																								
	0°	0° - 10° 207 14%	Mounting Height Aff	<table border="1"> <thead> <tr> <th rowspan="2">Ceiling Height</th> <th rowspan="2">Fixture Spacing</th> <th colspan="2">RCR 2</th> <th colspan="2">RCR 4</th> </tr> <tr> <th>FC *</th> <th>W/Sq. Ft.</th> <th>FC *</th> <th>W/Sq. Ft.</th> </tr> </thead> <tbody> <tr> <td>14'</td> <td>6'</td> <td>43</td> <td>0.37</td> <td>38</td> <td>0.37</td> </tr> <tr> <td>18'</td> <td>8'</td> <td>21</td> <td>0.18</td> <td>19</td> <td>0.18</td> </tr> <tr> <td>22'</td> <td>10'</td> <td>16</td> <td>0.14</td> <td>11</td> <td>0.11</td> </tr> <tr> <td colspan="2">Delivered Illuminance Rating: (DIR)</td> <td colspan="2">118 FC per W/Sq. Ft.</td> <td colspan="2">105 FC per W/Sq. Ft.</td> </tr> <tr> <td colspan="6"> 2' Suspension Length to luminous aperture Square rooms used for multiple units: RCR 2: Length & Width = Ceiling Ht. - 4.5' x 5.00 RCR 4: Length & Width = Ceiling Ht. - 4.5' x 2.50 * Average Footcandles at 2.5' Above Floor </td> </tr> </tbody> </table>	Ceiling Height	Fixture Spacing	RCR 2		RCR 4		FC *	W/Sq. Ft.	FC *	W/Sq. Ft.	14'	6'	43	0.37	38	0.37	18'	8'	21	0.18	19	0.18	22'	10'	16	0.14	11	0.11	Delivered Illuminance Rating: (DIR)		118 FC per W/Sq. Ft.		105 FC per W/Sq. Ft.		2' Suspension Length to luminous aperture Square rooms used for multiple units: RCR 2: Length & Width = Ceiling Ht. - 4.5' x 5.00 RCR 4: Length & Width = Ceiling Ht. - 4.5' x 2.50 * Average Footcandles at 2.5' Above Floor					
	Ceiling Height	Fixture Spacing	RCR 2				RCR 4																																					
			FC *		W/Sq. Ft.	FC *	W/Sq. Ft.																																					
	14'	6'	43		0.37	38	0.37																																					
	18'	8'	21		0.18	19	0.18																																					
	22'	10'	16		0.14	11	0.11																																					
	Delivered Illuminance Rating: (DIR)		118 FC per W/Sq. Ft.		105 FC per W/Sq. Ft.																																							
	2' Suspension Length to luminous aperture Square rooms used for multiple units: RCR 2: Length & Width = Ceiling Ht. - 4.5' x 5.00 RCR 4: Length & Width = Ceiling Ht. - 4.5' x 2.50 * Average Footcandles at 2.5' Above Floor																																											
	0° 2121	0° - 20° 716 48%	6' 59 fc 5.7' 22 fc																																									
	5° 2136	0° - 30° 1220 82%	8' 33 fc 7.7' 12 fc																																									
	15° 1874	0° - 40° 1457 98%	10' 21 fc 9.6' 8 fc																																									
25° 1111	0° - 60° 1483 100%	12' 15 fc 11.5' 5 fc																																										
35° 365	0° - 80° 1487 100%	14' 11 fc 13.4' 4 fc																																										
45° 15	0° - 90° 1488 100%	16' 8 fc 15.3' 3 fc																																										
55° 2	Total 1488 100%	20' 5 fc 19.2' 2 fc																																										
90° 1		24' 4 fc 23.0' 1 fc																																										

Delivered Lumens: 1488
Luminaire Watts: 12.9
LER: 115.35

CP at 0° (Nadir): 2121
CRI: 80

Beam Angle: 51°
Spacing Ratio: 0.81

Lumen Multiplier: 10L x 0.5, 15L x 0.74
CCT Multiplier: 27K x 0.972, 30K x 0.981, 40K x 1.04
27HK x 0.78, 30HK x 0.82






4" ROUND DIRECT

GAMMA SERIES / PHOTOMETRIC DATA

CF04XXPC 20L 35K XW XX CL XX

CANDLEPOWER CURVE TEST SP-01071	INTENSITY CANDELA 0° AZIMUTH	ZONAL LUMENS		SINGLE UNIT: PERFORMANCE DIRECT FOOTCANDLES BASED ON DOWNLIGHT ONLY				MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT							
		0°	0° - 10°	15%	11%	Mounting Height AFF	FC at Center on Floor	Beam Diameter	FC at Beam Edge	Ceiling Height	Fixture Spacing	RCR 2		RCR 4	
											FC *	W/Sq. Ft.	FC *	W/Sq. Ft.	
	0°	1678	0° - 10°	159	11%	6'	47 fc	7.1'	15 fc	14'	8'	24	0.21	21	0.21
	5°	1656	0° - 20°	596	41%	8'	26 fc	9.5'	8 fc	16'	10'	16	0.14	14	0.14
	15°	1558	0° - 30°	1150	78%	10'	17 fc	11.8'	5 fc	22'	12'	10	0.08	6	0.06
	25°	1243	0° - 40°	1432	98%	12'	12 fc	14.2'	4 fc	Delivered Illuminance Rating: (DIR)		116 FC per W/Sq. Ft.		102 FC per W/Sq. Ft.	
	35°	447	0° - 60°	1462	100%	14'	9 fc	16.6'	3 fc	2' Suspension Length to luminous aperture Square rooms used for multiple units: RCR 2: Length & Width = Ceiling Ht. - 4.5' x 5.00 RCR 4: Length & Width = Ceiling Ht. - 4.5' x 2.50 * Average Footcandles at 2.5' Above Floor					
	45°	18	0° - 80°	1466	100%	16'	7 fc	19.0'	2 fc						
	55°	3	0° - 90°	1468	100%	20'	4 fc	23.7'	1 fc						
	90°	1	Total	1468	100%	24'	3 fc	28.4'	1 fc						



Delivered Lumens: **1468**
 Luminaire Watts: **12.9**
 LER: **113.80**

CP at 0° (Nadir): **1678**
 CRI: **80**

Beam Angle: **61°**
 Spacing Ratio: **0.98**

Lumen Multiplier: 10L x 0.5, 15L x 0.74
 CCT Multiplier: 27K x 0.972, 30K x 0.981, 40K x 1.04
 27HK x 0.78, 30HK x 0.82



STANDARD MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES, CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.
NOTE: THIS IS TYPICAL OF CYLINDERS SPECIFICATION FOR PENDANT MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.



CANOPY DIMENSIONS

HM / PM / AT CANOPY		CM CANOPY		CM RDC5C CANOPY		CD CANOPY		CD RDC5C CANOPY		SM CANOPY	EMCRC CANOPY	
A	B	A	B	A	B	A	B	A	B	A	A	B
5.0 127.0 mm	1.5 38.1 mm	5.0 127.0 mm	.25 6.4 mm	5.3 134.6 mm	2.5 63.5 mm	5.0 127.0 mm	.25 6.4 mm	5.3 134.6 mm	2.5 63.5 mm	4.9 124.5 mm	9.0 228.6 mm	3.25 82.6 mm

MOUNTING TYPES

<p>HM* HANG STRAIGHT 45° SWIVEL 5/8" OD STEM - 3/8" IP</p> <p>ORDER: HM (Length) SPECIFY LENGTH: HM3 - 3" HM24 - 24" HM6 - 6" HM36 - 36" HM12 - 12" HM48 - 48" HM18 - 18" HM72 - 72" HMLC(XX) Custom Length (Specify in Inches)</p>	<p>PM* RIGID PENDANT MOUNT RIGID 5/8" OD STEM - 3/8" IP</p> <p>ORDER: PM (Length) SPECIFY LENGTH: PM3 - 3" PM24 - 24" PM6 - 6" PM36 - 36" PM12 - 12" PM48 - 48" PM18 - 18" PM72 - 72" PMLC(XX) Custom Length (Specify in Inches)</p>	<p>AT** HANG STRAIGHT ALL THREAD 45° SWIVEL 5/8" OD STEM - 1/4" IP</p> <p>ORDER: AT (Length) SPECIFY LENGTH: AT12 - 12" AT24 - 24" AT36 - 36"</p> <p>FIELD CUT THREADED PIPE TO LENGTH NEEDED CUT PIPE COVER .314" SHORTER THAN THREADED PIPE SLIP PIPE COVER OVER THREADED PIPE</p>	<p>CM CORD MOUNT SJ CORD WITH STRAIN RELIEF</p> <p>ORDER: CM (Length) SPECIFY LENGTH: CM36 - 36" CM72 - 72" CM144 - 144" CMLC(XX) Custom Length (Specify in Inches)</p>	<p>CD CORD / CABLE MOUNT SJ CORD WITH 1/16 SS CABLE</p> <p>ORDER: CD (Length) SPECIFY LENGTH: CD36 - 36" CD72 - 72" CD144 - 144" CDLC(XX) Custom Length (Specify in Inches)</p>	<p>SM SURFACE MOUNT</p> <p>ORDER: SM (Flush to Ceiling)</p>
<p>*MAXIMUM ONE PIECE STEM LENGTH IS 72". **MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS.</p>					

REMOTE EMERGENCY BATTERY OPTIONS

<p>EMRM* - 7W REMOTE EMERGENCY BATTERY (50" MAX)</p> <table border="1"> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> <tr> <td>1.3</td> <td>12.6</td> <td>13.0</td> </tr> </table>	A	B	C	1.3	12.6	13.0	<p>EMEN* - 7W REMOTE EMERGENCY BATTERY WITH ENCLOSURE (50" MAX)</p> <table border="1"> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> <tr> <td>2.0</td> <td>17.0</td> <td>6.2</td> </tr> </table>	A	B	C	2.0	17.0	6.2
A	B	C											
1.3	12.6	13.0											
A	B	C											
2.0	17.0	6.2											
<p>*BOTH EMRM AND EMEN OPTIONS COME STANDARD WITH RDC5C SMALL DRIVER CANOPY</p> <p>OTHER EM BATTERY SIZES AVAILABLE, CONSULT FACTORY</p>													

