



WAREHOUSE SHADE
DAMP / WET LOCATION
CLASSIC SHAPES

PROJECT: _____
QUANTITY: _____ TYPE: _____



WS1611GV
MW - Matte White



WS1611GV
AY - Aero Yellow



WS1611GV
BZ - Bronze



WS1611GV
RD - Red Baron

| SERIES | LUMENS ¹ | CCT | DRIVER / DIMMING ² | ACCESSORIES ⁶ | MOUNTING ⁹ | INTERIOR ¹³ | FINISH ¹³ | WET KIT |
|---|--|--|--|--|--|---|--|------------------------------|
| WS1210GV WS1410GV WS1611GV WS1812GV WS2015GV | 15L 1500 Lm 27L 2700 Lm 37L 3700 Lm 55L 5500 Lm | 80 CRI 27K 2700K 30K 3000K 35K 3500K 40K 4000K 90 CRI 27HK 2700K 30HK 3000K 35HK 3500K 40HK 4000K | EX³ Electronic Driver, 120V/277V DO10X 1%, 0-10V, 120V/277V DS2W1⁴ ELV/MLV, 120V DLTE1⁵ Lutron® 2-Wire Forward Phase (MLV), 120V DL3EX⁶ 1%, Lutron® EcoSystem®, Fades to Black, 120V/277V | ENCLOSURES TF2⁷ 4" Frosted Dome TG2 4" Dome Wire Guard MF2 4" Frosted Mini MG2 4" Short Wire Guard FJ2 4" Frosted Tall FG2 4" Tall Wire Guard FIXTURE WIRE GUARDS⁸ See 2 nd Page for Ordering Details | WALL MOUNT CP104 Small Driver Canopy CP104KO Small Driver Canopy w/ Knockouts CP106 Large Driver Canopy CP6/RMD Remote Mount Driver SP90_19 Straight Arm PA_19 Mounting Arm Style CEILING MOUNT RDC5 Small Driver Canopy CP13 Large Driver Canopy HM_11 Hang Straight AT_11 Hang Straight All Thread PM_11 Rigid Pendant Mount CD_11 Cord / Cable Mount CD72 72" Cord / Cable Mount CM_11 Cord Mount EMCR¹⁰ 10W Large Driver Canopy EM EMRM 7W Remote EM EMEN 7W Remote with Enclosure | MW1¹⁴ Matte White CCI Custom Color FCI Fixture Color Interior | MW¹⁵ Matte White MB¹⁵ Matte Black PT¹⁵ Platinum Silver CC Custom Color | WLKA Wet Location Kit |

QUICK SHIP

EXAMPLE: WS1210GV37L30KEXTF2/CP104PA23MWIRD

NOTES:

1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 37L Max with CP104 4 37L Max with CP104/RDC5, 55L Max with CP106/CP13
 5 Available with CP106/CP13 Only 6 Enclosure, Wire Guard - Choose One Option 7 Standard Enclosure 8 Wire Guard Requires TF2 Enclosure
 9 See Mounting Page for Details on Components and Finishes 10 See Mounting Page for Available Arm Options 11 Specify Length in Inches:
 See Mounting Page for Available Lengths 12 EMCR Replaces RDC5 or CP13 13 Reference Color Sheet Located on Product Webpage for Full List of Available Colors 14 Standard Finishes






WAREHOUSE SHADE
DAMP / WET LOCATION
 CLASSIC SHAPES

| LUMENS / WATTAGE DATA | | | | |
|-----------------------|----------------------------|-------------------------------|--------------|-----|
| PART NUMBER | SOURCE LUMENS ¹ | DELIVERED LUMENS ² | SYSTEM WATTS | LPW |
| WS1611GV15L | 1500 | 1166 | 10 | 117 |
| WS1611GV27L | 2700 | 2038 | 18 | 113 |
| WS1611GV37L | 3700 | 2988 | 26 | 115 |
| WS1611GV55L | 5500 | 4401 | 39 | 113 |

¹ Nominal Source Lumens at 35K ² Nominal Delivered Lumens at 35K

HOUSING DIMENSIONS



Dimensioned with **WS1611GV**

| SERIES | A | B |
|----------|-------|-------|
| WS1210GV | 12.50 | 9.87 |
| WS1410GV | 14.50 | 11.68 |
| WS1611GV | 16.50 | 12.18 |
| WS1812GV | 18.50 | 12.68 |
| WS2015GV | 20.00 | 13.19 |

QUICK SHIP

Quick Ship Surface highlights products that can ship in 5 - 10 working days.

APPLICATIONS

The Warehouse Shade is one of our most popular RLM styles.

FEATURES

Spectrum Lighting's RLM Classics are inspired by vintage lighting fixtures redesigned with modern LED light sources and materials. The wide range of options for illumination, mounting, enclosures, guards and finishes allows for creative fixture specification and design. LED module and driver are serviceable for future replacement. Available in five sizes.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. Variety of standard and custom finishes are available. Interior is Matte White unless specified. Custom Color interior finishes available.

ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 80+. Higher CRI, R9 and custom LED configurations are available; consult factory. Choice of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Fixture shades are spun in our factory from 0.063 high purity aluminum. Wall mount canopies are die-cast aluminum with stainless steel hardware. Wall arms are formed 3/4 NPT aluminum pipe and may be field cut.

CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Wet Location Option. Manufactured and tested to UL standards No. 1598/8750.

SERIES SIZES

WS1210GV



WS1410GV



WS1611GV



WS1812GV



WS2015GV



ENCLOSURES

TF2
4" FROSTED DOME



MF2
4" FROSTED MINI



FJ2
4" FROSTED TALL



TG2
4" FROSTED DOME
WIRE GUARD - FITS TF2



MG2
4" FROSTED MINI
WIRE GUARD - FITS MF2



FG2
4" FROSTED TALL
WIRE GUARD - FITS FJ2



FIXTURE WIRE GUARDS

WG12 - 12" Ø

WG14 - 14" Ø

WG16 - 16" Ø

WG18 - 18" Ø



WS1611GV SHOWN WITH WG16

WALL MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & DIMENSIONS.)

PA_
MOUNTING ARM STYLE



WS1611GV SHOWN WITH CP104PA23

CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

HM / AT / PM
HANG STRAIGHT / ALL THREAD / PENDANT



WS1611GV SHOWN WITH RDC5PM

CD
CORD / CABLE MOUNT



WS1611GV SHOWN WITH RDC5CD

CM
CORD MOUNT



WS1611GV SHOWN WITH RDC5CM



WAREHOUSE SHADE
DAMP / WET LOCATION
 CLASSIC SHAPES / PHOTOMETRIC DATA

WS1611GV-55L-35K-EX-TF2-MWI

| CANDLEPOWER CURVE | INTENSITY | ZONAL LUMENS | | SINGLE UNIT: PERFORMANCE INITIAL FOOTCANDLES BASED ON IES BEAM ANGLE | | | | MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT | | | | | | | | | | | | | | | | |
|---------------------------|-----------|--------------------|----------|--|-----------------------|---------------|-----------------|--|-----------------|---|-----|----------------------|------|---------------------|------|--|--|--|--|--|--|--|--|--|
| | | | | Mounting Height AFF | FC at Center on Floor | Beam Diameter | FC at Beam Edge | Ceiling Height | Fixture Spacing | RCR 1 | | RCR 3 | | | | | | | | | | | | |
| | 0.00° | | | | | | | | | | | | | | | | | | | | | | | |
| | 0.00° | 1,739 | 0° - 10° | 174 | 4% | 8.0' | 27 fc | 23.2' | 8 fc | 17' | 16' | 17 | 0.14 | 10 | 0.11 | | | | | | | | | |
| | 5.00° | 1,730 | 0° - 20° | 635 | 14% | 10.0' | 17 fc | 29.0' | 5 fc | 21' | 18' | 15 | 0.13 | 12 | 0.13 | | | | | | | | | |
| | 10.00° | 1,700 | 0° - 30° | 1,323 | 30% | 12.0' | 12 fc | 34.7' | 4 fc | 25' | 20' | 12 | 0.10 | 8 | 0.08 | | | | | | | | | |
| | 15.00° | 1,648 | 0° - 40° | 2,145 | 49% | 14.0' | 9 fc | 40.5' | 3 fc | Delivered Illuminance Rating: (DIR) | | 116 FC per W/Sq. Ft. | | 91 FC per W/Sq. Ft. | | | | | | | | | | |
| | 20.00° | 1,579 | 0° - 60° | 3,781 | 86% | 16.0' | 7 fc | 46.3' | 2 fc | 3' Suspension Length Square rooms used for multiple units: - RCR 1: Length & Width = Ceiling Ht. - 5.5' x 10.00 - RCR 3: Length & Width = Ceiling Ht. - 5.5' x 3.33 * Average Footcandles at 2.5' Above Floor ** Exceeds spacing criteria by 16% *** Exceeds spacing criteria by -3% **** Exceeds spacing criteria by -15% | | | | | | | | | | | | | | |
| | 30.00° | 1,407 | 0° - 80° | 4,362 | 99% | 20.0' | 4 fc | 57.9' | 1 fc | | | | | | | | | | | | | | | |
| | 40.00° | 1,219 | 0° - 90° | 4,394 | 100% | 24.0' | 3 fc | 69.5' | 1 fc | | | | | | | | | | | | | | | |
| | 50.00° | 1,010 | Total | 4,394 | 100% | 28.0' | 2 fc | 81.1' | 1 fc | | | | | | | | | | | | | | | |
| | 60.00° | 688 | | | | | | | | | | | | | | | | | | | | | | |
| | 70.00° | 216 | | | | | | | | | | | | | | | | | | | | | | |
| | 80.00° | 54 | | | | | | | | | | | | | | | | | | | | | | |
| | 90.00° | 0 | | | | | | | | | | | | | | | | | | | | | | |
| CP at 0deg (Nadir): 1,739 | | Beam Angle: 110.62 | | Lamp Multiplier: 15L x 0.265, 27L x 0.463, 37L x 0.679 | | | | CCT Multiplier: 27K x 0.971, 30K x 0.985, 40K x 1.03 | | | | | | | | | | | | | | | | |
| CRI: 85+ | | Spacing Ratio: 1.2 | | | | | | | | | | | | | | | | | | | | | | |

Delivered Lumens: 4,394
 Luminaire Watts: 39
 LER: 112.67




MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION. NOTE: THIS IS TYPICAL OF RLM SPECIFICATION FOR MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.




WALL MOUNTING

CP104 - SMALL DRIVER CANOPY (STANDARD)
MAY BE USED AS SPLICE BOX FOR DIRECT FEED
NOT AVAILABLE W/ PA16 & PA16F




CP106 - LARGE DRIVER CANOPY
MAY BE USED AS SPLICE BOX FOR DIRECT FEED



CP6/RMD - REMOTE MOUNT DRIVER
MOUNTS DIRECTLY TO WALL OR OCTAGON STYLE J-BOX




CUSTOM AND OTHER WALL ARMS AVAILABLE - CONTACT FACTORY. ARMS MAY BE FIELD CUT ON WALL SIDE - FIXTURE SIDE THREADED 3/4" NPT REQUIRES SEALANT FOR WET LOCATION.




CEILING MOUNTING


RDC5 - SMALL DRIVER CANOPY (STANDARD)
MOUNTS TO 4" OCTO J-BOX



CP13 - LARGE DRIVER CANOPY




HM*
HANG STRAIGHT
45° SWIVEL 5/8" OD STEM - 3/8" IP




ORDER: HM (Length)
SPECIFY LENGTH:
HM3 - 3" HM24 - 24"
HM6 - 6" HM36 - 36"
HM12 - 12" HM48 - 48"
HM18 - 18" HM72 - 72"
HMLC(XX)
Custom Length
(Specify in Inches)

PM*
RIGID PENDANT MOUNT
RIGID 5/8" OD STEM - 3/8" IP




ORDER: PM (Length)
SPECIFY LENGTH:
PM3 - 3" PM24 - 24"
PM6 - 6" PM36 - 36"
PM12 - 12" PM48 - 48"
PM18 - 18" PM72 - 72"
PMLC(XX)
Custom Length
(Specify in Inches)

AT**
HANG STRAIGHT ALL THREAD
45° SWIVEL 5/8" OD STEM - 1/4" IP



ORDER: AT (Length)
SPECIFY LENGTH:
AT12 - 12" AT48 - 48"
AT24 - 24" AT60 - 60"
AT36 - 36" AT72 - 72"
FIELD CUT - THREADED PIPE
TO LENGTH - THREADED
CUT PIPE COVER 3/4" SHORTER
DRAIN THREADED PIPE
SLIP PIPE COVER OVER THREADED PIPE

CD
CORD / CABLE MOUNT
SJ CORD WITH 1/16 SS CABLE



ORDER: CD (Length)
SPECIFY LENGTH:
CD36 - 36"
CD72 - 72"
CD144 - 144"
CDLC(XX)
Custom Length
(Specify in Inches)

CM
CORD MOUNT
SJ CORD WITH STRAIN RELIEF




ORDER: CM (Length)
SPECIFY LENGTH:
CM36 - 36"
CM72 - 72"
CM144 - 144"
CMLC(XX)
Custom Length
(Specify in Inches)

*MAXIMUM ONE PIECE STEM LENGTH IS 72". **MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS.
**ORDER IN 12" INCREMENTS, ODD SIZES MAY BE FIELD CUT


EMERGENCY BATTERY OPTIONS

EMCR - LARGE DRIVER CANOPY FOR 10W EMERGENCY BATTERY




REMOTE EMERGENCY BATTERY OPTIONS

EMRM* - 7W REMOTE EMERGENCY BATTERY (50' MAX)



EMEN* - 7W REMOTE EMERGENCY BATTERY WITH ENCLOSURE (50' MAX)



*OTHER EM BATTERY SIZES AVAILABLE. CONTACT FACTORY.

