
# **6" ROUND OPEN REFLECTOR**







С

6.0

152.4 mm

D

16.0

406.4 mm

187.3 mm 25.4 mm

Fixture Weight: 4.0 lbs

В

1.0

Α

304.8 mm Ceiling Cutout: Ø 6.2

12.0

# SG6IN

## APPLICATION

6" aperture series with deep cutoff for A and PAR LED lamps.

#### **FEATURES**

Efficient reflector design optimized for A, PAR, and R LED lamps (Sold by others). Posi-lock reflector attachment. Integral 5/8" (0.625") plaster ring. Tool-less access for ease of maintenance. Multi-bar adjustable mounting brackets.

#### **TRIM FINISH**

Variety of powdercoat and anodized finishes available on trim.

### LAMPING

Accepts E21 medium base A lamps and PAR20/30/38 lamps.

#### CONSTRUCTION

Frame constructed of 20 ga. galvanized steel. Reflectors spun from .063" high purity aluminum and finished to specification.

### **CODE COMPLIANCE**

ETL listed for damp locations. Manufactured and tested to UL Standard No. 1598.

# **PRODUCT SELECTOR GUIDE**



HOUSING	MOUNTING OPTIONS	TRIM OPTIONS
SERIES	BAR HANGERS	TRIM FINISH FLANGE FINISH
SGGIN	BH27 27" Solid Bars H12 12" - 24" Expandable Bars	AR6415 SG Semi-Diffuse Low Iridescent MW Matte White MB Matte Black MF Matte Slack MATTER MATTER MA



