



**ALUMINUM REFLECTOR
PENDANT
DAMP LOCATION
XT SERIES**

PROJECT: _____

QUANTITY: _____ TYPE: _____



RPEXT1014XT
RD - Red Baron
ALI - Almond Interior



RPEXT1014XT
PL - Purple
ORI - Orange Interior



RPEXT1014XT
BR - Brecchia
SNI - Sun Gold Interior



RPEXT1014XT
VE - Verde Green
SFI - Sea Foam Interior

SERIES	LUMENS ¹	CCT	DRIVER / DIMMING ²	MOUNTING ³	INTERIOR ⁵	FINISH ⁵		
RPEXT1014XT RPEXT1214XT	83 CRI		EX Electronic Driver, 120V/277V DO10X 1%, 0-10V, 120V/277V DS2W1 ELV/MLV, 120V DLTE1 Lutron® 2-Wire Forward Phase (MLV), 120V DL3EX 1%, Lutron® EcoSystem®, 120V/277V	HM ⁴ Hang Straight AT ⁴ Hang Straight All Thread PM ⁴ Rigid Pendant Mount CD ⁴ Cord / Cable Mount CM ⁴ Cord Mount EMRM 7W Remote EM EMEN 7W Remote with Enclosure	MWI ⁶ Matte White CCI Custom Color FCI Fixture Color Interior	MW ⁶ Matte White MB ⁶ Matte Black PT ⁶ Platinum Silver CC Custom Color		
	10L	1000 Lm					27K	2700K
	13L	1300 Lm					30K	3000K
	20L	2000 Lm					35K	3500K
	30L	3000 Lm					40K	4000K
	40L	4000 Lm						
	98 CRI							
	10L	1000 Lm					27HK	2700K
	13L	1300 Lm					30HK	3000K
	20L	2000 Lm					35HK	3500K
30L	3000 Lm	40HK	4000K					

EXAMPLE: RPEXT1014LEDXT30L30KEX/CD36MB

NOTES:
 1 Nominal Source Lumens at Any CCT 2 Contact Factory for Additional Options 3 See Mounting Page for Details on Components and Finishes 4 Specify Length in Inches:
 See Mounting Page for Available Lengths 5 Reference Color Sheet Located on Product Webpage for Full List of Available Colors/Consult Factory for Special Finishes
 6 Standard Finishes






ALUMINUM REFLECTOR PENDANT DAMP LOCATION XT SERIES

LUMENS / WATTAGE DATA		
PART NUMBER	SOURCE LUMENS ¹	SYSTEM WATTS
RPEXT1014XT10L	1000	8
RPEXT1014XT13L	1300	12
RPEXT1014XT20L	2000	20
RPEXT1014XT30L	3000	30
RPEXT1014XT40L	4000	40

¹Nominal Source Lumens at Any CCT

HOUSING DIMENSIONS



Dimensioned with **RPEXT1014XT**

SERIES	A	B
RPEXT1014XT	11.7	20.8
RPEXT1214XT	14.0	22.3

APPLICATION

The Aluminum Reflector Pendant's distinctive styling will enhance any space with efficient lighting and striking design.

FEATURES

Speculume series fixtures offer simple contemporary style with functional luminaire performance. All fixtures are designed and manufactured in our factory. Reflector pendant is available in three sizes for direct downlighting. Separate finishes may be chosen for fixture and mounting. A variety of mounting and finish options available.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. A wide variety of standard and custom finishes are available. All exposed materials are chromate pretreated to resist corrosion. Matte white interior is standard.

ELECTRONICS

LED system features Xicato LED module with proprietary phosphor technology that provides consistent stable color with CCT control of +/- 100K over life of the light engine. Base CRI is 83 with 1 x 2-step MacAdam Ellipse binning. High CRI is 98 with 1 x 2-step MacAdam Ellipse binning. Variety of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Fixtures are spun and fabricated in our factory from high purity aluminum. Fixture top is machined extruded aluminum. OSD diffusion optic lens standard.

CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750

SERIES SIZES

RPEXT1014XT



RPEXT1214XT



CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

HM / AT / PM

HANG STRAIGHT / ALL THREAD / PENDANT



RPEXT1014XT SHOWN WITH PM

CD

CORD / CABLE MOUNT



RPEXT1014XT SHOWN WITH CD

CM

CORD MOUNT



RPEXT1014XT SHOWN WITH CM



MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION. NOTE: THIS IS TYPICAL OF SPECULUME SPECIFICATION FOR PENDANT MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.



CEILING MOUNTING

<p>RDC5 - SMALL DRIVER CANOPY (STANDARD) MOUNTS TO 4" OCTO J-BOX</p> <p>CP13 - LARGE DRIVER CANOPY</p>	<p>HM* HANG STRAIGHT 45° SWIVEL 1/2" STEM - 3/8" NPT</p> <p>ORDER: HM (Length) SPECIFY LENGTH: HM3 - 3" HM24 - 24" HM6 - 6" HM36 - 36" HM12 - 12" HM48 - 48" HM18 - 18" HM72 - 72" HMLC(XX) Custom Length (Specify in Inches)</p>	<p>AT** HANG STRAIGHT ALL THREAD 45° SWIVEL 1/2" STEM - 1/4" IP</p> <p>ORDER: AT (Length) SPECIFY LENGTH: AT12 - 12" AT48 - 48" AT24 - 24" AT60 - 60" AT36 - 36" AT72 - 72" <small>FIELD-CUT THREADED PIPE TO LENGTH REQUIRED CUT PIPE COVER 1/4" SHORTER THAN THREADED PIPE SLIP PIPE COVER OVER THREADED PIPE</small></p>	<p>PM* RIGID PENDANT MOUNT RIGID 1/2" STEM - 3/8" NPT</p> <p>ORDER: PM (Length) SPECIFY LENGTH: PM3 - 3" PM24 - 24" PM6 - 6" PM36 - 36" PM12 - 12" PM48 - 48" PM18 - 18" PM72 - 72" PMLLC(XX) Custom Length (Specify in Inches)</p>	<p>CD CORD / CABLE MOUNT SJ CORD WITH 1/16 SS CABLE</p> <p>ORDER: CD (Length) SPECIFY LENGTH: CD36 - 36" CD72 - 72" CD144 - 144" CDLC(XX) Custom Length (Specify in Inches)</p>	<p>CM CORD MOUNT SJ CORD WITH STRAIN RELIEF</p> <p>ORDER: CM (Length) SPECIFY LENGTH: CM36 - 36" CM72 - 72" CM144 - 144" CMLC(XX) Custom Length (Specify in Inches)</p>
--	--	--	--	--	--

*MAXIMUM ONE PIECE STEM LENGTH IS 72". **MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS. **ORDER IN 12" INCREMENTS. ODD SIZES MAY BE FIELD CUT

EMERGENCY BATTERY OPTIONS

EMCR - LARGE DRIVER CANOPY FOR 10W EMERGENCY BATTERY (FOR ROUND CEILING MOUNT TYPES)

REMOTE EMERGENCY BATTERY OPTIONS

<p>EMRM* - 7W REMOTE EMERGENCY BATTERY (50' MAX)</p> <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>1.3</td> <td>12.6</td> <td>13.0</td> </tr> </tbody> </table>	A	B	C	1.3	12.6	13.0	<p>EMEN* - 7W REMOTE EMERGENCY BATTERY WITH ENCLOSURE (50' MAX)</p> <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>2.0</td> <td>17.0</td> <td>6.2</td> </tr> </tbody> </table>	A	B	C	2.0	17.0	6.2
A	B	C											
1.3	12.6	13.0											
A	B	C											
2.0	17.0	6.2											

*OTHER EM BATTERY SIZES AVAILABLE. CONSULT FACTORY

