



APRIO
INCANDESCENT
 CAFÉS

PROJECT: _____
 QUANTITY: _____ TYPE: _____



AC1007INC - INTERIOR ONLY / DAMP LOCATION

APPLICATION

Cafe series offers a playful variety of fixture shapes. INC Series is designed for covered or indoor dry/damp locations.

FEATURES

Spectrum Lighting's RLM Series are interpretations of classic lighting fixtures reimagined with modern INC light sources and materials. The wide range of options for illumination, mounting and finishes allows for creative fixture specification and design.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. Variety of standard and custom finishes are available. Interior is Matte White unless specified.

ELECTRONICS


E26 Edison medium base 120V socket for incandescent or LED lamps.

CONSTRUCTION

Fixture shades are spun in our factory from 0.063 high purity aluminum. Wall mount canopies are die-cast aluminum with stainless steel hardware. Wall arms are formed 3/4 NPT aluminum pipe.

CODE COMPLIANCE

BAA Compliant. ETL listed for dry/damp locations. Manufactured and tested to UL standards No. 1598/8750.



A	B
10.0	7.6
254.0 mm	183.04 mm

SERIES	MOUNTING ¹	INTERIOR FINISH ⁴	EXTERIOR FINISH ⁴
AC1007INC	WALL MOUNT		MW⁵ Matte White MB⁵ Matte Black FCI Fixture Color Interior CCI Custom Color
	CP6¹	Wall Pipe Interface	
	CP3	CP6 Decorative Cover	
	PA²	Mounting Arm Style	
	SP90²	Straight Arm	
	CEILING MOUNT		
	HM³	Hang Straight Pendant	
	AT³	Hang Straight All Thread	
	PM³	Pendant/Straight Mount	
	HC³	Hook/Cord	
CD³	Cord and Cable Mount		
CM³	Cord Mount		
CHN³	Chain Mount		
		MW⁵ Matte White MB⁵ Matte Black PT⁵ Platinum Silver CC Custom Color	

EXAMPLE: AC1007INC/CD96/MWIBZ

NOTES:
 1 See Mounting Pages Options and Details on Components and Finishes 2 See Mounting Page for Available Arm Options
 3 Specify Length in Inches: See Mounting Page for Available Lengths 4 Reference Color Sheet Located on Product Webpage for Full List of Available Colors/Consult Factory for Special Finishes 5 Standard Finish



MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.
NOTE: THIS IS TYPICAL OF RLM SPECIFICATION FOR MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.



WALL MOUNTING

CP6 - MOUNTS DIRECTLY TO WALL OR OCTAGON STYLE J-BOX

CUSTOM AND OTHER WALL ARMS AVAILABLE - CONTACT FACTORY. ARMS MAY BE FIELD CUT ON WALL SIDE - FIXTURE SIDE THREADED 3/4" NPT REQUIRES SEALANT FOR WET LOCATION.

<p>PA15 15.0 9.8 8.3</p> <p>PA17 17.0 7.0</p> <p>PA22 22.0 7.5 12.5</p> <p>PA23 23.0 7.0</p> <p>PA23(xx) SPECIFY LENGTH 7.0 EXAMPLE: PA2330 - 30" PA23</p>	<p>PA24 15.0 18.0 9.5 24.0</p> <p>PA26 28.5 12.7</p> <p>SP9012 FIELD CUTTABLE 12</p> <p>SP9024 FIELD CUTTABLE 24</p> <p>PA90 (Wxx)(Dxx) SPECIFY LENGTH (Wxx) SPECIFY DROP (6.5 Minimum) (Dxx) EXAMPLE: PA90W20D07 - 90° PIPE 20 LONG 7" DEEP THREADED AT FIXTURE END</p>	<p>PA32 32.6 19.5 30.0 10.5 32.2</p> <p>PA36 36.0 7.0</p> <p>PA48 48.0 7.0</p>	<p>PA16 - Front Wall Mount 15.0 25.0 13.0</p> <p>PA16F - Back Wall Mount 20.0 25.0 13.0</p> <p>PA901212 12.0 12.0</p>
---	---	---	--

CEILING MOUNTING

<p>HM* HANG STRAIGHT 45° SWIVEL 5/8" OD STEM - 3/8" IP</p> <p>ORDER: HM (Length) SPECIFY LENGTH: HM3 - 3" HM24 - 24" HM6 - 6" HM36 - 36" HM12 - 12" HM48 - 48" HM18 - 18" HM72 - 72" HMLC(XX) Custom Length (Specify in Inches)</p>	<p>PM* RIGID PENDANT MOUNT RIGID 5/8" OD STEM - 3/8" IP</p> <p>ORDER: PM (Length) SPECIFY LENGTH: PM3 - 3" PM24 - 24" PM6 - 6" PM36 - 36" PM12 - 12" PM48 - 48" PM18 - 18" PM72 - 72" PMLC(XX) Custom Length (Specify in Inches)</p>	<p>AT** HANG STRAIGHT ALL THREAD 45° SWIVEL 5/8" OD STEM - 1/4" IP</p> <p>ORDER: AT (Length) SPECIFY LENGTH: AT12 - 12" AT48 - 48" AT24 - 24" AT60 - 60" AT36 - 36" AT72 - 72" FIELD CUT THREADED PIPE TO LENGTH REQUIRED OD PIPE LOOSE 3/4" SHORTER THAN THREADED PIPE 1/4" PIPE COVER OVER THREADED PIPE</p>	<p>HC HOOK & CORD FOR INDEPENDENT MOUNTING</p> <p>ORDER: HC (Length) SPECIFY LENGTH: HC36 - 36" HC72 - 72" HC144 - 144" HCLC(XX) Custom Length (Specify in Inches) PLUG LP120 - 120V Twist Lock LP277 - 277V Twist Lock</p>	<p>CD CORD / CABLE MOUNT SJ CORD WITH 1/16 SS CABLE</p> <p>ORDER: CD (Length) SPECIFY LENGTH: CD36 - 36" CD72 - 72" CD144 - 144" CDLC(XX) Custom Length (Specify in Inches)</p>	<p>CM CORD MOUNT SJ CORD WITH STRAIN RELIEF</p> <p>ORDER: CM (Length) SPECIFY LENGTH: CM36 - 36" CM72 - 72" CM144 - 144" CMLC(XX) Custom Length (Specify in Inches)</p>	<p>CHN CHAIN MOUNT SJ CORD / DECORATIVE CHAIN</p> <p>ORDER: CHN (Length) SPECIFY LENGTH: CHN36 - 36" CHN72 - 72" CHN144 - 144" CHNLC(XX) Custom Length (Specify in Inches)</p>
--	---	---	--	--	--	---

*MAXIMUM ONE PIECE STEM LENGTH IS 72". **MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS.
**ORDER IN 12" INCREMENTS, ODD SIZES MAY BE FIELD CUT

