



**HIGH TOP PENDANT**  
**DAMP LOCATION**  
 DOMO SHADES

PROJECT: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_ TYPE: \_\_\_\_\_



HT1813GV  
 SN - Sun Gold  
 GAI - Galvanized Interior



HT1813GV  
 MW - Matte White  
 MBI - Matte Black Interior



HT1813GV  
 MB - Matte Black  
 ALI - Almond Interior



HT1813GV  
 PT - Platinum Silver  
 BLI - Blue Streak Interior

SERIES	LUMENS <sup>1</sup>	CCT	DRIVER / DIMMING <sup>2</sup>	MOUNTING <sup>6</sup>	CORD OPTIONS	INTERIOR <sup>10</sup>	FINISH <sup>10</sup>		
HT1813GV	15L	1500 Lm	27K	2700K	<b>EX<sup>3</sup></b> Electronic Driver, 120V/277V <b>DO10X<sup>3</sup></b> 1%, 0-10V, 120V/277V <b>DS2W1<sup>4</sup></b> ELV / MLV,120V <b>DLTE1<sup>5</sup></b> Lutron® 2-Wire Forward Phase (MLV), 120V <b>DL3EX<sup>5</sup></b> 1%, Lutron® EcoSystem®, Fades to Black, 120V/277V	<b>RDC5<sup>3/4</sup></b> Small Driver Canopy <b>CP13<sup>4/5</sup></b> Wire Bail / Cord <b>HM_<sup>7</sup></b> Hang Straight <b>AT_<sup>7</sup></b> Hang Straight All Thread <b>PM_<sup>7</sup></b> Rigid Pendant Mount <b>CD_<sup>7</sup></b> Cord / Cable Mount <b>CM_<sup>7</sup></b> Cord Mount <b>CHN_<sup>7</sup></b> Chain / Cord <b>EMCR<sup>8</sup></b> 10W Canopy Mounted EM <b>EMRM</b> 7W Remote EM <b>EMEN</b> 7W Remote with Enclosure	STANDARD CORDS	<b>MWI<sup>11</sup></b> Matte White <b>CCI</b> Custom Color <b>FCI</b> Fixture Color Interior	<b>MW<sup>11</sup></b> Matte White <b>MB<sup>11</sup></b> Matte Black <b>PT<sup>11</sup></b> Platinum Silver <b>CC</b> Custom Color
	27L	2700 Lm	30K	3000K			<b>CW</b> White <b>CB</b> Black <b>CS</b> Silver		
	37L	3700 Lm	35K	3500K			DECORATIVE CORDS <sup>9</sup> See Page 4 for Decorative Braided Color Cords		
	55L	5500 Lm	40K	4000K					

EXAMPLE: HT1813GV15L35KEX/RDC5HM36PT

**NOTES:**  
 1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 RDC5 for EX/DO10X Drivers 4 37L Max with RDC5, 55L Max with CP13 5 CP13 for Lutron Drivers  
 6 See Mounting Page for Details on Components and Finishes 7 Specify Length in Inches: See Mounting Page for Available Lengths 8 EMCR Replaces RDC5 or CP13  
 9 Decorative Cord 120" Max Length 10 Reference Color Sheet Located on Product Webpage for Full List of Available Colors 11 Standard Finishes





DECORATIVE

# HIGH TOP PENDANT


## DAMP LOCATION

### DOMO SHADES

LUMENS / WATTAGE DATA				
PART NUMBER	SOURCE LUMENS <sup>1</sup>	DELIVERED LUMENS <sup>2</sup>	SYSTEM WATTS	LPW
HT1813GV15L	1500	1195	10	120
HT1813GV27L	2700	2158	18	120
HT1813GV37L	3700	3160	26	122
HT1813GV55L	5500	4625	39	119

<sup>1</sup> Nominal Source Lumens at 35K    <sup>2</sup> Nominal Delivered Lumens at 35K

## HOUSING DIMENSIONS



A	B
18.1	13.9
459.7 mm	353.1 mm

### APPLICATION

The High Top Pendant for wide area lighting.

### FEATURES

SpecLume series fixtures offer contemporary style with functional luminaire performance. Passive integral heat sink. LED module and drivers are replaceable and upgradable. Standard diffuser for visual comfort and to eliminate LED source visibility. A variety of mounting options are available.

### FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. See mounting and color pages for standard finishes. Interior is Matte White unless specified. Custom Color interior finish available.

### ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 80+. Higher CRI, R9 and custom LED configurations are available; consult factory. Variety of electronic 120V/277V and dimming drivers.

### CONSTRUCTION

Fixtures constructed of machined and formed aluminum and door with lens option available. Carbon gasket for optimal thermal management.

### CODE COMPLIANCE


BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.

## CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

### HM / AT / PM

HANG STRAIGHT / ALL THREAD / PENDANT



HT1813GV SHOWN WITH RDC5PM

### CD


CORD / CABLE MOUNT



HT1813GV SHOWN WITH RDC5CD

### CM

CORD MOUNT



HT1813GV SHOWN WITH RDC5CM

### CHN

CHAIN MOUNT



HT1813GV SHOWN WITH CHN





# EXPRESS PENDANT

## DAMP LOCATION

### DOMO SHADES / PHOTOMETRIC DATA

DECORATIVE

TT1811GV-55L-35K-EX-MWI-PT-TF2

CANDLEPOWER CURVE	INTENSITY	ZONAL LUMENS	SINGLE UNIT: PERFORMANCE INITIAL FOOTCANDLES BASED ON IES BEAM ANGLE				MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT												
			Mounting Height AFF	FC at Center on Floor	Beam Diameter	FC at Beam Edge	Ceiling Height	Fixture Spacing	RCR 2		RCR 4								
	0.00°																		
	0.00°	1,710	0° - 10°	164	4%														
	5.00°	1,699	0° - 20°	630	16%														
	10.00°	1,678	0° - 30°	1,338	33%														
	15.00°	1,655	0° - 40°	2,184	54%														
	20.00°	1,616	0° - 60°	3,704	91%														
	30.00°	1,452	0° - 80°	4,028	99%														
	40.00°	1,266	0° - 90°	4,052	100%														
	50.00°	1,040	Total	4,052	100%														
	60.00°	385																	
	70.00°	142																	
	80.00°	63																	
	90.00°	0																	
Delivered Lumens: 4,052 Luminaire Watts: 39 LER: 103.90	CP at 0deg (Nadir): 1,710 CRI: 85+	Beam Angle: 106.26 Spacing Ratio: 1.25	Lamp Multiplier: 15L x 0.265, 27L x 0.463, 37L x 0.68 CCT Multiplier: 27K x 0.971, 30K x 0.985, 40K x 1.03	2' Suspension Length Square rooms used for multiple units: - RCR 2: Length & Width = Ceiling Ht. - 4.5' x 5.00 - RCR 4: Length & Width = Ceiling Ht. - 4.5' x 2.50 * Average Footcandles at 2.5' Above Floor * Exceeds spacing criteria by 1% ** Exceeds spacing criteria by -17% *** Exceeds spacing criteria by -27%															



# MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION. NOTE: THIS IS TYPICAL OF SPECULUME SPECIFICATION FOR PENDANT MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.



## CEILING MOUNTING

<p><b>RDC5</b> - SMALL DRIVER CANOPY (STANDARD) MOUNTS TO 4" OCTO J-BOX</p> <p><b>CP13</b> - LARGE DRIVER CANOPY</p>	<p><b>HM*</b> HANG STRAIGHT 45° SWIVEL 1/2" STEM - 3/8" NPT</p> <p>ORDER: <b>HM</b> (Length) SPECIFY LENGTH: HM3 - 3"    HM24 - 24" HM6 - 6"    HM36 - 36" HM12 - 12"    HM48 - 48" HM18 - 18"    HM72 - 72" <b>HMLC(XX)</b> Custom Length (Specify in Inches)</p>	<p><b>AT**</b> HANG STRAIGHT ALL THREAD 45° SWIVEL 1/2" STEM - 1/4" IP</p> <p>ORDER: <b>AT</b> (Length) SPECIFY LENGTH: AT12 - 12"    AT48 - 48" AT24 - 24"    AT60 - 60" AT36 - 36"    AT72 - 72"</p> <p><small>FIELD CUT - THREADED PIPE TO LENGTH WISHED CUT PIPE COUPLER 1/4" SHORTER THAN THREADED PIPE SLIP "PIPE COVER" OVER THREADED PIPE</small></p>	<p><b>PM*</b> RIGID PENDANT MOUNT RIGID 1/2" STEM - 3/8" NPT</p> <p>ORDER: <b>PM</b> (Length) SPECIFY LENGTH: PM3 - 3"    PM24 - 24" PM6 - 6"    PM36 - 36" PM12 - 12"    PM48 - 48" PM18 - 18"    PM72 - 72" <b>PMLLC(XX)</b> Custom Length (Specify in Inches)</p>	<p><b>CD</b> CORD / CABLE MOUNT SJ CORD WITH 1/16 SS CABLE</p> <p>ORDER: <b>CD</b> (Length) SPECIFY LENGTH: CD36 - 36" CD72 - 72" CD144 - 144" <b>CDLC(XX)</b> Custom Length (Specify in Inches)</p>	<p><b>CM</b> CORD MOUNT SJ CORD WITH STRAIN RELIEF</p> <p>ORDER: <b>CM</b> (Length) SPECIFY LENGTH: CM36 - 36" CM72 - 72" CM144 - 144" <b>CMLC(XX)</b> Custom Length (Specify in Inches)</p>	<p><b>CHN</b> CHAIN MOUNT SJ CORD / DECORATIVE CHAIN</p> <p>ORDER: <b>CHN</b> (Length) SPECIFY LENGTH: CHN36 - 36" CHN72 - 72" CHN144 - 144" <b>CHNLC(XX)</b> Custom Length (Specify in Inches)</p>
--	--	---	--	--	--	---

\*MAXIMUM ONE PIECE STEM LENGTH IS 72". \*\*MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS. \*\*ORDER IN 12" INCREMENTS, ODD SIZES MAY BE FIELD CUT

## EMERGENCY BATTERY OPTIONS

**EMCR** - LARGE DRIVER CANOPY FOR 10W EMERGENCY BATTERY (FOR ROUND CEILING MOUNT TYPES)

## REMOTE EMERGENCY BATTERY OPTIONS

<p><b>EMRM*</b> - 7W REMOTE EMERGENCY BATTERY (50' MAX)</p> <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>1.3</td> <td>12.6</td> <td>13.0</td> </tr> </tbody> </table>	A	B	C	1.3	12.6	13.0	<p><b>EMEN*</b> - 7W REMOTE EMERGENCY BATTERY WITH ENCLOSURE (50' MAX)</p> <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>2.0</td> <td>17.0</td> <td>6.2</td> </tr> </tbody> </table>	A	B	C	2.0	17.0	6.2
A	B	C											
1.3	12.6	13.0											
A	B	C											
2.0	17.0	6.2											

\*OTHER EM BATTERY SIZES AVAILABLE, CONSULT FACTORY

## CORD OPTIONS

STANDARD VINYL CORDS

DECORATIVE BRAIDED COLOR CORDS

