



14" EXPRESS PENDANT
DAMP LOCATION
 DOMO SHADES

PROJECT: _____
 QUANTITY: _____ TYPE: _____



EP1414GV
 RD - Red Baron
 CHI - Charcoal Interior



EP1414GV
 BL - Blue Streak
 PTI - Platinum Silver Interior



EP1414GV
 MW - Matte White
 TQI - Turquoise Interior



EP1414GV
 PG - Pub Green
 GAI - Galvanized Interior

SERIES	LUMENS ¹	CCT	DRIVER / DIMMING ²	MOUNTING ⁶	CORD OPTIONS	DIFFUSER ¹⁰	INTERIOR ¹¹	FINISH ¹¹	
EP1414GV	15L	1500 Lm	27K	2700K	RDC5 ^{3/4} Small Driver Canopy CP13 ^{4/5} Large Driver Canopy HM ⁷ Hang Straight AT ⁷ Hang Straight All Thread PM ⁷ Rigid Pendant Mount CD ⁷ Cord / Cable Mount CM ⁷ Cord Mount EMCR ⁸ 10W Canopy Mounted EM EMRM 7W Remote EM EMEN 7W Remote with Enclosure	STANDARD CORDS CW White CB Black CS Silver DECORATIVE CORDS ⁹ See Page 4 for Decorative Braided Color Cords	ENCLOSURES TF2 4" Frosted Dome (Standard) DOORS & LENSES DR Door (See 2 nd Page for Ordering Details)	MW ¹² Matte White CC Custom Color FCI Fixture Color Interior	MW ¹² Matte White MB ¹² Matte Black PT ¹² Platinum Silver CC Custom Color
	27L	2700 Lm	30K	3000K					
	37L	3700 Lm	35K	3500K					
	55L	5500 Lm	40K	4000K					

EXAMPLE: EP1414GV15L30KEX/RDC5DR14BSOMWIMW

NOTES:
 1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 RDC5 for EX/DO10X Drivers 4 37L Max with RDC5, 55L Max with CP13 5 Available with CP13 Only
 6 See Mounting Page for Details on Components and Finishes 7 Specify Length in Inches: See Mounting Page for Available Lengths 8 EMCR Replaces RDC5 or CP13
 9 Decorative Cord 120" Max Length 10 TF2 Enclosure or Door & Lens Required - Choose One Option 11 Reference Color Sheet Located on Product Webpage for Full List of Available Colors 12 Standard Finishes





14" EXPRESS PENDANT


DAMP LOCATION

DOMO SHADES

LUMENS / WATTAGE DATA				
PART NUMBER	SOURCE LUMENS ¹	DELIVERED LUMENS ²	SYSTEM WATTS	LPW
EP1414GV15L	1500	904	10	90
EP1414GV27L	2700	1675	16	93
EP1414GV37L	3700	2317	33	89
EP1414GV55L	5500	3412	36	87

¹ Nominal Source Lumens at 35K ² Nominal Delivered Lumens at 35K

HOUSING DIMENSIONS



A	B
14.5 368.3 mm	14.6 370.8

APPLICATION

Express Pendant is a popular European styled fixture for decorative lighting.

FEATURES

SpecLume series fixtures offer contemporary style with functional luminaire performance. Passive integral heat sink. LED module and drivers are replaceable and upgradable. Standard diffuser for visual comfort and to eliminate LED source visibility. A variety of mounting options are available.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. See mounting and color pages for standard finishes. Interior is Matte White unless specified. Custom Color interior finish available.

ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 80+. Higher CRI, R9 and custom LED configurations are available; consult factory. Variety of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Fixtures constructed of machined and formed aluminum and door with lens option available. Carbon gasket for optimal thermal management.

CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.

SERIES SIZES

EP1414GV



CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

HM / AT / PM

HANG STRAIGHT / ALL THREAD / PENDANT



EP1414GV SHOWN WITH RDC5PM

CD

CORD / CABLE MOUNT



EP1414GV SHOWN WITH RDC5CD

CM

CORD MOUNT



EP1414GV SHOWN WITH RDC5CM


DOORS

DR14B - 14" Ø

LENSES

S0 - SOLITE™ LENS

FO - WHITE OPTICAL LENS



EP1414GV SHOWN WITH DR14BFO





14" EXPRESS PENDANT


DAMP LOCATION

DOMO SHADES / PHOTOMETRIC DATA

DECORATIVE

EP1414GV-55L-35K-EX-TF2-MWI

CANDLEPOWER CURVE



Delivered Lumens: **3,410**
 Luminaire Watts: **39**
 LER: **87.44**

INTENSITY

0.00°	0.00°
0.00°	1,993
5.00°	2,004
10.00°	1,981
15.00°	1,919
20.00°	1,836
30.00°	1,646
40.00°	958
50.00°	407
60.00°	275
70.00°	161
80.00°	56
90.00°	1

CP at 0deg (Nadir): **1,993**
 CRI: **85+**

ZONAL LUMENS

0° - 10°	191	6%
0° - 20°	722	21%
0° - 30°	1,516	44%
0° - 40°	2,345	69%
0° - 60°	3,072	90%
0° - 80°	3,391	99%
0° - 90°	3,410	100%
Total	3,410	100%

Beam Angle: **78**
 Spacing Ratio: **1.21**

SINGLE UNIT: PERFORMANCE
 INITIAL FOOTCANDLES
 BASED ON IES BEAM ANGLE

Mounting Height AFF	FC at Center on Floor	Beam Diameter	FC at Beam Edge
6.0'	55 fc	9.9'	26 fc
8.0'	31 fc	13.2'	15 fc
10.0'	20 fc	16.5'	9 fc
12.0'	14 fc	19.8'	7 fc
14.0'	10 fc	23.0'	5 fc
16.0'	8 fc	26.3'	4 fc
20.0'	5 fc	32.9'	2 fc
24.0'	3 fc	39.5'	2 fc

MULTIPLE UNITS: PERFORMANCE
 80/50/20% REFLECTANCES
 INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT

Ceiling Height	Fixture Spacing	RCR 2		RCR 4	
		FC *	W/Sq. Ft.	FC *	W/Sq. Ft.
14'	12'*	23	0.28	19	0.28
18'	14'**	18	0.21	9	0.14
22'	16'***	11	0.13	13	0.18
Delivered Illuminance Rating: (DIR)		83 FC per W/Sq. Ft.		69 FC per W/Sq. Ft.	
† Suspension Length Square rooms used for multiple units: - RCR 2: Length & Width = Ceiling Ht. - 4.5' x 5.00 - RCR 4: Length & Width = Ceiling Ht. - 4.5' x 2.50 * Average Footcandles at 2.5' Above Floor ** Exceeds spacing criteria by 4% *** Exceeds spacing criteria by -14% **** Exceeds spacing criteria by -24%					

Lamp Multiplier: 15L x 0.265, 27L x 0.491, 37L x 0.679
 CCT Multiplier: 27K x 0.971, 30K x 0.985, 40K x 1.03



MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION. NOTE: THIS IS TYPICAL OF SPEC LUME SPECIFICATION FOR PENDANT MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.



CEILING MOUNTING

<p>RDC5 - SMALL DRIVER CANOPY (STANDARD) MOUNTS TO 4" OCTO J-BOX</p> <p>CP13 - LARGE DRIVER CANOPY</p>	<p>HM* HANG STRAIGHT 45° SWIVEL 1/2" STEM - 3/8" NPT</p> <p>ORDER: HM (Length) SPECIFY LENGTH: HM3 - 3" HM24 - 24" HM6 - 6" HM36 - 36" HM12 - 12" HM48 - 48" HM18 - 18" HM72 - 72" HMLC(XX) Custom Length (Specify in Inches)</p>	<p>AT** HANG STRAIGHT ALL THREAD 45° SWIVEL 1/2" STEM - 1/4" IP</p> <p>ORDER: AT (Length) SPECIFY LENGTH: AT12 - 12" AT48 - 48" AT24 - 24" AT60 - 60" AT36 - 36" AT72 - 72"</p> <p><small>FIELD-CUT THREADED PIPE FIELD-CUT HESSEID CUT PIPE COVER - 3/4" SHORTER THAN THREADED PIPE SLIP PIPE COVER OVER THREADED PIPE</small></p>	<p>PM* RIGID PENDANT MOUNT RIGID 1/2" STEM - 3/8" NPT</p> <p>ORDER: PM (Length) SPECIFY LENGTH: PM3 - 3" PM24 - 24" PM6 - 6" PM36 - 36" PM12 - 12" PM48 - 48" PM18 - 18" PM72 - 72" PMLLC(XX) Custom Length (Specify in Inches)</p>	<p>CD CORD / CABLE MOUNT SJ CORD WITH 1/16 SS CABLE</p> <p>ORDER: CD (Length) SPECIFY LENGTH: CD36 - 36" CD72 - 72" CD144 - 144" CDLC(XX) Custom Length (Specify in Inches)</p>	<p>CM CORD MOUNT SJ CORD WITH STRAIN RELIEF</p> <p>ORDER: CM (Length) SPECIFY LENGTH: CM36 - 36" CM72 - 72" CM144 - 144" CMLC(XX) Custom Length (Specify in Inches)</p>
--	--	--	--	--	--

*MAXIMUM ONE PIECE STEM LENGTH IS 72". **MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS. **ORDER IN 12" INCREMENTS, ODD SIZES MAY BE FIELD CUT

EMERGENCY BATTERY OPTIONS

EMCR - LARGE DRIVER CANOPY FOR 10W EMERGENCY BATTERY (FOR ROUND CEILING MOUNT TYPES)

REMOTE EMERGENCY BATTERY OPTIONS

<p>EMRM* - 7W REMOTE EMERGENCY BATTERY (50" MAX)</p> <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>1.3</td> <td>12.6</td> <td>13.0</td> </tr> </tbody> </table>	A	B	C	1.3	12.6	13.0	<p>EMEN* - 7W REMOTE EMERGENCY BATTERY WITH ENCLOSURE (50" MAX)</p> <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>2.0</td> <td>17.0</td> <td>6.2</td> </tr> </tbody> </table>	A	B	C	2.0	17.0	6.2
A	B	C											
1.3	12.6	13.0											
A	B	C											
2.0	17.0	6.2											

*OTHER EM BATTERY SIZES AVAILABLE, CONSULT FACTORY

CORD OPTIONS

STANDARD VINYL CORDS

DECORATIVE BRAIDED COLOR CORDS

