



**DODGER PENDANT**  
**DAMP LOCATION**  
 GV SERIES

DECORATIVE

PROJECT: \_\_\_\_\_

QUANTITY: \_\_\_\_\_ TYPE: \_\_\_\_\_



PAC0624GV  
 MW - Matte White



PAC0609GV  
 BZ - Bronze



PAC0820GV  
 CO - Copper Metallic



PAC0810GV  
 PT - Platinum Silver



PAC0618GV  
 MB - Matte Black

SERIES	LUMENS <sup>1</sup>	CCT	DRIVER / DIMMING <sup>2</sup>	OPTIONS <sup>3</sup>	MOUNTING <sup>4</sup>	FINISH <sup>8</sup>	OPTIONAL LOWER LENS
PAC0609GV PAC0618GV PAC0624GV PAC0810GV PAC0820GV	15L 1500 Lm 27L 2700 Lm	27K 2700K 30K 3000K 35K 3500K 40K 4000K	EX Electronic Driver, 120V/277V DO10X 1% 0-10V, 120V/277V DS2W1 ELV/MLV, 120V	FS Fusing	RDC5 <sup>5</sup> Small Driver Canopy HM_6 Hang Straight AT_6 Hang Straight All Thread PM_6 Rigid Pendant Mount CD_6 Cord / Cable Mount CM_6 Cord Mount EMCR <sup>7</sup> 10W Canopy Mounted EM EMRM 7W Remote EM EMEN 7W Remote with Enclosure	MW <sup>9</sup> Matte White MB <sup>9</sup> Matte Black PT <sup>9</sup> Platinum Silver CC Custom Color	FG6 6" Frosted Lens FG8 8" Frosted Lens

EXAMPLE: PAC0618GV15L27KEX/RDC5CD36PTFG6

**NOTES:**  
 1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 See Product Options Page for Details  
 4 See Mounting Page for Details on Components and Finishes 5 Required for Driver 6 Specify Length in Inches: See Mounting Page for Available Lengths  
 7 EMCR Replaces RDC5 8 Reference Color Sheet Located on Product Webpage for Full List of Available Colors 9 Standard Finishes






# DODGER PENDANT DAMP LOCATION GV SERIES

DECORATIVE

## HOUSING DIMENSIONS



Dimensioned with PAC0609GV

SERIES	A	B
PAC0609GV	6.1	9.3
PAC0618GV	6.1	18.4
PAC0624GV	6.1	24.3
PAC0810GV	8.1	10.3
PAC0820GV	8.1	20.5

PART NUMBER	LUMENS / WATTAGE DATA			
	SOURCE LUMENS <sup>1</sup>	DELIVERED LUMENS <sup>2</sup>	SYSTEM WATTS	LPW
PAC0609LEDGV15L	1500	808	10	81
PAC0609LEDGV27L	2700	1418	19	75

<sup>1</sup> Nominal Source Lumens at 35K    <sup>2</sup> Nominal Delivered Lumens at 35K

### APPLICATION

Dodger Pendant originally designed for LA Dodgers Stadium Remodel. Inner matte white acrylic glows softly while outer perforated shade creates visual appeal.

### FEATURES

SpecLume series fixtures offer contemporary style with functional luminaire performance. Fixtures are designed and manufactured in our factory. The Dodger Pendant evokes 1930's luminaire design with modern materials. The wide range of sizes allows for a creative use of these pendants. Top and bottom of fixture are nicely finished with beautifully spun aluminum end caps. LED module and drivers are replaceable and upgradable. LED Driver in canopy for thermal management. A variety of sizes, finishes and mounting options are available.

### FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. See mounting and color pages for standard finishes.

### ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 80+. Higher CRI, R9 and custom LED configurations are available; consult factory. Variety of electronic 120V/277V and dimming drivers.

### CONSTRUCTION

Fixture fabricated from formed and spun aluminum. Opal acrylic inner diffuser. Carbon gasket for optimal thermal management.

### CODE COMPLIANCE

BAA Compliant. ETL listed for damp locations. Manufactured and tested to UL standards No. 1598/8750.

## SERIES SIZES

PAC0609GV



PAC0618GV



PAC0624GV



PAC0810GV



PAC0820GV



## CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

### HM / AT / PM

HANG STRAIGHT / ALL THREAD / PENDANT



PAC0609GV SHOWN WITH RDC5PM

### CD

CORD / CABLE MOUNT



PAC0609GV SHOWN WITH RDC5CD

### CM

CORD MOUNT



PAC0609GV SHOWN WITH RDC5CM





# DODGER PENDANT

## DAMP LOCATION

### GV SERIES / PHOTOMETRIC DATA

DECORATIVE

PAC0810GV 27L 35K xx FG8

CANDLEPOWER CURVE TEST SP-00968	INTENSITY CANDELA 0° AZIMUTH	ZONAL LUMENS		SINGLE UNIT: PERFORMANCE INITIAL FOOTCANDLES BASED ON IES BEAM ANGLE				MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT									
		0° - 10°	0° - 20°	0° - 30°	0° - 40°	0° - 60°	0° - 80°	0° - 90°	Total	Mounting Height AFF	FC at Center on Floor	Beam Diameter	FC at Beam Edge	Ceiling Height	Fixture Spacing	RCR 2	
	0.00°	721	0° - 10°	68	5%	6.5'	17 fc	7.4'	6 fc	9'	4'	79	1.23	46	0.90		
	5.00°	718	0° - 20°	244	17%	7.5'	13 fc	8.5'	4 fc	12'	6'	33	0.52	19	0.38		
	10.00°	694	0° - 30°	448	32%	8.5'	10 fc	9.7'	3 fc	16'	8'	20	0.31	16	0.31		
	15.00°	642	0° - 40°	636	45%	10.0'	7 fc	11.4'	2 fc	Delivered Illuminance Rating: (DIR)							
	20.00°	551	0° - 60°	960	68%	12.0'	5 fc	13.7'	2 fc	64 FC per W/Sq. Ft.      51 FC per W/Sq. Ft.							
	30.00°	355	0° - 80°	1,173	83%	14.0'	4 fc	15.9'	1 fc	1' Suspension Length							
	40.00°	258	0° - 90°	1,241	88%	16.0'	3 fc	18.2'	1 fc	Square rooms used for multiple units:							
	50.00°	196	Total	1,418	100%	20.0'	2 fc	22.8'	1 fc	- RCR 2: Length & Width = Ceiling Ht. - 3.5' x 5.00							
	60.00°	141								- RCR 4: Length & Width = Ceiling Ht. - 3.5' x 2.50							
	70.00°	102								* Average Footcandles at 2.5' Above Floor							
	80.00°	70															
	90.00°	53															

Delivered Lumens: **1,418**  
 Luminaire Watts: **19**  
 LER: **74.63**

CP at 0deg (Nadir): **721**  
 CRI: **80+**

Beam Angle: **59.29**  
 Spacing Ratio: **0.88**

Lumen Multiplier: **15L x 0.57**  
 CCT Multiplier: **27K x 0.97, 30K x 0.99, 40K x 1.03**



# MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.  
NOTE: THIS IS TYPICAL OF SPECTLUME SPECIFICATION FOR PENDANT MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.



## CEILING MOUNTING

<p><b>RDC5</b> - SMALL DRIVER CANOPY (STANDARD) MOUNTS TO 4" OCTO J-BOX</p>	<p><b>HM*</b> HANG STRAIGHT 45° SWIVEL 1/2" STEM - 3/8" NPT</p> <p>ORDER: <b>HM</b> (Length) SPECIFY LENGTH:  <b>HM3</b> - 3"    <b>HM24</b> - 24"  <b>HM6</b> - 6"    <b>HM36</b> - 36"  <b>HM12</b> - 12"    <b>HM48</b> - 48"  <b>HM18</b> - 18"    <b>HM72</b> - 72"  <b>HMLC(XX)</b>          Custom Length          (Specify in Inches)</p>	<p><b>AT**</b> HANG STRAIGHT ALL THREAD 45° SWIVEL 1/2" STEM - 1/4" IP</p> <p>ORDER: <b>AT</b> (Length) SPECIFY LENGTH:  <b>AT12</b> - 12"    <b>AT48</b> - 48"  <b>AT24</b> - 24"    <b>AT60</b> - 60"  <b>AT36</b> - 36"    <b>AT72</b> - 72"  <small>FIELD CUT THREADED PIPE TO LENGTH REQUIRED          CUT TYPE COVER - 1/4" SHORTER THAN THE LENGTH          SLIP TYPE COVER OVER THREADED PIPE</small></p>	<p><b>PM*</b> RIGID PENDANT MOUNT RIGID 1/2" STEM - 3/8" NPT</p> <p>ORDER: <b>PM</b> (Length) SPECIFY LENGTH:  <b>PM3</b> - 3"    <b>PM24</b> - 24"  <b>PM6</b> - 6"    <b>PM36</b> - 36"  <b>PM12</b> - 12"    <b>PM48</b> - 48"  <b>PM18</b> - 18"    <b>PM72</b> - 72"  <b>PMLLC(XX)</b>          Custom Length          (Specify in Inches)</p>	<p><b>CD</b> CORD / CABLE MOUNT SJ CORD WITH 1/16 SS CABLE</p> <p>ORDER: <b>CD</b> (Length) SPECIFY LENGTH:  <b>CD36</b> - 36"  <b>CD72</b> - 72"  <b>CD144</b> - 144"  <b>CDLC(XX)</b>          Custom Length          (Specify in Inches)</p>	<p><b>CM</b> CORD MOUNT SJ CORD WITH STRAIN RELIEF</p> <p>ORDER: <b>CM</b> (Length) SPECIFY LENGTH:  <b>CM36</b> - 36"  <b>CM72</b> - 72"  <b>CM144</b> - 144"  <b>CMLC(XX)</b>          Custom Length          (Specify in Inches)</p>
---	---	---	---	---	---

\*MAXIMUM ONE PIECE STEM LENGTH IS 72". \*\*MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS.

## EMERGENCY BATTERY OPTIONS

**EMCR** - LARGE DRIVER CANOPY FOR TOW EMERGENCY BATTERY (FOR ROUND CEILING MOUNT TYPES)

## REMOTE EMERGENCY BATTERY OPTIONS

<p><b>EMRM*</b> - 7W REMOTE EMERGENCY BATTERY (50' MAX)</p> <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>1.3</td> <td>12.6</td> <td>13.0</td> </tr> </tbody> </table>	A	B	C	1.3	12.6	13.0	<p><b>EMEN*</b> - 7W REMOTE EMERGENCY BATTERY WITH ENCLOSURE (50' MAX)</p> <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>2.0</td> <td>17.0</td> <td>6.2</td> </tr> </tbody> </table>	A	B	C	2.0	17.0	6.2
A	B	C											
1.3	12.6	13.0											
A	B	C											
2.0	17.0	6.2											

\*OTHER EM BATTERY SIZES AVAILABLE. CONSULT FACTORY

